

AT SERIES

High-end plug & play LED TV



AT SERIES

- Mirror server function
- Touch screen
- Electric rising & lowering available
- Easy to use with plug-n-play design
- Support WIFI, 4G, network control
- Support remote control
- IP65 for outdoor version
- Support USB, HDMI input
- Support multiple video format



Front Access



Height Adjustable



Rental



Ultra Slim



Noise Free



High Definition

FEATURES



Multiple installation

SPECIFICATIONS

Parameter	Unit	AT1.9i	AT2.5i	AT1.9	AT2.5
Pixel pitch	mm	1.995	2.571	1.995	2.571
Brightness	nits	800	1000	2500-3000	3000-4000
Pixel configuration	R/G/B	SMD 3 in 1			
Colour temperature	deg.K	6500			
Viewing angle-Horizontal (50% brightness)	deg.	160 (+80/-80)			
Viewing angle-Vertical (50% brightness)	deg.	140 (+70/-70)			
Recommended minimum viewing distance	m	1.9	2.5	1.9	2.5
Panel width	mm	2355		2385	
Panel height	mm	1348		1408	
Panel depth	mm	90		105	
Panel area	m ²	3.1745		3.3581	
Panel material		Alloy Aluminum			
Panel weight	Kg	120		180	
Ingress protection (front/rear)	IP	41/30		65/54	
Pixel matrix per panel		1152x648	896x504	1152x648	896x504
Brightness control		255			
Digital processing	bit	14			
Frame rate	Hertz	50~60			
Display refresh rate	Hertz	2880			
Input voltage	VAC	100~240			
Input power frequency	Hertz	50~60			
Input power (Max.)	W/m ²	536	504	473	473
Input power (Avg.)	W/m ²	187	176	165	165
Operating temperature range	deg.C	-10~+40			
Lifetime (50% brightness)	Hour	100,000			