

iMeeting SERIES

Intelligent meeting LED TV



iMeeting SERIES

- Display size 108", 136", 162", 16:9 ratio
- Integrated display control, intelligent system, audio and video
- High refresh, high grayscale, wide color gamut
- Scan code to LED screen, free annotation
- Optional windows and andriod dual system



Front Access



Light Weight



High Definition



Ultra Slim



Noise Free

CE ETL RoHS EMC



FEATURES



Teleconference



Various installation

SPECIFICATIONS

Parameter	Unit	iMeeting LED Screen								
		iMeeting0.9			iMeeting1.2			iMeeting1.5		
Pixel pitch	mm	108.4	135.5	162.6	108.4	135.5	162.6	108.4	135.5	162.6
Display size	inch	108.4	135.5	162.6	108.4	135.5	162.6	108.4	135.5	162.6
Brightness	nits	500			700			800		
Pixel configuration	R/G/B	SMD Mini								
Colourtemperature	deg.K	6500								
Viewingangle-Horizontal(50% brightness)	deg.	160 (+80/-80)								
Viewingangle-Vertical (50% brightness)	deg.	160 (+80/-80)								
Recommendedminimumviewingdistance	m	0.9			1.2			1.5		
Panel width	mm	2419	3019	3619	2419	3019	3619	2419	3019	3619
Panel height	mm	1460	1797	2134.5	1460	1797	2134.5	1460	1797	2134.5
Panel depth	mm	45.5								
Panel area	m ²	3.53	5.4	7.7	3.53	5.4	7.7	3.53	5.4	7.7
Panel material		AlloyAluminum								
Panel weight	Kg	136	196	286	136	196	286	136	196	286
Ingressprotection(front/rear)	IP	30/30								
Pixel matrix per panel		2560x1440	3200x1800	3840x2160	1920x1080	2400x1350	2880x1620	1536x864	1920x1080	2304x1296
Brightnesscontrol		255								
Digital processing	bit	14bit	13bit	13bit	14bit	14bit	14bit	14bit	14bit	14bit
Frame rate	Hertz	50~60								
Display refresh rate	Hertz	3840	2880	2880	3840	3840	3840	3840	3840	3840
Input voltage	VAC	100~240								
Input power frequency	Hertz	50~60								
Input power (Max.)	W/Set	2100	3300	4700	2000	3200	4500	2100	3300	4700
Input power (Avg.)	W/Set	735	1200	1700	700	1120	1600	735	1200	1700
Operating temperature range	deg.C	-10~+40								
Lifetime (50% brightness)	Hour	100,000								