




## Conductivity Electrodes


Order No	Measurement range	0-20mS/cm
<b>CON-2710</b>	Work Temperature	0-80°C
	Working Principle	2 poles
	Constant	1±0.2
	Plate Type	Black Platinum
	Body	Glass
	Size(mm)	φ12x120
	Cable(m)	1.0
	Connector	BNC/MiniDin
	Sample Temperature	10KΩ/30KΩ/PT100





Order No	Measurement range	0-2000μS/cm
<b>CON-2711</b>	Work Temperature	0-80°C
	Working Principle	2 poles
	Constant	1±0.2
	Plate Type	Bright Platinum
	Body	Glass
	Size(mm)	φ12x120
	Cable(m)	1.0
	Connector	BNC/MiniDin
	Sample Temperature	10KΩ/30KΩ/PT100


Order No.	Measurement range	0-200mS/cm
<b>CON-2712</b>	Work Temperature	0-80°C
	Working Principle	2 poles
	Constant	10±2
	Plate Type	Black Platinum
	Body	Glass
	Size(mm)	φ12x120
	Cable(m)	1.0
	Connector	BNC/MiniDin
	Sample Temperature	10KΩ/30KΩ/PT100




Order No.	Measurement range	0-200μS/cm
<b>CON-2713</b>	Work Temperature	0-80°C
	Working Principle	2 poles
	Constant	0.1±0.02
	Plate Type	Bright Platinum
	Body	Glass
	Size(mm)	φ12x120
	Cable(m)	1.0
	Connector	BNC/MiniDin
	Sample Temperature	10KΩ/30KΩ/PT100

Order No.	Measurement range	0.01-500mS/cm
<b>CON-4714</b>	Work Temperature	0-100°C
	Working Principle	4 poles
	Constant	0.6±0.2
	Plate Type	Bright Platinum
	Body	Glass
	Size(mm)	φ12x120
	Cable(m)	1.0
	Connector	BNC/MiniDin
	Sample Temperature	10KΩ/30KΩ/PT100





Order No.	Measurement range	0.01-1000mS/cm
<b>CON-4722</b>	Work Temperature	0-80°C
	Working Principle	4 poles
	Constant	0.6±0.2
	Plate Type	Graphite
	Body	PC
	Size(mm)	φ12x120
	Cable(m)	1.0
	Connector	BNC/MiniDin
	Sample Temperature	10KΩ/30KΩ/PT100

## Conductivity Electrodes


Order No.	Measurement range	0-20mS/cm
<b>CON-2720</b>	Work Temperature	0-80°C
	Working Principle	2 poles
	Constant	1±0.2
	Plate Type	Graphite (Black)
	Body	PC
	Size(mm)	φ12x120
	Cable(m)	1.0
	Connector	BNC/MiniDin
	Sample Temperature	10KΩ/30KΩ/PT100




Order No.	Measurement range	0-2000μS/cm
<b>CON-2721</b>	Work Temperature	0-80°C
	Working Principle	2 poles
	Constant	1±0.2
	Plate Type	Graphite
	Body	PC
	Size(mm)	φ12x120
	Cable(m)	1.0
	Connector	BNC/MiniDin
	Sample Temperature	10KΩ/30KΩ/PT100

Order No.	Measurement range	0-500μS/cm
<b>CON-2730</b>	Work Temperature	0-100°C
	Working Principle	2 poles
	Constant	0.1±0.02
	Plate Type	Titanium Alloy
	Body	316L SS
	Size(mm)	φ12x120
	Cable(m)	1.0
	Connector	BNC/MiniDin
	Sample Temperature	10KΩ/30KΩ/PT100




Order No.	Measurement range	0-2 μ S/cm
<b>CON-2731</b>	Work Temperature	0-100°C
	Working Principle	2 poles
	Constant	0.01±0.02
	Plate Type	Titanium Alloy
	Body	316L SS
	Size(mm)	φ30x155
	Cable(m)	1m
	Connector	Customized
	Sample Temperature	10KΩ/30KΩ/PT100



Order No.	Measurement range	1-2000μS/cm
<b>CON-2751</b>	Work Temperature	0-80°C
	Working Principle	2 poles
	Constant	1±0.2
	Plate Type	Titanium Alloy
	Body	ABS
	Size(mm)	φ30x170
	Cable(m)	3.0
	Connector	Customized
	Sample Temperature	10KΩ/30KΩ/PT100



Order No.	Measurement range	0.1-200mS/cm
<b>CON-4752</b>	Work Temperature	0-80°C
	Working Principle	4 poles
	Constant	0.3±0.15
	Plate Type	Titanium Alloy
	Material	ABS
	Size(mm)	φ30x170
	Cable(m)	3.0
	Connector	Customized
	Sample Temperature	10KΩ/30KΩ/PT100