

Input voltage	Output voltage	Output current	Output power	Efficiency	Size
20-35V DC	48V DC	20 Amps	960 Watts	97%	150*127*63mm



### Features


- Design meeting RoHS / CE
- High efficiency: 97% ( @ 24V input )
- Non-isolated between input and output
- Internal capacitor: NCC & NICHICON (high reliability)
- 100% full load burn-in test
- Over load, Over temperature and Over voltage protections
- Waterproof level IP68
- 1 Year warranty

### Applications

- Trucks
- Forklifts
- Buses
- Logging Vehicles
- Electromotor
- Telecommunications
- Boat & Yacht
- LED Marketplaces and so on..

### Model naming method

**WG-24S4820**





Specifications

Model	WG-24S4820		
Input	Rated voltage	V	24
	Voltage range	V	20-35
	Efficiency (type)	%	97 @ 24Vin
Output	Voltage	V	48
	Max. rated current	A	20
	Max. rated power	W	960
	Voltage regulation	%	±1
	Load regulation	%	2
	No load loss	mA	60
	Ripple & noise	mVp-p	280
Environment	Working temperature	°c	-40 ~ +80
	Working humidity	RH	10% ~ 90%
	Storage temperature	°c	-40 ~ +100
Function	Short circuit protection		NO
	Over current protection	A	YES
	Waterproof		IP68
	Over temperature protection		YES
	Over voltage protection		YES
Mechanical	Weight	g	1500
	Size	mm	150*127*63
Other	Cooling		Free air convection
	Packaging		Brown box





szwengao

# DC-DC Converter Specification

Model No.:WG-24S4820

## Dimension



### Shenzhen Wengao Electronic Co., Ltd

A: 2/F A, Bldg.A2, Anle Ind. Hangcheng RD., Xixiang Street, Baoan Dist., Shenzhen, China 518102

T: +86 755 29418061    F: +86 755 29418061    E: [info@wengaoelec.com](mailto:info@wengaoelec.com)    W: [www.wengaoelec.com](http://www.wengaoelec.com)