

LED Display Maintenance Methods

1. Switching Sequences

(1) **Turn on the Display:** Turn on the computer first, then turn on the LED display.

(2) **Turn off the Display:** Turn off the LED display first, and then turn off the computer. (Turning off the computer first without turning off the display will cause the screen to have a high bright dot and burn the IC, which will have serious consequences.)

2. Turn on/off the LED Display at intervals of more than 5 minutes.

3. Once the computer is in the engineering control software, the display can be turned on and energized.

4. Avoid opening the display in full yellow, since the impulse current of the system is the highest.

5. Avoid opening the display in a uncontrolled state, since the impulse current of the system is the highest.

(1) Computers are not programmed to access engineering control software, etc.

(2) The computer is not powered on.

(3) Power to the control section is not turned on.

6. If the computer system case is energized, the display cannot be turned on.

7. It is recommended that the LED display rest time is more than 2 hours per day, and the LED display is used at least once a week during the rainy season. Generally, the display should be turned on at least once a month and lit for more than 2 hours.

8. When the environmental temperature is too high or the heat dissipation condition is not well, you should be careful not to open the display for a long time.

9. When a part of the display appears to be very bright, you should pay attention to turn off the display in a timely manner, and should not open the display for a long time in this state.

10. The power switch of the display is often tripped, you should check the display or replace the power switch in time. When you can not find the display failure, you should notify the service department of our company to help solve the problem.

11. Regularly check the firmness of the hitch. If there is any looseness, pay attention to timely adjustment, and if necessary, notify our company to re-strengthen or update the hangers.

12. According to the environmental conditions in which the display body and control part are located, avoid insect bites and place anti-rodent medicine if necessary.