



Nantong Yu Ru Engineering Materials Co., LTD.,

Transparent waterproof adhesive

Product introduction

Transparent waterproof glue is acrylic emulsion as the base material mixed with various additives prepared by the new high-grade waterproof material, colorless, transparent waterproof glue.

Product features

- 1, Coating colorless, transparent, coating will not destroy the original wall decoration effect, will not appear yellow, dust, dust and other phenomena.
- 2, Heat resistance, uv resistance, ozone resistance, acid and alkali resistance, weather resistance to adapt to a wide range; Add special modifier, surfactant.
- 3, The film has good film forming, strong adhesion, toughness can resist the stress generated by the deformation and cracking of the base.
- 4, With water as the dispersion medium, non-combustible, tasteless, no pollution to the environment, is an environmental protection product.
- 5, Cold construction, safe operation, convenient construction, can be directly sprayed, painted, brush, scraping on the wall.
- 6, Film with porous permeability, suitable for the southern humid climate of heat evaporation, and not agitating.
- 7, Less consumption, cheap cost.

Scope of application

- 1, All kinds of building wall wall leakage waterproof repair, wall brick, marble, granite, cement based inorganic materials such as corrosion, waterproof impermeable coating film.
- 2, Cement, ceramics, glass and other inorganic materials of anti-corrosion, waterproof coating.
- 3, Surface bottom, new and old roof walls, new and old basement, toilet, bath, parking platform, parking platform, swimming pool, civil air defense engineering impermeable moistureproof, Special-shaped structure, complex parts of the surface waterproof (mildew) anticorrosive.

Construction method

- 1, The surface must be smooth, solid, clean, no oil, dust and other loose animals.
- 2, the obvious gap and trachoma must be blocked with cement mortar, smooth, sharp edge should be removed.
- 3, Wet the substrate in advance to no water shall prevail.
- 4, The newly poured concrete should have a certain dry solid curing time to prevent the impact of concrete drying shrinkage.
- 5, The old concrete surface must be washed with clean water, dry after brushing
- 6, Roll, brush, scraping, spraying can be, the amount of film 0.8-1.2kg/square, coating for 2-3 times or more is appropriate.

Technical Parameters

Materials tensile test		
No	Test items	Technical data
1	Water tolerance, 96h	No white
2	Tensile strength , MPa	1.5
3	Elongation at break , %	320
4	Solid content	45
5	PH	7

Matters needing attention:

1. This product is non-flammable and explosive.
- 2, Rain, snow, fog can not be constructed, the temperature of 5 degrees Celsius can not be constructed.
- 3, Stored in 5-35 degrees Celsius in the shade, warranty for 18 months.