



# Attestation of Compliance

Reference No. : LCSB12283055E

Applicant : Gotall Technology (Shenzhen) Co., Ltd.

Address : 420A, Building B1, Fuhai B3 Section, Fuyong Community, Fuyong Street, Bao'an District, Shenzhen, China

Trade Mark : N/A

Product : LED Batten Light

Model(s) : SEE ANNEX I

Tested according to : EN IEC 55015:2019+A11:2020  
EN IEC 61000-3-2:2019+A1:2021  
EN 61000-3-3:2013+A1:2019+A2:2021  
EN IEC 61547:2023

The submitted products have been tested by us with the listed standards.

This Attestation of Compliance is issued according to the council Directive 2014/30/EU, Referred to as the Electromagnetic Compatibility. It confirms that the listed product complies with all essential requirements of the EMC directive and applies only to the sample and its technical documentation submitted to Shenzhen Southern LCS Compliance Testing Laboratory Ltd. for testing.

After preparation of the necessary technical documentation as well as the EC conformity declaration the required CE marking can be affixed on the product. Other relevant Directives have to be observed.



Date of issue: January 16, 2024

.....  
Manager



**ANNEX I:**



**Reference No. : LCSB12283055E**

**Model(s) :**

Model	Size(mm)	Input voltage	Power(W)	CCT
BA008-12C028-XXXXYX BA008-12C033-XXXXYX BA008-12C038-XXXXYX BA008-12C045-XXXXYX	1212*55*62 mm	AC 200-240V	28/33/38/45 Emergency discharge:3W3H	3000K 4000K 5000K
BA008-12C028-XXXXYX BA008-12C033-XXXXYX BA008-12C038-XXXXYX BA008-12C045-XXXXYX	1212*55*62 mm		28/33/38/45 Emergency discharge:4W2H	
BA008-15C028-XXXXYX BA008-15C033-XXXXYX BA008-15C038-XXXXYX BA008-15C045-XXXXYX BA008-15C055-XXXXYX	1512*55*62 mm	AC 200-240V	28/38 /45 /55 Emergency discharge:5W2H	3000K 4000K 5000K
BA008-15C028-XXXXYX BA008-15C033-XXXXYX BA008-15C038-XXXXYX BA008-15C045-XXXXYX BA008-15C055-XXXXYX	1512*55*62 mm		28/38 /45 /55 Emergency discharge:4W2H	
BA009-12C028-XXXXYX BA009-12C033-XXXXYX BA009-12C038-XXXXYX BA009-12C045-XXXXYX	1200*55*66 mm	AC 200-240V	28/33/38/45 Emergency discharge:3W3H	3000K 4000K 5000K
BA009-12C028-XXXXYX BA009-12C033-XXXXYX BA009-12C038-XXXXYX BA009-12C045-XXXXYX	1200*55*66 mm		28/33/38/45 Emergency discharge:4W2H	
BA009-15C028-XXXXYX BA009-15C033-XXXXYX BA009-15C038-XXXXYX BA009-15C045-XXXXYX BA009-15C055-XXXXYX	1500*55*66 mm	AC 200-240V	28/38 /45 /55 Emergency discharge:5W2H	3000K 4000K 5000K
BA009-15C028-XXXXYX BA009-15C033-XXXXYX BA009-15C038-XXXXYX BA009-15C045-XXXXYX BA009-15C050-XXXXYX BA009-15C055-XXXXYX	1500*55*66 mm		28/38 /45 /50 /55 Emergency discharge:4W2H	
BA010-12C028-XXXXYX BA010-12C033-XXXXYX BA010-12C038-XXXXYX BA010-12C045-XXXXYX	1200*57*63 mm	AC 200-240V	28/33/38/45 Emergency discharge:3W3H	3000K 4000K 5000K
BA010-12C028-XXXXYX BA010-12C033-XXXXYX BA010-12C038-XXXXYX BA010-12C045-XXXXYX	1200*57*63 mm		28/33/38/45 Emergency discharge:4W2H	3000K 4000K 5000K
BA010-15C028-XXXXYX BA010-15C033-XXXXYX BA010-15C038-XXXXYX BA010-15C045-XXXXYX	1500*57*63 mm	AC 200-240V	28/38 /45 /55 Emergency discharge:5W2H	





BA010-15C055-XXXXYX			
BA010-15C028-XXXXYX BA010-15C033-XXXXYX BA010-15C038-XXXXYX BA010-15C045-XXXXYX BA010-15C055-XXXXYX	1500*57*63 mm		28/38 /45 /55 Emergency discharge:4W2H

Remark: Each product number is followed by five XXXXX. In order from left to right, the first X represents the color temperature of the product, the second X represents the brand name of the power supply used, and the third X represents the light efficiency of the product. The last two XX products are serial number XXXYX. In order from left to right, the first X represents the color temperature of the product, the second X represents the brand name of the power supply used, the third X represents the light efficiency of the product, Y represents the emergency, and the last X: Product serial number. The X17D X27 X28 power supply and emergency power supply are assembled in the base.

