

Primer sealant coupling agent

Excellent coupling agent, good compatibility with materials, can form a protective screen to ultraviolet rays

Features And Usage

1. Primer is kind of coupling agent with outstanding performance
2. Having good compatibility with glass, painting metal, stainless steel, ceramics and wood and so on
3. Good supporting the cohesion of polyurethane
4. Can form a protective screen to ultraviolet rays on glasses
5. Primer is better to use with cleaner

Data Table

Model Number	Primer
Main Raw Material	reactivity polyurethane, mixture
Color	black
Density	1.0g/cm ³ (20°C)
touch dry time	2-3Min
viscosity	1200cps

Package and Storage

Package

100ml/bottle

250ml/bottle

Color: Black

Storage

Keep in cool and ventilative place

Temperature≤25°C, humidity≤50%RH

Attention of operation

Wear suitable protective clothing, gloves and eye/face Protection. After contact with skin, wash immediately with plenty of water and soap. In case of accident or if you feel unwell, seek medical advice immediately

Warranty and Liability

All product properties and application details based on information are ensured to be reliable and accurate. But you still need to test its property and safety before application. All advices we supply can't be applied in any circumstances.

CHEMP Udon't make assurance of any other applications outside the specification until CHEMP U supply a special written guarantee.

CHEMP Uis only responsible to replace or refund if this product is defective within the warranty period stated above.

CHEMPU makes it clear that will not take responsible for any accidents.