

# QY-F5121



## Industrial Touch Monitor



## Product Features:

- 12.1 inch true color liquid CRYSTAL display
- Front panel IP65 water and dust proof
- Support Flush mount and wall mount (VESA standard)
- Two interface options (1\*HDMI+1\*VGA or 1\*DVI+1\*VGA)
- Touch screen type options (USB touch screen or RS-232 touch screen)

## Specification:

<b>QY-F5121</b>			
<b>I/O interfaces</b>	<b>1*HDMI+1*VGA 1*DVI+1*VGA</b>		
<b>LCD Screen</b>	<b>Size</b>	<b>12.1 inch</b>	
	<b>Resolution</b>	<b>1024*768</b>	
	<b>Brightness</b>	<b>350</b>	
	<b>Contrast</b>	<b>800/1</b>	
	<b>Largest Color</b>	<b>16M</b>	
	<b>Pixel Distance</b>	<b>0.297 X 0.297</b>	
	<b>Largest Perspective</b>	<b>(H)160 / (V)160</b>	
<b>Touch Screen</b>	<b>Type</b>	<b>Capacitive</b>	<b>Resistive</b>
	<b>Port</b>	<b>USB / RS-232 (Standard USB touch screen)</b>	
	<b>Touch Life</b>	<b>50 million times</b>	
	<b>Response Time</b>	<b>&lt; 5ms</b>	
	<b>Constant Temperature Pressure Test</b>	<b>85°C/90%RH/1000hrs</b>	
<b>Mechanism Parameters</b>	<b>Box</b>	<b>Sheet metal box structure</b>	
	<b>Power</b>	<b>DC 12V (DC 9-36V optional)</b>	
	<b>Installation</b>	<b>Wall mount and flush mount</b>	
	<b>Total Size</b>	<b>238.3mm*298.3mm*57mm</b>	
<b>Environmental Parameters</b>	<b>Working Temperature</b>	<b>0°C - 60°C</b>	
	<b>Storage Temperature</b>	<b>-20°C - 70°C</b>	

# Selection Guide:

USB touch screen	1*HDMI+1*VGA+1*USB touch line
	1*DVI+1*VGA+1*USB touch line
RS-232 touch screen	1*HDMI+1*VGA+1*RS-232 touch line
	1*DVI+1*VGA+1*RS-232 touch line

## USB Touch Screen:



## RS-232 Touch Screen:



# Size Drawing:

