

Model name (2NB)	Single	Frequency	Rated	Rated Volatge		Rated	Max	Rated	Rated	Noise	Weight	
	Double		Power			Current		Airflow	let Pressu			tlet Pressu
	Stage		KW			A		m3/h	mbar			mbar
		HZ		V								
210 H06	Single	50	0.2	200-240Δ	345-415Y							
		60	0.23	220-275Δ	380-480Y							
210 H16	single	50	0.4	200-240Δ	345-415Y	2.6Δ/1.5Y	80	-120	130	53	10	
		60	0.5	220-275Δ	380-480Y	2.6Δ/1.5Y	98	-150	160	56		
220 H26	double	50	0.7	200-240Δ	345-415Y	3.8Δ/2.2Y	88	-210	240	55	16	
		60	0.83	220-275Δ	380-480Y	3.75Δ/2.15Y	103	-250	250	61		
230 H16	single	50	0.4	200-240Δ	345-415Y	2.6Δ/1.5Y	105	-120	130	54	11	
		60	0.5	220-275Δ	380-480Y	2.6Δ/1.5Y	120	-150	155	57		
230 H26	single	50	0.7	200-240Δ	345-415Y	3.8Δ/2.2Y	105	-120	130	54	12	
		60	0.83	220-275Δ	380-480Y	3.8Δ/2.2Y	120	-165	180	57		
310 H06	single	50	0.55	200-240Δ	345-415Y	2.4Δ/1.7Y	100	-120	130	57	11	
		60	0.62	220-275Δ	380-480Y	2.6Δ/1.5Y	120	-120	130	60		
320 H26	double	50	0.85	200-240Δ	345-415Y	4.2Δ/2.4Y	110	-200	230	58	17	
		60	0.95	220-275Δ	380-480Y	4.0Δ/2.3Y	130	-240	240	60		
320 H36	double	50	1.3	200-240Δ	345-415Y	5.7Δ/3.3Y	110	-280	290	58	18	
		60	1.5	220-275Δ	380-480Y	6.0Δ/3.5Y	130	-300	400	60		
330 H06	single	50	0.55	200-240Δ	345-415Y	2.8Δ/1.6Y	140	-60	60	56	12	
		60	0.63	220-275Δ	380-480Y	3.0Δ/1.7Y	165	-50	50	58		
330 H16	single	50	0.7	200-240Δ	345-415Y	3.8Δ/2.2Y	140	-100	100	56	13	
		60	0.83	220-275Δ	380-480Y	3.8Δ/2.2Y	165	-115	100	58		
410 H06	single	50	0.7	200-240Δ	345-415Y	3.8Δ/2.2Y	145	-120	120	63	15	
		60	0.83	220-275Δ	380-480Y	3.75Δ/2.15Y	175	-130	130	64		
410 H16	single	50	0.85	200-240Δ	345-415Y	4.2Δ/2.4Y	145	-160	160	63	17	
		60	0.95	220-275Δ	380-480Y	4.0Δ/2.3Y	175	-160	160	64		
410 H26	single	50	1.3	200-240Δ	345-415Y	6.6Δ/3.8Y	145	-170	200	63	18	
		60	1.5	220-275Δ	380-480Y	6.9Δ/4.0Y	175	-210	220	64		
420 H36	double	50	1.6	200-240Δ	345-415Y	7.5Δ/4.3Y	150	-280	280	66	25	
		60	2.05	220-275Δ	380-480Y	7.6Δ/4.4Y	180	-320	310	69		
420 H46	double	50	2.2	200-240Δ	345-415Y	9.7Δ/5.6Y	150	-330	440	66	27	
		60	2.55	220-275Δ	380-480Y	10Δ/5.8Y	180	-350	420	69		
430 H06	single	50	0.7	200-240Δ	345-415Y	3.8Δ/2.2Y	180	-70	70	64	14	
		60	0.83	220-275Δ	380-480Y	3.8Δ/2.2Y	210	-50	50	65		
430 H16	single	50	0.85	200-240Δ	345-415Y	4.2Δ/2.4Y	180	-120	120	64	17	
		60	0.85	220-275Δ	380-480Y	4.0Δ/2.3Y	210	-90	70	65		

1 / 7 page

Model name (2NB)	Single	Frequency	Rated	Rated Volatge		Rated	Max	Rated	Rated	Noise	Weight	
	Double		Power			Current		Airflow	let Pressu			tlet Pressu
	Stage		KW			A		m3/h	mbar			mbar
		HZ		V								
430 H26	single	50	1.3	200-240Δ	345-415Y	6.6Δ/3.8Y	180	-170	220	64	18	
		60	1.5	220-275Δ	380-480Y	6.9Δ/4.0Y	210	-200	160	65		
510 H06	single	50	0.85	200-240Δ	345-415Y	4.2Δ/2.4Y	210	-110	100	64	20	
		60	0.95	220-275Δ	380-480Y	4.0Δ/2.3Y	255	-80	70	70		
510 H16	single	50	1.3	200-240Δ	345-415Y	6.6Δ/3.8Y	210	-170	170	64	22	
		60	1.5	220-275Δ	380-480Y	6.9Δ/4.0Y	255	-150	140	70		
510 H26	single	50	1.6	200-240Δ	345-415Y	7.5Δ/4.3Y	210	-200	190	64	23	
		60	2.1	220-275Δ	380-480Y	7.6Δ/4.4Y	255	-220	210	70		
510 H36	single	50	2.2	200-240Δ	345-415Y	9.7Δ/5.6Y	210	-220	270	64	26	
		60	2.55	220-275Δ	380-480Y	10.3Δ/6.0Y	255	-260	290	70		
520 H36	double	50	2.2	200-240Δ	345-415Y	9.7Δ/5.6Y	230	-290	360	72	35	
		60	2.55	220-275Δ	380-480Y	10.3Δ/6.0Y	275	-350	330	74		
520 H46	double	50	3	200-240Δ	345-415Y	12.5Δ/7.2Y	230	-340	410	72	39	
		60	3.45	220-275Δ	380-480Y	12.5Δ/7.3Y	275	-380	360	74		
520 H57	double	50	4	345-415Δ	600-720Y	10Δ/5.8Y	230	-390	490	72	44	
		60	4.6	380-480Δ	660-720Y	9.9Δ/5.71Y	275	-410	480	74		
530 H06	single	50	0.85	200-240Δ	345-415Y	4.0Δ/2.3Y	270	-40	40	65	21	
		60	0.95	220-275Δ	380-480Y	4.2Δ/2.4Y	330	-40	40	71		
530 H16	single	50	1.3	200-240Δ	345-415Y	6.6Δ/3.8Y	270	-100	100	65	23	
		60	1.5	220-275Δ	380-480Y	6.9Δ/4.0Y	330	-70	50	71		
530 H26	single	50	1.6	200-240Δ	345-415Y	7.5Δ/4.3Y	270	-150	150	65	24	
		60	2.05	220-275Δ	380-480Y	7.6Δ/4.4Y	330	-150	130	71		
530 H36	single	50	2.2	200-240Δ	345-415Y	9.7Δ/5.6Y	270	-220	230	65	26	
		60	2.55	220-275Δ	380-480Y	10.3Δ/6.0Y	330	-230	210	71		
610 H06	single	50	1.6	200-240Δ	345-415Y	8.5Δ/4.9Y	270	-180	190	67	24	
		60	2.1	220-275Δ	380-480Y	8.8Δ/5.5Y	315	-200	190	70		
610 H16	single	50	2.2	200-240Δ	345-415Y	10Δ/5.6Y	270	-230	250	67	27	
		60	2.5	220-275Δ	380-480Y	10.3Δ/6.5Y	315	-250	270	70		
610 H26	single	50	3	200-240Δ	345-415Y	12.5Δ/7.2Y	270	-280	280	69	32	
		60	3.45	220-275Δ	380-480Y	12.6Δ/7.3Y	315	-260	270	72		
630 H06	single	50	1.6	200-240Δ	345-415Y	8.5Δ/4.9Y	345	-125	125	70	26	
		60	2.05	220-275Δ	380-480Y	8.8Δ/5.5Y	415	-105	130	73		
630 H16	single	50	2.2	200-240Δ	345-415Y	9.7Δ/5.6Y	345	-200	195	70	29	
		60	2.55	220-275Δ	380-480Y	10.3Δ/6.0Y	415	-170	195	73		
630 H26	single	50	3	200-240Δ	345-415Y	12.5Δ/7.2Y	345	-240	220	70	35	
		60	3.45	220-275Δ	380-480Y	12.6Δ/7.3Y	415	-210	220	73		
710 H16	single	50	2.2	200-240Δ	345-415Y	9.7Δ/5.6Y	318	-190	190	69	31	

710 H16	single	60	2.55	220-275Δ	380-480Y	10.3Δ/6.0Y	376	-190	190	72	31
710 H26	single	50	3	200-240Δ	345-415Y	12.5Δ/7.2Y	318	-270	290	69	36
		60	3.45	220-275Δ	380-480Y	12.5Δ/7.3Y	376	-250	230	72	

2 / 7 page

Model name (2NB)	Single	Frequency	Rated	Rated Volatge		Rated	Max	Rated	Rated	Noise	Weight	
	Double		Power			Current		Airflow	let Pressu			tlet Pressu
	Stage		KW			V		A	m3/h			mbar
710 H37	single	50	4	345-415Δ	600-720Y	9.0Δ/5.2Y	318	-290	330	69	40	
		60	4.6	380-480Δ	660-720Y	9.4Δ/5.2Y	376	-330	330	72		
710 H47	single	50	4.3	345-415Δ	600-720Y	9.5Δ/5.5Y	318	-295	335	69	43	
		60	4.8	380-480Δ	660-720Y	9.5Δ/5.5Y	376	-335	335	72		
720 H16	double	50	2.2	200-240Δ	345-415Y	9.7Δ/5.6Y	320	-220	210	73	45	
		60	2.55	220-275Δ	380-480Y	10.3Δ/6.0Y	385	-170	150	76		
720 H26	double	50	3	200-240Δ	345-415Y	12.5Δ/7.2Y	320	-280	260	73	49	
		60	3.45	220-275Δ	380-480Y	12.6Δ/7.3Y	385	-230	200	76		
720 H27	double	50	4	345-415Δ	600-720Y	9.0Δ/5.2Y	320	-355	375	73	53	
		60	4.6	380-480Δ	660-720Y	9.4Δ/5.2Y	385	-345	315	76		
720 H37	double	50	4.3	345-415Δ	600-720Y	10Δ/5.2Y	320	-360	380	73	56	
		60	4.8	380-480Δ	660-720Y	10.4Δ/6.0Y	385	-350	320	76		
720 H47	double	50	5.5	345-415Δ	600-720Y	13.3Δ/7.7Y	320	-440	500	73	70	
		60	6.3	380-480Δ	660-720Y	13.3Δ/7.7Y	385	-440	500	76		
720 H57	double	50	7.5	345-415Δ	600-720Y	16.7Δ/9.6Y	320	-440	570	73	74	
		60	8.6	380-480Δ	660-720Y	17.3Δ/10.0Y	385	-460	660	76		
730 H06	single	50	1.6	200-240Δ	345-415Y	8.5Δ/4.9Y	420	-100	100	70	29	
		60	2.05	220-275Δ	380-480Y	8.8Δ/5.5Y	500	-110	80	73		
730 H16	single	50	2.2	200-240Δ	345-415Y	9.7Δ/5.6Y	420	-170	170	70	32	
		60	2.55	220-275Δ	380-480Y	10.3Δ/6.0Y	500	-160	120	73		
730 H26	single	50	3	200-240Δ	345-415Y	12.5Δ/7.2Y	420	-220	220	70	37	
		60	3.45	220-275Δ	380-480Y	12.6Δ/7.3Y	500	-200	190	73		
730 H37	single	50	4	345-415Δ	600-720Y	9.0Δ/5.2Y	420	-260	310	70	43	
		60	4.6	380-480Δ	660-720Y	9.0Δ/5.2Y	500	-260	280	73		
740 H37	double	50	4.3	345-415Δ	600-720Y	9.0Δ/5.2Y	500	-150	140	74	54	
		60	4.6	380-480Δ	660-720Y	9.0Δ/5.2Y	600	-100	90	78		
740 H47	double	50	5.5	345-415Δ	600-720Y	13.3Δ/7.7Y	500	-240	260	74	69	
		60	6.3	380-480Δ	660-720Y	13.3Δ/7.7Y	600	-210	200	78		
740 H57	double	50	7.5	345-415Δ	600-720Y	16.7Δ/9.6Y	500	-240	320	74	75	
		60	8.6	380-480Δ	660-720Y	16.7Δ/9.6Y	600	-270	300	78		
810 H07	single	50	4.3	345-415Δ	600-720Y	9.5Δ/5.5Y	530	-200	200	70	51	
		60	4.8	380-480Δ	660-720Y	9.5Δ/5.5Y	620	-160	160	74		
810 H17	single	50	5.5	345-415Δ	600-720Y	12.9Δ/7.4Y	530	-300	320	80	62	
		60	6.3	380-480Δ	660-720Y	12.9Δ/7.45Y	620	-320	340	82		
810 H27	single	50	7.5	345-415Δ	600-720Y	16.7Δ/9.6Y	530	-320	380	80	65	
		60	8.6	380-480Δ	660-720Y	17.3Δ/10.0Y	620	-340	400	82		
820 H17	double	50	5.5	345-415Δ	600-720Y	13.3Δ/7.7Y	520	-240	240	74	83	
		60	6.3	380-480Δ	660-720Y	13.3Δ/7.7Y	620	-170	160	78		
820 H27	double	50	7.5	345-415Δ	600-720Y	16.7Δ/9.6Y	520	-400	400	74	88	
		60	8.6	380-480Δ	660-720Y	17.3Δ/10.0Y	620	-360	330	78		
820 H37	double	50	11	345-415Δ	600-720Y	28.0Δ/16.2Y	520	-430	660	74	123	
		60	12.6	380-480Δ	660-720Y	29.0Δ/16.7Y	620	-460	600	78		
820 H47	double	50	15	345-415Δ	600-720Y	32.5Δ/18.8Y	520	-460	670	74	140	
		60	17.3	380-480Δ	660-720Y	34.5Δ/19.9Y	620	-490	750	78		

3 / 7 page

Model name (2NB)	Single	Frequency	Rated	Rated Volatge		Rated	Max	Rated	Rated	Noise	Weight	
	Double		Power			Current		Airflow	let Pressu			tlet Pressu
	Stage		KW			V		A	m3/h			mbar
830 H07	single	50	4	345-415Δ	600-720Y	9.5Δ/5.5Y	700	-150	140	70	57	
		60	4.6	380-480Δ	660-720Y	9.5Δ/5.5Y	840	-90	90	74		
830 H17	single	50	5.5	345-415Δ	600-720Y	12.9Δ/7.4Y	700	-200	180	70	66	
		60	6.3	380-480Δ	660-720Y	12.9Δ/7.45Y	840	-180	180	74		
830 H27	single	50	7.5	345-415Δ	600-720Y	16.7Δ/9.6Y	700	-270	260	70	59	
		60	8.6	380-480Δ	660-720Y	17.3Δ/10.0Y	840	-270	260	74		
840 H17	double	50	5.5	345-415Δ	600-720Y	16.0Δ/9.0Y	870	-180	150	72	83	
		60	6.3	380-480Δ	660-720Y	16.5Δ/9.5Y	1000	-130	100	75		
840 H27	double	50	7.5	345-415Δ	600-720Y	16.7Δ/9.6Y	900	-200	180	74	91	
		60	8.6	380-480Δ	660-720Y	17.3Δ/10.0Y	1050	-150	120	78		
840 H37	double	50	11	345-415Δ	600-720Y	28.0Δ/16.2Y	900	-280	370	74	110	
		60	12.6	380-480Δ	660-720Y	29.0Δ/16.7Y	1050	-310	350	78		
840 H47	double	50	15	345-415Δ	600-720Y	32.0Δ/19.0Y	950	-300	390	74	115	
		60	17.5	380-480Δ	660-720Y	32.0Δ/19.0Y	1150	-330	370	78		
910 H07	single	50	8.5	345-415Δ	600-720Y	18.2Δ/10.5Y	1050	-210	210	74	93	
		60	9.8	380-480Δ	660-720Y	18.2Δ/10.5Y	1250	-180	180	79		
910 H17	single	50	12.5	345-415Δ	600-720Y	28.0Δ/16.2Y	1050	-280	270	74	116	
		60	14.5	380-480Δ	660-720Y	29.0Δ/16.7Y	1250	-270	260	79		
910 H37	single	50	18.5	345-415Δ	600-720Y	37.0Δ/21.0Y	1050	-340	460	74	126	
		60	21.3	380-480Δ	660-720Y	39.0Δ/22.5Y	1250	-380	420	79		
920 H17	double	50	12.5	345-415Δ	600-720Y	28.0Δ/16.2Y	1110	-300	270	74	187	
		60	14.5	380-480Δ	660-720Y	29.0Δ/16.7Y	1310	-220	200	78		

920 H27	double	50	16.5	345-415Δ	600-720Y	35.0Δ/20.0Y	1110	-410	370	74	197
		60	19.0	380-480Δ	660-720Y	36.5Δ/21.0Y	1310	-340	300	78	
920 H37	double	50	20.0	345-415Δ	600-720Y	40.0Δ/23.0Y	1110	-440	500	74	204
		60	23.0	380-480Δ	660-720Y	42.0Δ/24.2Y	1310	-440	430	78	
920 H47	double	50	25.0	345-415Δ	600-720Y	52.0Δ/30.0Y	1110	-440	590	74	211
		60	29.0	380-480Δ	660-720Y	52.0Δ/30.0Y	1310	-440	540	78	
920 H57	double	50	30.0	345-415Δ	600-720Y	60.0Δ/35.0Y	1110	-440	660	74	218
		60	35.0	380-480Δ	660-720Y	60.0Δ/35.0Y	1310	-440	620	78	
930 H07	single	50	8.5	345-415Δ	600-720Y	18.2Δ/10.5Y	1370	-120	110	75	98
		60	9.8	380-480Δ	660-720Y	18.2Δ/10.5Y	1650	-80	70	80	
930 H17	single	50	12.5	345-415Δ	600-720Y	28.0Δ/16.2Y	1370	-210	190	75	121
		60	14.5	380-480Δ	660-720Y	29.0Δ/16.7Y	1650	-170	160	80	
930 H37	single	50	18.5	345-415Δ	600-720Y	37.0Δ/21.0Y	1370	-310	320	75	131
		60	21.3	380-480Δ	660-720Y	39.0Δ/22.5Y	1650	-300	280	80	
940 H27	double	50	15.0	345-415Δ	600-720Y	35.0Δ/20.0Y	1940	-130	110	75	187
		60	17.5	380-480Δ	660-720Y	36.5Δ/21.0Y	2310	-60	40	84	
940 H37	double	50	20.0	345-415Δ	600-720Y	40.0Δ/23.0Y	1940	-220	200	75	212
		60	23.0	380-480Δ	660-720Y	42.0Δ/24.2Y	2310	-160	130	84	
940 H47	double	50	25.0	345-415Δ	600-720Y	52.0Δ/30.0Y	1940	-310	270	75	219
		60	29.0	380-480Δ	660-720Y	52.0Δ/30.0Y	2310	-270	220	84	
940 H57	double	50	30.0	345-415Δ	600-720Y	60.0Δ/35.0Y	1940	-380	350	75	225
		60	35.0	380-480Δ	660-720Y	60.0Δ/35.0Y	2310	-340	320	84	
943 H27	double	50	15.0	345-415Δ	600-720Y	35.0Δ/20.0Y	2050	-160	170	75	220
		60	17.5	380-480Δ	660-720Y	36.5Δ/21.0Y	2480	-110	120	84	
943 H37	double	50	20.0	345-415Δ	600-720Y	40.0Δ/23.0Y	2050	-250	230	75	230
		60	23.0	380-480Δ	660-720Y	42.0Δ/24.2Y	2480	-190	180	84	
943 H47	double	50	25.0	345-415Δ	600-720Y	52.0Δ/30.0Y	2050	-310	270	75	235
		60	29.0	380-480Δ	660-720Y	52.0Δ/30.0Y	2480	-270	230	84	
943 H57	double	50	30.0	345-415Δ	600-720Y	60.0Δ/35.0Y	2050	-380	350	75	240
		60	35.0	380-480Δ	660-720Y	60.0Δ/35.0Y	2480	-340	320	84	

4 / 7 page

Model name (2NB)	Single	Frequency	Rated	Rated Voltage	Rated	Max	Rated	Rated	Noise	Weight
	Double		Power		Current	Airflow	let Pressu	tlet Pressu		
	Stage		HZ		KW	V	A	m3/h		
210 A01	Single	50	0.2	220-240V	1.6	80	-100	110	53	9
		60	0.23	220-240V	1.9	98	-110	110	56	
210 A11	single	50	0.4	220-240V	2.7	80	-120	130	53	10
		60	0.5	220-240V	3.2	98	-150	160	56	
220 A21	double	50	0.7	220-240V	4.5	88	-210	240	55	16
		60	0.83	220-240V	5.6	103	-250	250	61	
230 A11	single	50	0.37	220-240V	2.7	100	-110	110	54	11
		60	0.45	220-240V	3	120	-130	140	57	
310 A01	single	50	0.55	220-240V	3.7	95	-120	130	57	13
		60	0.62	220-240V	4.9	110	-120	130	60	
330 A11	single	50	0.7	220-240V	4.8	145	-100	100	56	14
		60	0.83	220-240V	4.1	165	-110	100	58	
410 A01	single	50	0.7	220-240V	4.5	145	-120	120	63	15
		60	0.83	220-240V	5.6	175	-130	130	64	
410 A11	single	50	0.85	220-240V	5	145	-160	160	63	16
		60	0.95	220-240V	5.8	175	-160	160	64	
410 A21	single	50	1.3	220-240V	7.3	145	-170	200	63	17
		60	1.5	220-240V	7.8	175	-210	220	64	
420 A31	double	50	1.5	220-240V	9	150	-260	260	66	28
		60	1.75	220-240V	9.5	180	-300	290	69	
420 A41	double	50	2.2	220-240V	10	150	-265	265	66	31
		60	2.55	220-240V	11	180	-310	300	69	
430 A11	single	50	0.85	220-240V	5.2	180	-100	110	64	16
		60	0.95	220-240V	5.8	210	-100	110	66	
430 A21	single	50	1.1	220-240V	7.3	180	-170	210	64	17
		60	1.3	220-240V	8.3	210	-145	145	66	
510 A01	single	50	0.85	220-240V	5	210	-160	160	64	20
		60	0.95	220-240V	5.8	255	-145	140	70	
510 A11	single	50	1.3	220-240V	7.3	210	-170	170	64	22
		60	1.5	220-240V	7.5	255	-150	140	70	
510 A21	single	50	1.5	220-240V	9	210	-200	190	64	24
		60	1.75	220-240V	9.5	255	-220	210	70	
510 A31	single	50	2.2	220-240V	10	210	-220	270	64	28
		60	2.55	220-240V	11	255	-260	290	70	
520 A31	double	50	2.2	220-240V	10	230	-290	360	72	38
		60	2.55	220-240V	11	275	-350	330	74	
530 A21	single	50	1.5	220-240V	9	270	-140	120	65	26
		60	1.75	220-240V	10	330	-110	100	71	
610 A11	single	50	2.2	220-240V	10	270	-230	250	64	30
		60	2.55	220-240V	11	315	-250	270	70	
710 A11	single	50	2.2	220-240V	12.8	318	-190	190	72	30
		60	2.55	220-240V	12.8	376	-190	200	74	