

Model name (4NB)	single		Rated		Rated	Max	Rated	Rated	Noise dB(A)	Weight Kg
	Double	Frequency	Power	Rated Volatge	Current	Airflow	Inlet Pressure	Outlet Pressure		
	Stage	HZ	KW	V	A	m3/h	mbar	mbar		
210 H16	single	50	0.55	200-240△345-415Y	2.8△/1.6Y	47	-230	290	57	16
		60	0.63	220-275△380-480Y	3.0△/1.7Y	57	-270	320	62	
220 H26	Double	50	0.81	200-240△345-415Y	4.0△/2.3Y	47	-370	490	58	24
		60	0.94	220-275△380-480Y	4.0△/2.3Y	60	-440	480	62	
220 H56	Double	50	1.5	200-240△345-415Y	7.5△/4.3Y	47	-370	650	58	28
		60	1.75	220-275△380-480Y	7.5△/4.3Y	60	-500	740	62	
310 H16	single	50	0.55	200-240△345-415Y	2.8△/1.6Y	66	-250	250	57	16
		60	0.63	220-275△380-480Y	3.0△/1.7Y	80	-260	250	62	
310 H26	single	50	0.81	200-240△345-415Y	4.0△/2.3Y	66	-280	350	59	17
		60	0.94	220-275△380-480Y	4.0△/2.3Y	80	-340	360	62	
320 H46	Double	50	1.1	200-240△345-415Y	5.4△/3.1Y	65	-400	480	59	29
		60	1.3	220-275△380-480Y	5.4△/3.1Y	76	-480	480	63	
320 H56	Double	50	1.5	200-240△345-415Y	7.5△/4.3Y	65	-440	540	59	30
		60	1.75	220-275△380-480Y	7.6△/4.4Y	76	-560	600	63	
410 H16	single	50	1.1	200-240△345-415Y	5.4△/3.1Y	87	-300	380	55	23
		60	1.3	220-275△380-480Y	5.4△/3.1Y	105	-340	370	62	
420 H26	Double	50	1.5	200-240△345-415Y	7.5△/4.3Y	87	-480	450	61	33
		60	1.75	220-275△380-480Y	7.6△/4.4Y	105	-430	410	66	
420 H56	Double	50	3.3	200-240△345-415Y	13.0△/7.5Y	87	-500	750	61	39
		60	3.8	220-275△380-480Y	13.8△/8.0Y	105	-510	850	66	
510 H16	single	50	1.5	200-240△345-415Y	7.5△/4.3Y	120	-310	360	64	26
		60	1.75	220-275△380-480Y	7.6△/4.4Y	145	-340	320	68	
510 H26	single	50	2.2	200-240△345-415Y	11.4△/6.6Y	120	-310	470	64	29
		60	2.25	220-275△380-480Y	11.2△/6.5Y	145	-360	480	68	
520 H26	Double	50	2.2	200-240△345-415Y	11.4△/6.6Y	120	-470	460	64	40
		60	2.55	220-275△380-480Y	11.2△/6.5Y	145	-500	450	70	
520 H77	Double	50	4	345-415△	9.0△	120	-500	820	65	51
		60	4.6	380-480△	9.5△	145	-530	810	71	

6 / 7 page

Model name (4NB)	single		Rated		Rated	Max	Rated	Rated	Noise dB(A)	Weight Kg
	Double	Frequency	Power	Rated Volatge	Current	Airflow	Inlet Pressure	Outlet Pressure		
	Stage	HZ	KW	V	A	m3/h	mbar	mbar		
610 H16	single	50	2.2	200-240△345-415Y	11.4△/6.6Y	165	-340	360	65	32
		60	2.55	220-275△380-480Y	11.2△/6.5Y	195	-360	315	71	
610 H26	single	50	3.3	200-240△345-415Y	13.0△/7.5Y	165	-340	480	65	35
		60	3.8	220-275△380-480Y	14.2△/8.2Y	195	-380	530	71	
620 H36	Double	50	3.3	200-240△345-415Y	13.0△/7.5Y	165	-460	500	67	48
		60	3.8	220-275△380-480Y	14.2△/8.2Y	195	-480	420	71	
620 H57	Double	50	5.7	345-415△	12.5△	165	-460	740	68	65
		60	6.6	380-480△	12.0△	195	-480	840	72	
630 H67	single	50	7.5	345-415△	16.07△	170	-730	1040	72	85
		60	8.6	380-480△	16.0△	200	-700	1040	76	
210 A75	Single	50	0.55	220-240V	3.1	47	-230	290	57	18
		60	0.63	220-240V	7.1	57	-270	320	62	
220 A75	Double	50	1.5	220-240V	9.7	47	-370	600	58	30
		60	1.75	220-240V	10.3	60	-420	660	62	
310 A71	Single	50	0.94	220-240V	9	66	-350	350	57	18
		60	1.1	220-240V	9	80	-280	390	62	
320 A75	Double	50	1.5	220-240V	9.7	65	-400	550	59	32
		60	1.75	220-240V	10.3	76	-390	540	53	
410 A41	single	50	1.1	220-240V	10.1	87	-300	380	55	23
		60	1.3	220-240V	10.3	105	-350	390	62	

7 / 7 page