



YANGTIAN MASTERBATCH

TECHNICAL DATA SHEET

BaSO₄ Filler Masterbatch

Product description:

Na₂SO₄ Filler Masterbatch is made of micro sized Sodium Sulfate and PE carrier. It is designed for high demands of plastic film process. Filler masterbatch offers a nice balance of cost saving and good performance. It is high whiteness with good filler properties.

Range of Application:

Na₂SO₄ Filler Masterbatch is designed for use in LDPE,HDPE,PP and Ethylene copolymer.

Appearance:

Dim2.5MM *Thickness 1.0MM round granule, white

Characteristic:

Environment-friendly, nontoxic, smellless, spotless, smooth appearance and stable color, good dispersion. Reduce cost and save additives, no pollution during production.

Technical specifications:

Carrier	PE
Na ₂ SO ₄ Content	>85%
Moisture Content	<0.1%
Bulk Density	1.6+/-0.1g/cm ³
Specific Gravity	23℃ 2.0kg/m ³
Melting Point	130-135℃
Melting Flow Index	15.5-25.0g/10min



Usage:

Mixed with the materials.

Dosage:

Suggested 5%~35%.

Packing:

25kg per bag, KP bag or PE white bag. It should be stored in a dry place.

Note:

The above index is based on the testing result for reference only, not as the specific index.

YANGTIAN ENVIRONMENTAL MASTERBATCH CO., Limited

TEL: 0086-20-31066625

FAX:0086-20-39045153

Add: NO.568 B Building, HengDa Business Center, NanPu BiGui Road, PanYu District, GuangZhou City, China.

www.ytplasticmasterbatch.com

E-mail:yt_masterbatch@163.com