



Forever Medical

+2~8°C Pharmacy Refrigerator



| | Model | YJ-5V100 | YJ-5V236 |
|----------------|----------------------------|---------------------------|---------------------------|
| Specificaitons | Shelf/drawer | Shelves/3 | Shelves/4 |
| | Cooling method | Forced Air Cooling System | Forced Air Cooling System |
| | Defrost | Auto | Auto |
| | Refrigerant | R600a | R600a |
| | Power consumption(kWh/24h) | | 2.56 |
| | Noise (db) | 50 | 46 |
| | Ambient temperature (°C) | 10~32°C | 10~32°C |
| | Temperature range (°C) | 2~8°C | 2~8°C |
| Cooling system | Compressor brand/QTY | China Brand/1 | China Brand/1 |
| | Sensor Type | NTC | NTC |
| | Temperature controller | Microprocessor | Microprocessor |



| | Display | Digital display | Digital display |
|-----------------|---|----------------------------|----------------------------|
| Power | Voltage/frequency (V/Hz) | 220/50Hz | 220/50Hz |
| | Power (W) | 80W | 170W |
| | Current (A) | 0.8A | 1.09A |
| Material | Inside material | HIPS | Color sprayed steel |
| | Outside material | Color sprayed steel | Color sprayed steel |
| | Insulation | PURF | PURF |
| Size | Capacity (L/cu.ft) | 100/3.53 | 236/8.33 |
| | NT./GT. (kg) | 35/38 | 67/81 |
| | Exterior size(W*D*H)(mm) | 505*510*875 | 580*560*1760 |
| | Interior size(W*D*H)(mm) | 385*356*737 | 500*420*1090 |
| | Package size(W*D*H)(mm) | 580*580*940 | 730*675*1910 |
| | CBM | 0.32 | 0.94 |
| | 20GP/40GP/40HQ | 40/80/80 | 24/51/51 |
| Alarm | High/low temperature | Y | Y |
| | Power failure | Y | Y |
| | Thermostat failure | Y | Y |
| | Backup battery failure alarm | / | / |
| | Condenser fault alarm | / | / |
| | Ambient Temperatures | / | / |
| | Voltage abnormality alarm | / | / |
| | Door ajar | Y | Y |
| Optional | Foot | Y | Y |
| | Castor | / | Y |
| | Outer door/Type | 1/Glass door | 1/Glass door /Low-E |
| | Door Lock | 1 | 1 |
| | Test hole QTY/diameter | / | Optional |
| | Lamp | LED | LED |
| | USB port | / | / |
| | Temperature recorder | Optional | Optional |
| | Power failure backup system(alarm) | | 8h |
| | Remote alarm port | / | Y |
| | RS232/485 port | / | / |
| Other | Certification | ISO9001/13485/14 001;CE | ISO9001/13485/14 001;CE |