

HIGH FREQUENCY MOBILE DIGITAL RADIOGRAPHY SYSTEM

YJ-X5200A






PRODUCT DESCRIPTION

Product Usage

YJ-X5200A is high frequency combined digital X-ray radiography medical diagnostic equipment, it is used in radiography department, orthopedics, wards, emergency room, operation room, ICU, etc. It can satisfy the requirement of parts of body such as head, limbs, chest, spine, stomach, ect.



It can meet all positions to get images when combined with a mobile radiography table (optional)





Туре	ltem		Spec
High frequency X- ray	Max output power		25kW
	Main Inverter Frequency		60KHz
	X-ray tube	Focus	Small focus: 0.6; Large focus: 1.3
		Rotation anode speed	3000rpm
	Heat capacity		900kJ (1200kHU)
	Tube current		200mA
	Tube voltage		40-125kV
	MAS		0.4-360mAs
Digital image system	Digital detector 2 pieces	Detector	Amorphous silicon detector
		scintillator	cesium iodide
		View	14"×17"& 8"×10"
		Pixel	3000×2400&2304*2800
		Max spatial resolution	3.5Lp/mm
		Pixel size	150µm
		Output gray-scale	16bits
		DQE	75%
	Workstation	Acquisition module	Gigabit nets collection
		Image processing model	Built-in CONTEXTVISION
			GOPVIEW XR2 Enhance module,
			parameters chosen
			according to particular part
		Image information management	Dicom Storage
			Dicom Print
			Dicom transmission
Physical construction performance	Distance from floor to focus		Max: 191cm; Min: 73cm
	Distance from focus to pillar		Max:125cm; Min:75cm
	X-ray Tube components can rotate		±90°
	around the telescopic boom axis		± 50
	Collimator rotate around vertical axis		±90°
	Rotation range of pillar		0°~360°
Power supply			220V±10% 50/60Hz



Basic configuration:

- 1. High quality combined high frequency high voltage generator
- 2. Color graphical touch LCD control system
- 3. Panel detector with free movement
- 4. High quality IPC
- 5. Large size medical LCD display
- 6. New type mobile column rack
- 7. Symmetric adjustable, wireless ranging rotatable collimator with lamp
- 8. Electric assistance drive system
- 9. Cable exposure handbrake
- 10. Wireless remote control exposure device

X-ray generator:

- 1. 25KW compact x-ray generator;
- 2. High frequency of 60KHz;
- 3. With high technology to reduce the radiation;

Unique Power supply way:

- 1. Supers capacitor to supply power in photography and durable life;
- 2. Li-Battery to supply power in mechanical movement;

Mechanical movement:

- 1. The horizon arm can be contracted freely;
- 2. The pillar has the electronic up and down movement; and be rotated 360degree;
- 3. X-ray tube is rotary and moves left and right with 90degree;
- 4. Collimator can be rotated left and right with 90degree;
- 5. Comprehensive integration control drive
- 6. Collimator Rotation Range: ±90degrees
- 7. Tube Tilt: -10 to +90degrees
- 8. Tube Rotation: ±180degrees

Software:

LCD touch screen operation panel to control the machine conveniently



FORERMED® www.forermedchina.com





HENAN FOREVER MEDICAL CO.,LTD. Room 806, Floor 8, Wanda Center, Jinshui District, Zhengzhou, Henan, China Contact: Emily Yang Email: emily@yjcompany.com Whatsapp/TEL.:86-18838114181 Web: www.forermedchina.com