



# Y.J-MCR2S

YJ-MCR3S

# **MORTUARY FREEZER** SIDE OPEN DOOR

Henan Forever Medical CO.,LTD. Room 806, Floor 8, Wanda Center, Jinshui District, Zhengzhou, Henan Province

Fax: 86-371-61315851

Email: cassie@yicompany.com Whatsapp/TEL.:0086 -18236758227 Web: www.forermedchina.com

# FEATURE:

1: The whole body is made of 304 stainless steel material.

Anti corrosion and anti-rust. It is all-in-one machine without installation on-site.

- 2: Disposable 10 cm foam machine overall. Make cold room quickly reach the specified temperature.
- 3: LED display. Standard temperature: from 0°C to -10°C. Adjustable from -15°C to 5°C.
- 4: Separate compressor system and temperature controller system Original SECOP compressor, service life: 8-10 years.
- 5: Body tray is made of 304 stainless steel

Capacity: 200kg, anti-drop design with double rows of nylon silent rollers. Common size with Roundfin lifting trolley's tray.

- 6: Seven types of fault alarms: high temperature/low temperature/long time door opening/ low voltage/sensor failure/power failure/low battery.
- 7: Each room with door locks and spare keys to ensure the safety and privacy. 8: 5 inch universal wheel for easy move.



## INSULATION TECHNOLOGY

10 cm foamed in place urethane It is a green/ environmental foam material. Disposable foam machine overall.



## · COOLING QUALITY

High quality compressor (Germany Secop Compressor is optional) to be sure the necessary temperature.



# · SAFETY DOOR

Safe door locked system, with lock keys Unique door seal design for the minimum loss of cold temperature during a door opening. Door seal belt can be replaced. Door frame with a unique one-piece design.



# REMOVABLE TRAY

Separate body tray with the strong sliding system to make sure easy to pull out and pull back.Note: All the body trays (mortuary refrigerator, lifting cart, walk- in rack) size is the same.



## ALARM FUNCTION

Seven types of fault alarms: high temperature /low temperature/long time door opening/ low voltage/sensor failure/power failure/ low battery.



## · UNIVERSAL WHEEL

5 inch universal wheel for easy move.14pcs maintenance free nylon roller (7pcs of each side) for easy move the body tray.

## SPECIFICATION LIST:

Model No.	YJ-MCR2S
Material	Stainless steel 304 (201/316optional)
Thickness of stainless steel	Outer: 1.0 Body Tray: 1.0 Inner: 0.6
Compressor Place	Top of the freezer
External Size(mm)	2150*800*1750
Inner Room Size(mm)	1950*630*440
Body Tray size(mm)	1940*580
Body Tray	2
Body Tray load capacity	200kg
Compressor Ge	ermany Secop/Chinese compressor(optional)
Compressor Number	2 independent control of each chamber
Refrigerant	R404A
Temperature	Standard:0 to -10°C( optional -15 to 5°C)
Temperature Accuracy	1℃
Working temperature	10-38°C
Foamed urethane thickness(mm)	100
Chamber Height(mm)	440
Door	2
Rate of work	436W/1.2A
Voltage	220V/50HZ(110V/60HZ) optiona
Weight	280kg
Packing Size(mm)	2210*900*1810
CBM	3.€
Package	Plywood
Certification	CE
Customization	All can be
IICACE CCENADIO	

1710101101	otaliness steel so i (Ec i) o i copilaria
Thickness of stainless steel	Outer:1.0 Body Tray:1.0 Inner:0.
Compressor Place	Side of the freeze
External Size(mm)	2500*700*203
Inner Room Size(mm)	1950*630*44
Body Tray size(mm)	1940*58
Body Tray	
Body Tray load capacity	200k
Compressor	Germany Secop/Chinese compressor(optional
Compressor Number	3 independent control of each chambe
Refrigerant	R404
Temperature	Standard:0 to -10°C( optional -15 to 5°C
Temperature Accuracy	19
Working temperature	10-38°
Foamed urethane thickness(r	nm) 10
Chamber Height(mm)	44
Door	
Rate of work	654W/1.2
Voltage	220V/50HZ(110V/60HZ) option
Weight	380k
Packing Size(mm)	2700*900*217
CBM	5.
Package	Plywoo
Certification	C

YJ-MCR3S

All can be

Stainless steel 304 (201/316optional)

### USAGE SCENARIO:





Customization

Model No.

Material



Page 001 Page 002