TOBO GROUP

升降式止回阀
口径：1"—20"
压力：PN10-PN64,150LB—600LB
材质：WCB,WC6,WC9,CF8,CF8,
CF3,CF3M
连接方式：法兰
操作方式：———
介质：水，蒸汽，油

lift check valve
size:1"—20"
pressure:PN10-PN64,150LB-600LB
material:WCB,WC6,WC9,CF8,
CF8,CF3,CF3M
connection type:flange
operation type:———
medium:water,steam,oil

升降式止回阀
口径：1"—20"
压力：PN10-PN64,150LB—600LB
材质：WCB,WC6,WC9,CF8,CF8,
CF3,CF3M
连接方式：法兰
操作方式：———
介质：水，蒸汽，油

lift check valve
size:1"—20"
pressure:PN10-PN64,150LB-600LB
material:WCB,WC6,WC9,CF8,CF8,
CF3,CF3M
connection type:flange
operation type:———
medium:water,steam,oil

旋启式止回阀
口径：1/2"—2"
压力：150LB—600LB
材质：A105,WC6,WC9,CF8,CF8,
CF3,CF3M
连接方式：法兰
操作方式：———
介质：水，蒸汽，油

swing check l valve
size:1/2"—2"
pressure:150LB—600LB
material:A105,WC6,WC9,CF8,CF8,
CF3,CF3M
connection type:flange
operation type:———
medium:water,steam,oil

旋启式止回阀
口径：1"—28"
压力：PN10-PN64
材质：WCB,WC6,WC9,CF8,CF8,
CF3,CF3M
连接方式：法兰
操作方式：———
介质：水，蒸汽，油

swing check valve
size:1"—28"
pressure:PN10-PN64
material:WCB,WC6,WC9,CF8,CF8,
CF3,CF3M
connection type:flange
operation type:———
medium:water,steam,oil

对夹法兰止回阀
口径：1"—20"
压力：PN10-PN64,150LB—600LB
材质：WCB,WC6,WC9,CF8,CF8,
CF3,CF3M
连接方式：法兰
操作方式：———
介质：水，蒸汽，油

wafer flange type check l valve
size:1"—20"
pressure:PN10-PN64,150LB-600LB
material:WCB,WC6,WC9,CF8,CF8,
CF3,CF3M
connection type:flange
operation type:———
medium:water,steam,oil

旋启式止回阀
口径：1"—20"
压力：150LB—600LB
材质：WCB,WC6,WC9,CF8,CF8,
CF3,CF3M
连接方式：法兰
操作方式：———
介质：水，蒸汽，油

swing check l valve
size:1"—20"
pressure:150LB—600LB
material:WCB,WC6,WC9,CF8,CF8,
CF3,CF3M
connection type:flange
operation type:———
medium:water,steam,oil

TOBO GROUP 图博实业有限公司

TOBO Industrial Co., LTD

TOBO GROUP 图博实业有限公司

TOBO Industrial Co., LTD

ADD： 2nd Floor, Building 7, Baolong Center, Jiading District, Shanghai

TEL：+86-21-31261985

Email：info@tobo-group.com

公司简介 BRIEF INTRODUCTION

图博实业有限公司是一家阀门设计、制造、销售、服务于一体的科技型现代化企业。经过三十多年的发展、创新。公司现有占地面积8200m2 ,职工120多名,其中高级工程师与技术人员22名, 拥有精良的设备,先进的制造工艺和完善的检测手段并进行严格试验,使其出厂合格率达到100%。企业技术力量雄厚,主要产品覆盖国标、美标、德标、英标、日标等各种标准的闸阀、截止阀、球阀、硬密封半球阀、硬密封蝶阀、电动调节阀、止回阀、平板闸阀、耐高温三通球阀,管道配套阀等千余个品种规格。同时还可按客户要求生产非标阀门,产品主体材质选用:碳钢、不锈钢、耐热合金钢、蒙耐尔合金钢、低温钢、双相钢及其他特殊钢种;产品广泛用于化工、石油、石化、轻工、电力、水利、建筑、楼宇自动化系统的各类管道和设备上。产品畅销全国各地及海外市场。热诚欢迎各界友人莅临指导考察工作、洽谈业务!

TOBO Industrial Co., Ltd. is a valve design, manufacturing, sales, service in one of the scientific and technological modern enterprises. After more than 30 years of development and innovation. The company covers an area of 8200m2, more than 120 employees, including 22 senior engineers and technicians, with sophisticated equipment, advanced manufacturing technology and perfect testing methods and strict tests, so that its factory pass rate reaches 100%. Strong technical force, the main products cover national standard, American standard, German standard, British standard, Japanese standard and other standards of gate valve, globe valve, ball valve, hard sealed half ball valve, hard sealed butterfly valve, electric control valve, check valve, flat gate valve, high temperature three-way ball valve. Pipeline valves and other more than a thousand varieties of specifications. At the same time can also produce non-standard valves according to customer requirements, the main material selection of products: carbon steel, stainless steel, heat-resistant alloy steel, Monel alloy steel, low temperature steel, duplex steel and other special steel; Products are widely used in chemical, petroleum, petrochemical, light industry, power, water conservancy, construction, building automation system of all kinds of pipes and equipment. Products sell well all over the country and overseas markets. Warmly welcome friends from all walks of life to visit our work and talk about our business!

对夹凸耳蝶阀
口径：2"—20"
压力：PN10-PN16，150LB-300LB
材质：WCB,CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：手动，涡轮，气动，电动
介质：水，蒸汽，油

wafer lug type butterfly valve
size:2"—20"
pressure:PN10，150LB-300LB
material:WCB,CF8,CF8,CF3,CF3M
connection type:flange
operation type:manual,wormgear, Pneumatic, electric
medium:water,steam,oil

三偏心硬密封法兰蝶阀
口径：2"—48"
压力：PN10—PN40
材质：WCB,CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：涡轮，气动，电动
介质：水，蒸汽，油

triple eccentric hard seal flange type butterfly valve
size:2"—48"
pressure:PN10—PN40
material:WCB,CF8,CF8,CF3,CF3M
connection type:flange
operation type:manual,wormgear, Pneumatic, electric
medium:water,steam,oil

三偏心硬密封法兰蝶阀
口径：2"—20"
压力：150LB-600LB
材质：WCB,CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：涡轮，气动，电动
介质：水，蒸汽，油

triple eccentric hard seal flange type butterfly valve
size:2"—20"
pressure:150LB-600LB
material:WCB,CF8,CF8,CF3,CF3M
connection type:flange
operation type:manual,wormgear, Pneumatic, electric
medium:water,steam,oil

三偏心硬密封法兰蝶阀
口径：2"—48"
压力：PN10—PN40
材质：WCB,CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：涡轮，气动，电动
介质：水，蒸汽，油

triple eccentric hard seal flange type butterfly valve
size:2"—48"
pressure:PN10—PN40
material:WCB,CF8,CF8,CF3,CF3M
connection type:flange
operation type:manual,wormgear, Pneumatic, electric
medium:water,steam,oil

对夹三偏心硬密封蝶阀
口径：2"—48"
压力：PN10—PN40
材质：WCB,CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：手动，涡轮，气动，电动
介质：水，蒸汽，油

Wafer type triple eccentric butterfly valve
size:2"—48"
pressure:PN10—PN40
material:WCB,CF8,CF8,CF3,CF3M
connection type:flange
operation type:manual,wormgear, Pneumatic, electric
medium:water,steam,oil

通风蝶阀
口径：4"—120"
压力：PN2.5—PN10
材质：WCB
连接方式：法兰
操作方式：涡轮，气动，电动
介质：水，蒸汽，油

aeration butterfly valve
size:4"—120"
pressure:PN2.5—PN10
material:WCB
connection type:flange
operation type:manual,wormgear, Pneumatic, electric
medium:water,steam,oil

TOBO GROUP

截止阀
口径：2"—20"
压力：PN10—PN100
材质：WCB,WC6,WC9, CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：手动，伞齿轮，气动，电动
介质：水，蒸汽，油

Globe Valve
size:2"—20"
pressure:PN10-PN100
material:WCB,WC6,WC9,CF8, CF8,CF3,CF3M
connection type:flange
operation type:manual,gearbox, Pneumatic, electric
medium:water,steam,oil

截止阀
口径：2"—20"
压力：PN10—PN100
材质：WCB,WC6,WC9, CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：手动，伞齿轮，气动，电动
介质：水，蒸汽，油

Globe Valve
size:2"—20"
pressure:PN10-PN100
material:WCB,WC6,WC9,CF8, CF8,CF3,CF3M
connection type:flange
operation type:manual,gearbox, Pneumatic, electric
medium:water,steam,oil

截止阀
口径：3/4"—2"
压力：PN10—PN250
材质：A105,WC6,WC9, CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：手动，伞齿轮，气动，电动
介质：水，蒸汽，油

Globe Valve
size:3/4"—2"
pressure:PN10—PN250
material:A105,WC6,WC9, CF8,CF8,CF3,CF3M
connection type:flange
operation type:manual,gearbox, Pneumatic, electric
medium:water,steam,oil

截止阀
口径：2"—20"
压力：PN10—PN100
材质：WCB,WC6,WC9, CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：手动，伞齿轮，气动，电动
介质：水，蒸汽，油

Globe Valve
size:2"—20"
pressure:PN10—PN100
material:WCB,WC6,WC9,CF8, CF8,CF3,CF3M
connection type:flange
operation type:manual,gearbox, Pneumatic, electric
medium:water,steam,oil

截止阀
口径：2"—20"
压力：150LB—2500LB
材质：WCB,WC6,WC9, CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：手动，伞齿轮，气动，电动
介质：水，蒸汽，油

Globe Valve
size:2"—20"
pressure:150LB—2500LB
material:WCB,WC6,WC9,CF8, CF8,CF3,CF3M
connection type:flange
operation type:manual,gearbox, Pneumatic, electric
medium:water,steam,oil

氧气截止阀
口径：2"—20"
压力：PN10—PN100
材质：WCB,CF8,CF8, CF3,CF3M
连接方式：法兰
操作方式：手动，伞齿轮，气动，电动
介质：水，蒸汽，油

Oxygen Globe Valve
size:2"—20"
pressure:PN10—PN100
material:WCB,CF8,CF8,CF3,CF3M
connection type:flange
operation type:manual,gearbox, Pneumatic, electric
medium:water,steam,oil

TOBO GROUP

意式球阀
口径：2"—8"
压力：PN16
材质：WCB,CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：手动
介质：水，蒸汽，油

Italian ball valve
size:2"—8"
pressure:PN16
material:WCB,CF8,CF8,CF3,CF3M
connection type:flange
operation type:manual
medium:water,steam,oil

两片式法兰球阀
口径：2"—10"
压力：PN10-PN40,150LB—2500LB
材质：WCB,CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：手动，气动，电动
介质：水，蒸汽，油

2PC flange type ball valve
size:2"—10"
pressure:PN10-PN40,150LB-2500LB
material:WCB,CF8,CF8,CF3,CF3M
connection type:flange
operation type:manual,Pneumatic, electric
medium:water,steam,oil

电动固定球阀
口径：2"—20"
压力：PN10-PN40,150LB—2500LB
材质：WCB,CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：气动，电动
介质：水，蒸汽，油

electric fixed ball valve
size:2"—20"
pressure:PN10-PN40,150LB-2500LB
material:WCB,CF8,CF8,CF3,CF3M
connection type:flange
operation type:Pneumatic, electric
medium:water,steam,oil

硬密封偏心半球阀
口径：2"—20"
压力：PN10-PN40,150LB—2500LB
材质：WCB,CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：气动，电动
介质：水，蒸汽，油

Hard seal eccentric semi ball valve
size:2"—20"
pressure:PN10-PN40,150LB-2500LB
material:WCB,CF8,CF8,CF3,CF3M
connection type:flange
operation type:Pneumatic, electric
medium:water,steam,oil

气动固定球阀
口径：2"—20"
压力：PN10-PN40,150LB—2500LB
材质：WCB,CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：气动，电动
介质：水，蒸汽，油

pneumatic fixed ball valve
size:2"—20"
pressure:PN10-PN40,150LB-2500LB
material:WCB,CF8,CF8,CF3,CF3M
connection type:flange
operation type:Pneumatic, electric
medium:water,steam,oil

气动煤粉球阀
口径：2"—20"
压力：PN10-PN40,150LB—2500LB
材质：WCB,CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：气动，电动
介质：水，蒸汽，油

pneumatic pulverized coal ball valve
size:2"—20"
pressure:PN10-PN40,150LB-2500LB
material:WCB,CF8,CF8,CF3,CF3M
connection type:flange
operation type:Pneumatic, electric
medium:water,steam,oil

TOBO GROUP

闸阀
口径：2"—40"
压力：PN10—PN100
材质：WCB,WC6,WC9, CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：手动，伞齿轮，气动，电动
介质：水，蒸汽，油

gate valve
size:2"—40"
pressure:PN10—PN100
material:WCB,WC6,WC9,CF8, CF8,CF3,CF3M
connection type:flange
operation type:manual,gearbox, Pneumatic, electric
medium:water,steam,oil

闸阀
口径：2"—40"
压力：PN10—PN100
材质：WCB,WC6,WC9, CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：手动，伞齿轮，气动，电动
介质：水，蒸汽，油

gate valve
size:2"—40"
pressure:PN10-PN100
material:WCB,WC6,WC9,CF8, CF8,CF3,CF3M
connection type:flange
operation type:manual,gearbox, Pneumatic, electric
medium:water,steam,oil

闸阀
口径：2"—32"
压力：150LB—1500LB
材质：WCB,WC6,WC9, CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：手动，伞齿轮，气动，电动
介质：水，蒸汽，油

gate valve
size:2"—32"
pressure:150LB—1500LB
material:WCB,WC6,WC9,CF8, CF8,CF3,CF3M
connection type:flange
operation type:manual,gearbox, Pneumatic, electric
medium:water,steam,oil

闸阀
口径：2"—32"
压力：150LB—600LB
材质：A105,WCB,WC6, WC9,CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：手动，伞齿轮，气动，电动
介质：水，蒸汽，油

gate valve
size:2"—32"
pressure:150LB—600LB
material:A105,WCB,WC6,WC9, CF8,CF8,CF3,CF3M
connection type:flange
operation type:manual,gearbox, Pneumatic, electric
medium:water,steam,oil

暗杆闸阀
口径：2"—40"
压力：150LB—1500LB
材质：WCB,WC6,WC9, CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：手动，伞齿轮，气动，电动
介质：水，蒸汽，油

Non-rising steam gate valve
size:2"—40"
pressure:150LB—1500LB
material:WCB,WC6,WC9,CF8, CF8,CF3,CF3M
connection type:flange
operation type:manual,gearbox, Pneumatic, electric
medium:water,steam,oil

闸阀
口径：2"—32"
压力：PN10—PN100
材质：WCB,WC6,WC9 CF8,CF8,CF3,CF3M
连接方式：法兰
操作方式：手动，伞齿轮，气动，电动
介质：水，蒸汽，油

gate valve
size:2"—32"
pressure:150LB—1500LB
material:WCB,WC6,WC9,CF8, CF8,CF3,CF3M
connection type:flange
operation type:manual,gearbox, Pneumatic, electric
medium:water,steam,oil