



亮江化工
LIANGJIANG CHEM

DESCRIPTION

R-920 is a rutile titanium dioxide pigment, produced with chloride process and specially surface-treated, resulting in good particle size and distribution. It is widely applied in coatings, inks and plastic industry, matching technical requirements of multiple applications.

SAFETY AND HEALTH PRECAUTIONS

This product is non-toxic. Move to area with fresh air immediately if inhaled. Flush with clean water if eye exposed. Get medical advice when necessary. Please refer to the Safety Data Sheet for more information.

KEY FEATURES

- ◆ Bluish undertone
- ◆ High lightness
- ◆ High durability
- ◆ Multiple usages

PACKAGING

The product is packed in paper bags of three quality paper layers with a layer of plastic lining, 25 kg in net per bag. Jumbo bag of 500 kg or 1000 kg is available as per customer's option.

RECOMMENDED APPLICATIONS

- ◆ Building coating, indoors and outdoors, gloss and semi-gloss;
- ◆ Automobile OEM and refinishing paint; coil coating; industrial anti-corrosive coating; decorative coating; powder coating and other coatings;
- ◆ Letterpress printing, offset printing, gravure printing, and other ink uses;
- ◆ Engineering plastics, master batch, profiles and other plastic use.

CONTACT

TEL: 86-21-6911 2714
FAX: 86-21-3956 5974
MOB: 86-136 3659 9499
Email: alex@lj-group.com

TYPICAL PROPERTIES

PARAMETER	VALUE	PARAMETER	VALUE
TiO ₂ content	≥ 93.0 wt%	Aqueous suspension PH	6.5 ~ 8.5
Rutile ratio	≥ 99.0 %	105°C volatile	≤ 0.5 %
L *	≥ 98.2	Water extract resistance	≥ 100 Ω·m
b *	1.4 ~ 2.0	45 um residue	≤ 0.01 %
CBU	13~15	Water soluble	≤ 0.5%
TCS	≥ 90	Dispersion using a high-speed impeller mill	≤ 25 um
Oil absorption	≤ 20.0 g/100g		

STORAGE AND TRANSPORTION

The products should be stored in a ventilated and dry place as classified with the same batch number to avoid mixing or pollution. Do not store them directly on the ground. Pallets or plastic sheets shall be used to keep the products protected from moisture. It is prohibited to contact or mixed with substance that may react with the product. Handle with care when transport, loading and unloading. Keep out of direct sunlight and rain.

INFORMATION PROVIDED HEREIN ABOVE DOES NOT CONSTITUTE ANY LEGALLY BINDING OBLIGATIONS ON SHANGHAI LIANGJIANG. IT IS PROVIDED FOR GUIDANCE ONLY. IT IS STRONGLY SUGGESTED THAT CUSTOMERS TO PERFORM A FULL INSPECTION OF THE PRODUCTS OR SAMPLES UP RECEPTION. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, SHALL BE CONSTRUED WITH THIS DOCUMENT.THE DATA SETS HERE ABOVE ARE SUBJECT TO REGULATORY OR INREGULATORY UPDATING.