TECHNICAL DATA SHEET TITANIUM DIOXIDE R-1930



亮江化工 LIANGJIANG CHEM

### **DESCRIPTION**

R-1930 is a kind of rutile titanium dioxide pigment, produced by advance chloride process and special inorganic and organic surface-treated. Its special surface treatment makes the product has high hiding power, excellent fluidity of dry powder and excellent processing properties, it is specialized titanium dioxide for polyolefin masterbatch.

### **SAFETY AND HEALTH PRECAUSIONS**

This product is non-toxic. Move to area with fresh air immediately if inhaled. Flush with clean water if eye exposed. Get medical advice when necessary. Please refer to the Safety Date Sheet for more information.

# **KEY FEATURES**

- ♦ Bluish undertone
- ♦ High temperature resistance
- High tinting strength
- ♦ Strong dispersibility
- ♦ Excellent processing performance

# RECOMMENDED APPLICATIONS

- Engineering plastics such as PVC, PE, PP and ABS;
- PS and its copolymers, plastics, masterbatch, film blowing etc.

# PACKAGING

The product is packed in paper bags of three quality paper layers with a layer of plastic lining, 25 kg in net per bag. Jumbo bag of 500 kg or 1000 kg is available as per customer's option.

## **CONTACT**

TEL: 86-21-6911 2714

FAX: 86-21-3956 5974

MOB: 86-136 3659 9499

Email: alex@lj-group.com

## **TYPICAL PROPERTIES**

PARAMETER	VALUE	PARAMETER	VALUE
TiO <sub>2</sub> content	≥ 96.0 wt%	Resistivity of aqueous extract ( $\Omega$ ·m)	≥ 100
Rutile ratio	≥ 99.8%	Oil absorption	≤ 16.0 g/100g
L*	≥ 98.2	Aqueous suspension PH	6.5 ~ 8.5
b*	1.6 ~ 2.0	105℃ volatile	≤ 0.3 %
CBU	≥16	Filtration Pressure (bar/kg)	≤ 200
Surface treatment	Al, organic		

### STORAGE AND TRANSPORTION

The products should be stored in a ventilated and dry place as classified with the same batch number to avoid mixing or pollution.

Do not store them directly on the ground. Pallets or plastic sheets shall be used to keep the products protected from moisture. It is prohibited to contact or mixed with substance that may react with the product. Handle with care when transport, loading and unloading. Keep out of direct sunlight and rain.

INFORMATION PROVIDED HEREIN ABOVE DOES NOT CONSTITUTE ANY LEGALLY BINDING OBLIGATIONS ON SHANGHAI LIANGJIANG. IT IS PROVIDED FOR GUIDANCE ONLY. IT IS

STRONGLY SUGGESTED THAT CUSTOMERS TO PERFORM A FULL INSPECTION OF THE PRODUCTS OR SAMPLES UP RECEPTION. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR

IMPLIED, SHALL BE CONSTRUDED WITH THIS DOCUMENT. THE DATA SETS HERE ABOVE ARE SUBJECT TO REGULATORY OR INREGULATORY UPDATING.