TECHNICAL DATA SHEET TITANIUM DIOXIDE CR-223



亮江化工 LIANGJIANG CHEM

### **DESCRIPTION**

CR-223 is a rutile titanium dioxide pigment, is produced by advanced chloride process and treated with special organics and inorganics. With excellent yellowing resistance and polyester system degradation resistance, high hiding power, good dispersibility, and excellent dry powder fluidity, it is dedicated to Polycarbonate (PC).

# **SAFETY AND HEALTH PRECAUSIONS**

This product is non-toxic. If inhaled, move to fresh air immediately. If eye contacted, rinse thoroughly with plenty of water; call a physician if necessary. Avoid food touch.

## **KEY FEATURES**

Strong resistance to polycarbonate degradation due to TiO<sub>2</sub> adding

The product is packed in paper bags of three quality paper layers with a layer of plastic lining, 25 kg in net per bag. Jumbo bag of 500 kg or 1000 kg is available as per customer's option.

- ♦ Excellent high-temperature yellowing resistance
- ♦ Bluish undertone

**PACKAGING** 

♦ High hiding power and high tinting strength

Excellent mechanical property (Strong impact resistance)

### **RECOMMENDED APPLICATIONS**

- PC material field (highly recommended);
- ♦ PC masterbatch (highly recommended);
- PET, PA, ABS and other engineering plastics;
- Other high-temperature plastics processing (> 250 °C) field.

TEL: 86-21-6911 2714

FAX: 86-21-3956 5974

MOB: 86-136 3659 9499

**CONTACT** 

Email: alex@lj-group.com

# TYPICAL PROPERTIES

PARAMETER	VALUE	PARAMETER	VALUE
TiO₂ content	≥ 94.5 wt%	Surface treatment	Al, Organics
Rutile ratio	≥ 99.8 %	Oil absorption	≤ 14.0 g/100g
L*	≥ 98.2	105℃ volatile	≤ 0.1 %
b *	1.6 ~ 2.0	Resistivity (Ω·m)	≥ 100
CBU	≥ 14		

# STORAGE AND TRANSPORTION

The products should be stored in a ventilated and dry place as classified with the same batch number to avoid mixing or pollution. Do not store them directly on the ground. Pallets or plastic sheets shall be used to keep the products protected from moisture. It is prohibited to contact or mixed with substance that may react with the product. Handle with care when transport, loading and unloading. Keep out of direct sunlight and rain.

INFORMATION PROVIDED HEREIN ABOVE DOES NOT CONSTITUTE ANY LEGALLY BINDING OBLIGATIONS ON SHANGHAI LIANGJIANG. IT IS PROVIDED FOR GUIDANCE ONLY. IT IS

STRONGLY SUGGESTED THAT CUSTOMERS TO PERFORM A FULL INSPECTION OF THE PRODUCTS OR SAMPLES UP RECEPTION. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR

IMPLIED, SHALL BE CONSTRUDED WITH THIS DOCUMENT. THE DATA SETS HERE ABOVE ARE SUBJECT TO REGULATORY OR INREGULATORY UPDATING.