

SAFETY DATA SHEET

Product name : Heatless Ink VI IQ800 Black
SDS Number : 16A081

Date Prepared : Dec.27.2016
Revision Date :

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name : Heatless Ink VI IQ800 Black
Recommended use : Ink for ink jet printer

Company : GENERAL CO., LTD.
18, Satsukigaoka, Minakuchi-cho, Koka-shi, Siga 528-0062, Japan

Telephone number : +81-748-65-2260
Fax number : +81-748-63-1922
E-mail : qa_1@general.co.jp
Emergency telephone number : +81-748-65-2260

2. HAZARDS IDENTIFICATION

GHS Classification of the substance or mixture

Flammable liquid : Category 2
Serious eye damage/eye irritation : Category 1
Specific target organ toxicity - Single exposure : Category 3 (Narcotic effect)
Chronic hazards to the aquatic environment : Category 3

Label Elements

Hazard pictograms



Signal word : Danger

Hazard statements : Highly flammable liquid and vapor.
Causes serious eye damage.
May cause drowsiness or dizziness.
Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wear protective gloves/protective clothing/eye protection/face protection.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Avoid release to the environment.

Response

: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.
Rinse skin with water/shower.
In case of fire: Use an appropriate extinguishing agent for extinction.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing.
Immediately call a POISON CENTER or doctor/physician.

Storage

: Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Store locked up.

SAFETY DATA SHEET

Product name : Heatless Ink VI IQ800 Black
SDS Number : 16A081

Date Prepared : Dec.27.2016
Revision Date :

Disposal : Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards : None known

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance or Mixture : Mixture

Ingredients

Components	CAS No.	Concentration (wt%)
Dyestuff	Confidential	< 9
Ethanol	64-17-5	< 70
1-Propanol	71-23-8	< 20
Acetone	67-64-1	< 3
Diacetone alcohol	123-42-2	< 2

4. FIRST-AID MEASURES

Description of first aid measures

- Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Get medical advice/attention if you feel unwell.
- Skin contact : Wash thoroughly with soap and plenty of water while removing all contaminated clothes.
If skin irritation or rash occurs: Get medical advice/attention.
- Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Remove contact lenses, if present and easy to remove. Continue to rinse for at least 15 minutes.
Get medical attention immediately.
- Ingestion : Wash mouth with water and seek medical advice immediately.
Do not induce vomiting.

Most important symptoms and effects, both acute and delayed

: No further relevant information available.

Recommendations for immediate medical care and special treatment needed

Notes to physician : Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO₂), Dry chemical, Alcohol-resistant foam, Water spray.
Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the substance or mixture

: Carbon oxides, nitrogen oxides will form in fire.

Special protective equipment for firefighters

: Wear suitable protective suit and self-contained breathing apparatus.

SAFETY DATA SHEET

Product name : Heatless Ink VI IQ800 Black
SDS Number : 16A081

Date Prepared : Dec.27.2016
Revision Date :

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : Wear appropriate personal protective equipment as specified in section 8.
- : Keep unnecessary peoples away. Isolate area. Ensure adequate ventilation.

Environmental precautions : Do not release into soil, sewers, river, or the public water courses.

Methods and materials for containment and cleaning up

- : In the case of a cartridge: Not applicable.
- : At the time of the leakage of contents: Absorb or cover with dry earth, sand or other non-combustible material and transfer to sealable containers. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. HANDLING AND STORAGE

Handling

- Handling :
- Put on appropriate personal protective equipment (see Section 8).
 - Prohibition of dropping and throwing.
 - Avoid contact with skin, eyes and clothing.
 - Do not breathe vapors. Use only in a well-ventilated area.
 - Use a ventilation, local exhaust if vapor or aerosol will be generated.
 - Keep away from fire, sparks and heated surfaces.
 - Take precautionary measures against electrostatic discharges.

Hygiene measures : When using do not eat or drink. Wash hands thoroughly after handling.

- Storage :
- Do not store ink in high or freezing temperature.
 - Keep away from heat and direct sunlight.
 - Do not store ink with acids, oxidizing agents or explosives.
 - Keep containers tightly closed in a dry, cool and well-ventilated place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Components	CAS No.	OSHA PEL	ACGIH TLV
Ethanol	64-17-5	1000 ppm, 1900 mg/m3	STEL: 1000 ppm
1-Propanol	71-23-8	200 ppm, 500 mg/m3	TWA: 100 ppm
Acetone	67-64-1	1000 ppm, 2400 mg/m3	TWA: 500 ppm STEL: 750 ppm
Diacetone alcohol	123-42-2	50 ppm, 240 mg/m3	TWA: 50 ppm

Engineering controls

- Engineering measures :
- Adequate ventilation should be provided so that exposure limits are not exceeded.
 - Take precautionary measures against static discharge.

Personal protective equipment

- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
- Hand protection : Impermeable gloves.
- Eye protection : Safety glasses with side-shields. Goggles.
- Skin and body protection : Protective suit, Safety shoes.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Solvent type ink
Color : Black

SAFETY DATA SHEET

Product name : Heatless Ink VI IQ800 Black
SDS Number : 16A081

Date Prepared : Dec.27.2016
Revision Date :

Odor : Alcohol odor
pH : No data available
Melting point : No data available
Boiling point : 75 degree C
Flash point : 13 degree C (Ethanol) 23 degree C (1-Propanol)
Evaporation rate : No data available
Flammability (solid, gas) : No data available
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapor pressure : No data available
Vapor density : No data available
Relative density : 0.84 (at 25 degree C)
Water solubility : Insolubility
Partition coefficient: n-octanol/water : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity : 2.1 mPa·s (at 25 degree C)

10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions with proper storage and handling.
Chemical stability : The product is stable under normal conditions.
Possibility of hazardous reactions : No hazardous reactions with proper storage and handling.
Conditions to avoid : High temperature, heat, sparks, flames and other sources of ignition. Oxidizing condition.
Incompatible materials : No information available.
Hazardous decomposition products : Carbon oxides, nitrogen oxides will form in fire.

11. TOXICOLOGICAL INFORMATION

Acute toxicity
Acute toxicity (oral) : Ethanol LD50 (rat) 7060 mg/kg
1-Propanol LD50 (rat) 3830 mg/kg
Diacetone alcohol LD50 (rat) 4000 mg/kg
Acute toxicity (dermal) : Ethanol LDLo (rabbit) 20000 mg/kg
1-Propanol LD50 (rabbit) >10000 mg/kg
Diacetone alcohol LD50 (rabbit) 13630 mg/kg
Acute toxicity (inhalation) : Ethanol LC50 (rat) 63000 ppm/4h
1-Propanol LC50 (rat) >9.8 mg/l/4h
Skin corrosion/irritation : 1-Propanol (rabbit) 72h; Slight
Diacetone alcohol (rabbit) Mild irritation
Serious eye damage/eye irritation : 1-Propanol (rabbit) 72h; Severe
Respiratory or skin sensitization : 1-Propanol (guinea pig) Non-sensitizing
Germ cell mutagenicity : No data available
Carcinogenicity : NTP : Not listed.
IARC : Ethanol: Group 1
EPA : Not listed.
Reproductive toxicity : No data available
Specific target organ systemic toxicity - Single exposure : May cause drowsiness or dizziness.

SAFETY DATA SHEET

Product name : Heatless Ink VI IQ800 Black
SDS Number : 16A081

Date Prepared : Dec.27.2016
Revision Date :

Specific target organ systemic toxicity - : No data available
Repeated exposure
Aspiration hazard : No data available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxicity to fish	:	Ethanol	LC50 (Pimephales promelas)	>100 mg/l/96h
	:	1-Propanol	LC50 (Pimephales promelas)	>804 mg/l/96h
	:	Dyestuff	LC50 (Fish)	2.0 mg/l

Persistence and degradability : No data available
Bioaccumulation : No data available
Mobility in soil : No data available

13. DISPOSAL CONSIDERATIONS

Appropriate disposal methods : Dispose of waste material in accordance with local, state and federal pollution regulations.

Contaminated packaging : When disposing of an empty container, dispose after removing contents materials completely. Dispose of this material and its container according to your country law.

14. TRANSPORT INFORMATION

International Regulations

UN number : 1210
UN proper shipping name : Printing Ink
Class : Class 3
Packing group : II

Sea transport

IMDG-Code:
UN number : 1210
UN proper shipping name : Printing Ink
Class : Class 3
Packing group : II
Marine pollutant : No

Air transport

ICAO-TI/IATA-DGR :
UN number : 1210
UN proper shipping name : Printing Ink
Class : Class 3
Packing group : II

Land transport

DOT :
ADR/RID :
UN number : 1210
UN proper shipping name : Printing Ink
Class : Class 3
Packing group : II

SAFETY DATA SHEET

Product name : Heatless Ink VI IQ800 Black
SDS Number : 16A081

Date Prepared : Dec.27.2016
Revision Date :

15. REGULATORY INFORMATION

Follow all regulations in your country.

Toxic Substances Control Act (TSCA)

TSCA Status : All of the components of this product are listed on the TSCA Inventory.

16. OTHER INFORMATION

Literature Reference : SDS of raw material manufacturer
NITE: Chemical Risk Information Platform
3E: Ariel Research Tool

Revision date :

Further information

The information contained herein is based on the current knowledge. This Safety Data Sheet is intended to describe our products in correctness of safety requirements. It should not therefore be construed as guaranteeing specific properties. The data applies to only usual handling.