

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name IC-2BK130 PRINTING INK

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Printing ink.

1.3. Details of the supplier of the safety data sheet

Supplier Inkminic Logo
Technology (Guangzhou)
CO., LTD

1.4. Emergency telephone number

Emergency telephone For emergencies call +86020-32954560

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)


Physical hazards Flam. Liq. 2 - H225

Health hazards Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements
H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/ container in accordance with national regulations.

IC-2BK130 PRINTING INK

Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	butanone, C.I Acid Blue 317
Supplementary precautionary statements	P240 Ground and bond container and receiving equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P261 Avoid breathing vapour/ spray. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P312 Call a POISON CENTRE/doctor if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/ attention. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

2.3. Other hazards

None known.

Endocrine disrupting substances This product does not contain any known or suspected endocrine disruptors over 0.1%

PBT and vPvB The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration

SECTION 3: Composition/information on ingredients

3.2. Mixtures

butanone	50-80%
CAS number: 78-93-3	EC number: 201-159-0
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	
Isopropyl Acetate	5-10%
CAS number: 108-21-4	EC number: 203-561-1
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	
ethanol	5-10%
CAS number: 64-17-5	EC number: 200-578-6
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319	

IC-2BK130 PRINTING INK

Isopropyl Alcohol	3-5%
CAS number: 67-63-0	EC number: 200-661-7
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	
Chromate(1-), bis[1-[[5- (1,1-dimethylpropyl)-2- (hydroxy-kO)-3-nitrophenyl] azo-kN1]-2-naphthalenolato (2-)-kO]-, sodium	1-2.5%
CAS number: 57206-83-4	EC number: 260-617-8
Classification Aquatic Chronic 2 - H411	
C.I. Solvent Brown 44	1-2.5%
CAS number: 57206-81-2	EC number: 260-616-2
Classification Aquatic Chronic 2 - H411	
[1-[[2-(hydroxy-kO) -4-nitrophenyl]azo-kN1] -2-naphthalenolato(2-)-kO] [1-[[2-(hydroxy-kO) -5-nitrophenyl]azo-kN1] -2-naphtha	1-2.5%
CAS number: 59307-49-2	EC number: 261-691-4
Classification Aquatic Chronic 2 - H411	
C.I Acid Blue 317	1-2.5%
CAS number: 64611-73-0	EC number: 264-966-7
Classification Eye Irrit. 2 - H319 Skin Sens. 1B - H317	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention. Show this Safety Data Sheet to the medical personnel.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	IF SWALLOWED: Get medical attention. Rinse mouth thoroughly with water. Do not induce vomiting unless under the direction of medical personnel. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Skin contact	IF ON SKIN: Rinse immediately with plenty of water.
Eye contact	IF IN EYES: Rinse immediately with plenty of water. Get medical attention if irritation persists after washing.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

IC-2BK130 PRINTING INK

4.2. Most important symptoms and effects, both acute and delayed

General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Drowsiness, dizziness, disorientation, vertigo. Headache. Nausea, vomiting.
Ingestion	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
Skin contact	Prolonged contact may cause dryness of the skin.
Eye contact	Irritating to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
----------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Containers can burst violently or explode when heated, due to excessive pressure build-up. Take precautionary measures against static discharges.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Carbon monoxide (CO). Carbon dioxide (CO ₂).

5.3. Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. No smoking, sparks, flames or other sources of ignition near spillage.
----------------------	--

6.2. Environmental precautions

Environmental precautions	Harmful to aquatic life with long lasting effects. Contain spillage with sand, earth or other suitable non-combustible material. Use appropriate containment to avoid environmental contamination. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).
---------------------------	--

6.3. Methods and material for containment and cleaning up

IC-2BK130 PRINTING INK

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Collect and dispose of spillage as indicated in Section 13.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Flammable/combustible materials. Do not handle until all safety precautions have been read and understood. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Use only non-sparking tools. Avoid discharge to the aquatic environment.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Eliminate all sources of ignition. Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep containers upright. Take precautionary measures against static discharges.

Storage class

Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

butanone

Long-term exposure limit (8-hour TWA): WEL 200 ppm 600 mg/m³

Short-term exposure limit (15-minute): WEL 300 ppm 899 mg/m³

Sk, BMGV

Isopropyl Acetate

Short-term exposure limit (15-minute): WEL 200 ppm 849 mg/m³

ethanol

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

Isopropyl Alcohol

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

BMGV = Biological monitoring guidance value.

butanone (CAS: 78-93-3)

DNEL

Workers - Inhalation; Long term systemic effects: 600 mg/m³

Workers - Dermal; Long term systemic effects: 1161 mg/kg

IC-2BK130 PRINTING INK

PNEC	- Fresh water; 55.8 mg/l - marine water; 55.8 mg/l - Sediment (Freshwater); 284.7 mg/kg - Sediment (Marinewater); 284.7 mg/kg - Soil; 22.5 mg/kg
------	--

ethanol (CAS: 64-17-5)

DNEL	Workers - Inhalation; Long term systemic effects: 950 mg/m ³ Workers - Inhalation; Long term local effects: 1900 mg/m ³ Workers - Dermal; Long term systemic effects: 343 mg/kg/day
------	---

PNEC	- Fresh water; 0.96 mg/l - marine water; 0.79 mg/l - Intermittent release; 2.75 mg/l - STP; 580 mg/l - Sediment (Freshwater); 3.6 mg/kg - Sediment (Marinewater); 2.9 - Soil; 0.63 mg/kg
------	--

Isopropyl Acetate (CAS: 108-21-4)

DNEL	Workers - Inhalation; Short term systemic effects: 850 mg/m ³ Workers - Inhalation; Long term systemic effects: 420 mg/m ³ Workers - Inhalation; Long term local effects: 420 mg/m ³ Workers - Dermal; Long term systemic effects: 43 mg/kg/day
------	---

PNEC	- Fresh water; 0.22 mg/l - marine water; 0.022 mg/l - Intermittent release; 1.1 mg/l - Sediment (Freshwater); 1.25 mg/kg - Sediment (Marinewater); 0.125 mg/kg
------	--

Isopropyl Alcohol (CAS: 67-63-0)

DNEL	Workers - Inhalation; Long term systemic effects: 500 mg/m ³ Workers - Dermal; Long term systemic effects: 888 mg/kg/day
------	--

PNEC	- Fresh water; 140.9 mg/l - marine water; 140.9 mg/l - STP; 2251 mg/l - Sediment (Freshwater); 552 mg/kg - Sediment (Marinewater); 552 mg/kg - Soil; 28 mg/kg
------	---

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Ensure control measures are regularly inspected and maintained. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield. Personal protective equipment that provides appropriate eye and face protection should be worn.

IC-2BK130 PRINTING INK

Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation. Frequent changes are recommended. It is recommended that gloves are made of the following material: Laminate of polyethylene and ethylene vinyl alcohol (PE/EVOH). The selected gloves should have a breakthrough time of at least 8 hours. Polyvinyl alcohol (PVA). The selected gloves should have a breakthrough time of at least 0.75 hours. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. It should be noted that liquid may penetrate the gloves.
Other skin and body protection	Wear anti-static protective clothing if there is a risk of ignition from static electricity. Wear appropriate clothing to prevent skin contamination.
Hygiene measures	Provide eyewash station and safety shower. Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Black.
Odour	Ketonic.
Odour threshold	Lower 5 ppm Information given is applicable to the major ingredient.
pH	Not relevant. The product contains organic solvents. Technical impossibility to obtain the data.
Melting point	-86°C Information given is applicable to the major ingredient.
Initial boiling point and range	~79.6°C @ 1013 hPa Information given is applicable to the major ingredient.
Flash point	-6°C Closed cup.
Evaporation rate	3.7 (butyl acetate = 1) Information given is applicable to the major ingredient.
Flammability (solid, gas)	Not relevant. Flammable liquid
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.8 % Upper flammable/explosive limit: 11.5 % Information given is applicable to the major ingredient.
Vapour pressure	105 hPa @ 20°C 126 hPa @ 25°C Information given is applicable to the major ingredient.
Vapour density	2.41
Relative density	0.855-0.895
Solubility(ies)	270 g/l water @ 20°C Information given is applicable to the major ingredient. Soluble in the following materials: Organic solvents.
Partition coefficient	log Pow: 0.3 Information given is applicable to the major ingredient.
Auto-ignition temperature	404°C Information given is applicable to the major ingredient.
Decomposition Temperature	550 - 650°C Information given is applicable to the major ingredient.
Viscosity	3.2-4.5 cP @ 25°C
Explosive properties	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Volatile organic compound	This product contains a maximum VOC content of 86 %. This product contains a maximum VOC content of 0.701 kg/l.
---------------------------	---

IC-2BK130 PRINTING INK

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity See Section 10.3 (Possibility of hazardous reactions) for further information.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions The following materials may react strongly with the product: Oxidising agents.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented. Do not pressurise, cut, weld, drill, grind or otherwise expose containers to heat or sources of ignition.

10.5. Incompatible materials

Materials to avoid Oxidising materials. Acids - oxidising.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. Carbon dioxide (CO₂). Carbon monoxide (CO).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development

Based on available data the classification criteria are not met.

IC-2BK130 PRINTING INK

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H336 May cause drowsiness or dizziness.

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.

Ingestion No specific symptoms known.

Skin contact Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.

Eye contact Irritating to eyes.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target organs Central nervous system

Endocrine disrupting substances This product does not contain any known or suspected endocrine disruptors over 0.1%

Toxicological information on ingredients.

butanone

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >2000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rabbit

Isopropyl Acetate

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 6,750.0

Species Rat

ATE oral (mg/kg) 6,750.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 17,400.0

Species Rabbit

ATE dermal (mg/kg) 17,400.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 50,600.0

Species Rat

ATE inhalation (vapours mg/l) 50,600.0

IC-2BK130 PRINTING INK

ethanol

Acute toxicity - oral

Notes (oral LD₅₀) REACH dossier information.

Acute toxicity - dermal

Notes (dermal LD₅₀) REACH dossier information.

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ 125.0
vapours mg/l)

Notes (inhalation LC₅₀) REACH dossier information.

ATE inhalation (vapours mg/l) 125.0

Carcinogenicity

IARC carcinogenicity IARC Group 1 Carcinogenic to humans.

Isopropyl Alcohol

Acute toxicity - oral

Notes (oral LD₅₀) Supplier's information. LD₅₀ >2000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) Supplier's information. LD₅₀ >2000 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) REACH dossier information. LC₅₀ > 10000 ppm, Inhalation, Rat

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Ethyl Acetate

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 4,934.0
mg/kg)

Species Rabbit

ATE oral (mg/kg) 4,934.0

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >20000 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀ >22.5 mg/l, Inhalation, Rat

Reproductive toxicity

Reproductive toxicity - fertility Two-generation study - NOAEL 26400 mg/kg/day, Oral, Mouse P, F1

Reproductive toxicity - development Embryotoxicity: - NOAEL: >3500 mg/kg/day, Oral, Mouse

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 900 mg/kg/day, Oral, Rat NOAEC 350 ppm, Inhalation, Rat

SECTION 12: Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

12.1. Toxicity

IC-2BK130 PRINTING INK

Toxicity

Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

Ecological information on ingredients.

butanone

Acute aquatic toxicity

Acute toxicity - fish	REACH dossier information. LC ₅₀ , 96 hours: 2993 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	REACH dossier information. EC ₅₀ , 48 hours: 308 mg/l, Daphnia magna
Acute toxicity - aquatic plants	REACH dossier information. EC ₅₀ , 72 hours: 1972 mg/l, Selenastrum capricornutum

Isopropyl Acetate

Acute aquatic toxicity

Acute toxicity - fish	REACH dossier information. LC ₅₀ , 96 hours: 0.32 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	LC ₅₀ , 48 hours: >1000 mg/l, Daphnia magna
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 370 mg/l, Pseudokirchneriella subcapitata

ethanol

Acute aquatic toxicity

Acute toxicity - fish	REACH dossier information. EC ₀ , 200 hours: 3900 mg/l, Oryzias latipes (Red killifish)
Acute toxicity - aquatic invertebrates	EC ₅₀ , 24 hours: 20803 mg/l, Daphnia magna
Acute toxicity - aquatic plants	NOEC, 7 days: 467 mg/l, Freshwater plants
Acute toxicity - microorganisms	IC ₅₀ , 3 hours: >1000 mg/l, Activated sludge
Acute toxicity - terrestrial	LC ₅₀ , 48 hours: >1 mg/cm ² , Eisenia Fetida (Earthworm)

Chronic aquatic toxicity

Chronic toxicity - fish early life stage	NOEC, 42 hours: 500 mg/l, Brachydanio rerio (Zebra Fish)
Chronic toxicity - aquatic invertebrates	LC ₅₀ , 4 days: 12070 mg/l, Marinewater invertebrates

Isopropyl Alcohol

Acute aquatic toxicity

Acute toxicity - fish	Supplier's information. LC ₅₀ , 48 hours: > 100 mg/l, Leuciscus idus (Golden orfe)
Acute toxicity - aquatic invertebrates	Supplier's information. EC ₅₀ , 48 hours: > 100 mg/l, Daphnia magna
Acute toxicity - aquatic plants	Supplier's information. EC ₅₀ , 72 hours: > 100 mg/l, Scenedesmus subspicatus

Ethyl Acetate

Acute aquatic toxicity

IC-2BK130 PRINTING INK

Acute toxicity - fish LC₅₀, 96 hours: 230 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates IC₅₀, 48 hours: 346 mg/l, Marinewater invertebrates

Acute toxicity - aquatic plants LC₅₀, 48 hours: 5600 mg/l, Desmodesmus subspicatus
NOEC, 48 hours: >1000 mg/l, Scenedesmus subspicatus

Chronic aquatic toxicity

Chronic toxicity - fish early life stage NOEC, 96 hours: <9.65 mg/l, Freshwater fish

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient log Pow: 0.3 Information given is applicable to the major ingredient.

Ecological information on ingredients.

butanone

Partition coefficient log Pow: 0.3

Isopropyl Acetate

Partition coefficient log Pow: 1.28

ethanol

Partition coefficient log Pow: 0.32

Isopropyl Alcohol

Partition coefficient log Pow: 0.05

Ethyl Acetate

Partition coefficient log Pow: 0.68

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration

Ecological information on ingredients.

Ethyl Acetate

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current UK criteria.

12.6. Other adverse effects

Other adverse effects None known.

Endocrine disrupting substances This product does not contain any known or suspected endocrine disruptors over 0.1%

SECTION 13: Disposal considerations

IC-2BK130 PRINTING INK

13.1. Waste treatment methods

General information

The generation of waste should be minimised or avoided wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out.

Disposal methods

Dispose of waste product or used containers in accordance with local regulations Only store in correctly labelled containers. This material and its container must be disposed of as hazardous waste. Do not empty into drains. .

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1210
UN No. (IMDG)	1210
UN No. (ICAO)	1210
UN No. (ADN)	1210

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PRINTING INK
Proper shipping name (IMDG)	PRINTING INK
Proper shipping name (ICAO)	PRINTING INK
Proper shipping name (ADN)	PRINTING INK

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ADN packing group	II
ICAO packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-E, S-D
-----	----------

IC-2BK130 PRINTING INK

ADR transport category	2
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
--	-----------------

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Health and Safety at Work etc. Act 1974 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits.
Seveso Directive - Control of major accident hazards	P5c Lower-tier 5000 tonnes Upper-tier 50000 tonnes.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	ATE: Acute Toxicity Estimate. CAS: Chemical Abstracts Service. DNEL: Derived No Effect Level. EC ₅₀ : 50% of maximal Effective Concentration. GHS: Globally Harmonized System. IARC: International Agency for Research on Cancer. IATA: International Air Transport Association. Kow: Octanol-water partition coefficient. LC50: Lethal Concentration to 50 % of a test population. LD50: Lethal Dose to 50% of a test population (Median Lethal Dose). LOAEL: Lowest Observed Adverse Effect Level. NOAEL: No Observed Adverse Effect Level. PBT: Persistent, Bioaccumulative and Toxic substance. PNEC: Predicted No Effect Concentration. REACH: The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577. SVHC: Substances of Very High Concern. vPvB: Very Persistent and Very Bioaccumulative.
Key literature references and sources for data	Source: European Chemicals Agency, http://echa.europa.eu/ Supplier's information.
Classification procedures according to SI 2019 No. 720	: Calculation method.
Training advice	Only trained personnel should use this material. No action shall be taken without appropriate training or involving any personal risk. Ensure operatives are trained to minimise exposure. Ensure procedures and training for emergency decontamination and disposal are in place.
Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	14/05/2024
Revision	4

IC-2BK130 PRINTING INK

Supersedes date	22/12/2022
SDS number	329
Hazard statements in full	H225 Highly flammable liquid and vapour. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.