

320 Watt MC4 Poly Solar Panel PV Module Offgrid Solar Panel CE For Battery

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 100PCS

China

CE

Linksun

LS-320P

- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:
- 1pcs/carton 5-8days 30% TT in advance, 70% balance before delivery. 1000pieces per week



Product Specification

Cell Type:	Polycrystalline
Connector:	MC4
 Efficiency: 	16.66%
 Lifespan: 	25 Years
Operating Temperature:	-40 ~+85
Packaging:	Carton
 Product Name: 	320w Poly Solar Panel
• Size:	1950*992*40mm
Warranty:	25 Years
Weight:	23kg
Highlight:	320 watt Poly Solar Panel, MC4 Poly Solar Panel PV Module, 320W offgrid solar panel CE



Our Product Introduction

320 Watt MC4 Poly Solar Panel PV Module Offgrid Solar Panel CE For Battery

This 320W polycrystalline solar panel, equipped with MC4 connectors, is ideal for off-grid systems and battery charging. Certified by CE, it ensures high efficiency and reliable performance. Designed for durability, it is perfect for various applications, including residential, commercial, and remote locations. Its advanced technology provides optimal energy output, making it a cost-effective and sustainable energy solution. Ideal for those seeking to reduce energy costs and environmental impact, this solar panel offers a versatile and eco-friendly power source.

Product Features:

1)Durable&Sturdy

The product contains anodized aluminum alloy frame. It can work in the temperature between -40 ~85 and withstand the high winds (2400Pa) and snow loads (5400Pa).

2)Wide application

Common applications includes RV, camper, car, marine, residential rooftop, remote farm, traffic signs, etc.

3)eco-friendly

It uses polycrystalline solar cells. A poly crystalline solar panel is economical, eco-friendly, consumes less energy, and can function in all temperatures.

Product Details:

Model	LS-320P
Maximum Power(Pmax)	320W
Maximum Power Voltage(Vmp)	36.63V
Maximum Power Current(Imp)	8.74A
Open Circuit Voltage(Voc)	45.82V
Short Circuit Current(Isc)	9.42A
Power Tolerance(Positive)	3%
Cell Type	Poly-crystalline
Contract Dimensions(mm)	1950*992*40mm
Weight(KGS)	23kg
Protection Class	IP65
Maximum System Voltage	1000V
Temperature Range	-40 ~85
Module Efficiency STC	16.66%
Cell number	72(6x12)
Front Glass	3.2mm High Transmission Tempered Glass
Frame Type	Anodized Aluminum Alloy
Connector Type	MC4
Output Cables	4 mm ² ,Length:900mm

FAQ:

Q1:What's the solar panels warranty?

A: 5 year's warranty. If you have any questions about our quality during use, you can contact us at any time.

Q2:Do you accept OEM/ODM orders? A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order? A:Yes,of course.The lead time for samples is 7-10 days.

+8615888168085

Q4:Are you manufacturer or a trading company? A:We are manufacturer and our factory is based in Yuyao,Ningbo.Welcome your visit if you like.

Q5:Where are your goods exported? A:We can export to all over the world.

LINKS Ningbo Linksun Energy Science & Technology Co., LTD

@ monosolarpanel.com

sales02@zjlinksun.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China