



695w N Type Silicon Solar Panels High Efficiency Solar Panels

Basic Information

Place of Origin: China
Brand Name: Linksun
Certification: CE

Model Number: LS-D695M
 Minimum Order Quantity: 100PCS
 Packaging Details: 1pcs/carton
 Delivery Time: 5-8days

• Payment Terms: 30% TT in advance, 70% balance before

delivery.

Supply Ability: 1000pieces per week



Product Specification

• Application: RV,Home,House,Boat,Farm

Connector Type: MC4Efficiency: 22.4%Lifespan: 25 Years

Material: Monocrystalline Silicon

• Power: 695W

• Size: 2384*1303*33mm(93.85x51.29x1.30 Inches)

• Temperature Range: -40 ~+85

• Type: N Type Mono-crystalline 210x105mm

Warranty: 25 YearsWeight: 34kg

• Highlight: 695w Silicon Solar Panels,

N type Silicon Solar Panels, 695 watt high efficiency solar panels

Linksun Monocrystalline 695w silicon solar panels with 25 Years Warranty

These premium monocrystalline silicon solar panels deliver 695W of power and come with a 25-year warranty, ensuring long-lasting reliability and performance. Ideal for both residential and commercial installations, they are designed for maximum energy efficiency. With advanced technology and robust construction, these panels optimize energy capture even in low-light conditions, providing a sustainable and cost-effective energy solution.

Product Features:

1)High Efficiency

High modules conversion efficiency. Grade A solar cell and IP68 Rated waterproof solar panel connectors. This solar panel has 5 year 95% output warranty, 10 year 90% output warranty, 25 year 80% output warranty.

2)Reliable and Durable

Corrosion-resistant aluminum frame provides extended outdoor use that ensures the panel can last for decades. The IP68 rated junction box and solar connectors can withstand dirt, dust, debris, and water splashes.


3)High Tolerance

It can tolerate any part of the battery's shading, and performs well in low light conditions due to an increase in the number of batteries receiving more sunlight.

Product Details:

Model	LS-D695M	
Maximum Power(Pmax)	695W	
Maximum Power Voltage(Vmp)	39.8V	
Maximum Power Current(Imp)	17.47A	
Open Circuit Voltage(Voc)	47.7V	
Short Circuit Current(Isc)	18.44A	
Power Tolerance(Positive)	3%	
Cell Type	N type Mono-crystalline 210x105mm	
Product Dimension(mm)	2384*1303*33mm(93.85x51.29x1.30 inches)	
Weight(KGS)	34kg	
Protection Class	IP68 rated	
Maximum System Voltage	DC 1500V	
Operating Temperature Range	-40 ~85	
Module Efficiency STC	22.4%	
Cell number	132(6x22)(Half-Cell)	
Front Glass	3.2mm High Transmission Tempered	
	Glass(0.13 inches)	
Connector Type	MC4	
Output Cables	4.0 mm ² (0.006 inches ²),Length:1300mm	

Temperature Characteristics		Packing Configuration	
Temp.Coeff.of Isc(TK Isc)	0.05%/	Container	40'HQ
Temp.Coeff.of Voc(TK Voc)	-0.25%/	Pieces per pallet	66
Temp.Coeff.of Pmax(TK Pmax)	-0.29%/	Pallets per container	9
Normal operating cell Temperature	41±3	Pieces per container	594



FAQ:

Q1:What's the solar panels warranty?

A: 5 year's warranty. If you have any questions about our quality during use, you can contact us at any time.

Q2:Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order?

A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao, Ningbo. Welcome your visit if you like.

Q5:Where are your goods exported?

A:We can export to all over the world.



Ningbo Linksun Energy Science & Technology Co., LTD



+8615888168085



sales02@zjlinksun.com



e monosolarpanel.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China