



5W Mono Solar Panels 600V With 25 Years Warranty

Our Product Introduction

for more products please visit us on monosolarpanel.com

Basic Information

- Place of Origin: China
- Brand Name: Linksun
- Certification: CE、BSCI
- Model Number: LS-5M
- Minimum Order Quantity: 100PCS
- Packaging Details: 1pcs/carton
- Delivery Time: 5-8days
- Payment Terms: 30% TT in advance, 70% balance before delivery.
- Supply Ability: 1000pieces per week



Product Specification

- Cell Type: 5W Mono Solar Panels 600V With 25 Years Warranty
- Certifications: CE, BSCI
- Product Dimension(mm): 270*150*17mm
- Efficiency: 22%
- Output Cables: 4 Mm²,Length:1300mm
- Protection Class: IP68
- Type Of Connector: MC4
- Warranty: 25 Years
- Highlight: **5W Mono Solar Panels, 600V Mono Solar Panels , 25 Years Warranty Mono Solar Panels**

Product Description

5W Mono Solar Panels 600V With 25 Years Warranty

Solar panels harness the sun's energy, which is a renewable and abundant resource. By using solar power, you reduce reliance on finite fossil fuels, contributing to a cleaner and more sustainable energy future.

Product Features:

1)High Efficiency

High modules conversion efficiency. Grade A solar cell and IP68 Rated waterproof solar panel connectors. This solar panel has 5 year 95% output warranty, 10 year 90% output warranty, 25 year 80% output warranty.

2)Reliable and Durable

Corrosion-resistant aluminum frame provides extended outdoor use that ensures the panel can last for decades. The IP68 rated junction box and solar connectors can withstand dirt, dust, debris, and water splashes.

3)High Tolerance

It can tolerate any part of the battery's shading, and performs well in low light conditions due to an increase in the number of batteries receiving more sunlight.

Product Details:

Model	LS-05M
Maximum Power(Pmax)	5W
Maximum Power Voltage(Vmp)	18V
Maximum Power Current(Imp)	0.28A
Open Circuit Voltage(Voc)	22.4V
Short Circuit Current(Isc)	0.3A
Power Tolerance(Positive)	3%
Cell Type	N type Mono-crystalline,182x91mm
Product Dimension(mm)	265*175*17mm
Weight(KGS)	0.5kg
Protection Class	IP68
Maximum System Voltage	1500V DC-(H)
Temperature Range	-40 ~85
Module Efficiency STC	21.48%
Cell number	36
Front Glass	(F)2.0mm ultra clear embossed double layer colorless glass (B)2.0mm semi-tempered glass
Connector Type	MC4
Output Cables	4 mm ² ,Length:1300mm



FAQ:

Q1:What's the solar panels warranty?

A: 5 year's warranty.If you have any questions about our quality during use,you can contact us at any time.

Q2:Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order?

A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao,Ningbo.Welcome your visit if you like.

Q5:Where are your goods exported?

A:We can export to all over the world.



Ningbo Linksun Energy Science & Technology Co., LTD



+8615888168085



sales02@zjlinksun.com



monosolarpanel.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China