



300 Watt Poly Solar Panel 23kg Anodized Polycrystalline Silicon Cell

Our Product Introduction

for more products please visit us on monosolarpanel.com

Basic Information

- Place of Origin: China
- Brand Name: Linksun
- Certification: CE
- Model Number: LS-300P
- Minimum Order Quantity: 100PCS
- Packaging Details: 1pcs/carton
- Delivery Time: 5-8days
- Payment Terms: 30% TT in advance, 70% balance before delivery.
- Supply Ability: 1000pieces per week



Product Specification

- Cell Type: Polycrystalline
- Connector Type: MC4
- Frame Material: Anodized Aluminum Alloy
- Junction Box: IP65
- Operating Temperature: -40°C To +85°C
- Power: 300W
- Product Name: 300w Poly Solar Panel
- Size: 1950*992*40mm
- Warranty: 25 Years
- Weight: 23kg
- Highlight: **Battery Poly Solar Panel,
300 watt Poly Solar Panel,
23kg Anodized polycrystalline silicon cell**



Product Description

300 Watt Poly Solar Panel 23kg Anodized Polycrystalline Silicon Cell

This 300W polycrystalline solar panel, weighing 23kg, features durable anodized construction. Engineered with high-efficiency polycrystalline silicon cells, it provides reliable energy output for residential and commercial applications. Its robust design ensures long-lasting performance and optimal energy production. Ideal for reducing energy costs and environmental impact, this panel is a sustainable and cost-effective energy solution. Perfect for various installations, it offers an eco-friendly way to harness solar power efficiently.

Product Features:

1)Durable&Sturdy

The product contains anodized aluminum alloy frame. It can work in the temperature between -40 ~85 and withstand the high winds (2400Pa) and snow loads (5400Pa).

2)Wide application

Common applications include RV, camper, car, marine, residential rooftop, remote farm, traffic signs, etc.

3)eco-friendly

It uses polycrystalline solar cells. A polycrystalline solar panel is economical, eco-friendly, consumes less energy, and can function in all temperatures.

Product Details:

| | |
|----------------------------|--|
| Model | LS-300P |
| Maximum Power(Pmax) | 300W |
| Maximum Power Voltage(Vmp) | 36.2V |
| Maximum Power Current(Imp) | 8.28A |
| Open Circuit Voltage(Voc) | 45.5V |
| Short Circuit Current(Isc) | 9.11A |
| Power Tolerance(Positive) | 3% |
| Cell Type | Poly-crystalline |
| Contract Dimensions(mm) | 1950*992*40mm |
| Weight(KGS) | 23kg |
| Protection Class | IP65 |
| Maximum System Voltage | 1000V |
| Temperature Range | -40 ~85 |
| Module Efficiency STC | 15.62% |
| Cell number | 72(6x12) |
| Front Glass | 3.2mm High Transmission Tempered Glass |
| Frame Type | Anodized Aluminum Alloy |
| Connector Type | MC4 |
| Output Cables | 4 mm ² , Length:900mm |

FAQ:

Q1:What's the solar panels warranty?

A: 5 year's warranty. If you have any questions about our quality during use, you can contact us at any time.

Q2:Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders. Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order?

A:Yes, of course. The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao, Ningbo. Welcome your visit if you like.

Q5:Where are your goods exported?

A:We can export to all over the world.



Ningbo Linksun Energy Science & Technology Co., LTD



+8615888168085



sales02@zjlinksun.com



monosolarpanel.com

