



330w 36.89V Solar Panel All Black Polycrystal Solar Panel

Basic Information

Place of Origin: China
Brand Name: Linksun
Certification: CE
Model Number: LS-330P
Minimum Order Quantity: 100PCS
Packaging Details: 1pcs/carton
Delivery Time: 5-8days

• Payment Terms: 30% TT in advance, 70% balance before

delivery.

Supply Ability: 1000pieces per week



Product Specification

Cell Type: Poly-crystalline

Connector Type: MC4Efficiency: 16.86%

Frame Material: Anodized Aluminum Alloy

Junction Box: IP65Power: 330W

• Product Name: 330W Black Solar PV Panel

Size: 1950*992*40mmWarranty: 25 YearsWeight: 23kg

• Highlight: 330w solar panel all black,

36.89V solar panel all black, 330 watt polycrystal solar panel

Linksun 330w Black Polycrystalline solar panels

The 330W 36.89V All Black Polycrystal Solar Panel combines high efficiency with a sleek design. Ideal for residential and commercial installations, it delivers reliable performance even in low-light conditions. The all-black aesthetic enhances visual appeal, ensuring seamless integration with modern architecture. With robust construction, this panel offers long-term durability and low maintenance. Perfect for ecoconscious users, it helps reduce electricity costs and carbon footprint, providing a sustainable and efficient energy solution for a variety of applications.

Product Features:

1)Widely Use

Ideal for RVs, small houses, ships, household power supplies, commercial buildings, and more. It helps save electricity consumption and will save you more in the future.

2)Reliable and Durable

Corrosion-resistant aluminum frame provides extended outdoor use that ensures the panel can last for decades.

3)Low production cost

The production cost of monocrystalline silicon solar cells is relatively low, and the technology is already very mature, so it has been widely used.

Product Details:

Model	LS-330P
Maximum Power(Pmax)	330W
Maximum Power Voltage(Vmp)	36.89V
Maximum Power Current(Imp)	8.95A
Open Circuit Voltage(Voc)	46.12V
Short Circuit Current(Isc)	9.64A
Power Tolerance(Positive)	3%
Cell Type	Poly-crystalline
Contract Dimensions(mm)	1950*992*40mm
Weight(KGS)	23kg
Protection Class	IP65
Maximum System Voltage	1000V
Temperature Range	-40 ~85
Module Efficiency STC	16.86%
Cell number	72(6x12)
Front Glass	3.2mm High Transmission Tempered Glass
Frame Type	Anodized Aluminum Alloy
Connector Type	MC4
Output Cables	4 mm ² ,Length:900mm



FAQ:

Q1:What's the solar panels warranty?

A: 5 year's warranty. If you have any questions about our quality during use, you can contact us at any time.

Q2:Do you accept OEM/ODM orders?

A:We accept OEM/ODM orders.Welcome your inquiry.

Q3:Can I have samples to test?and what's the lead time for the sample order?

A:Yes,of course.The lead time for samples is 7-10 days.

Q4:Are you manufacturer or a trading company?

A:We are manufacturer and our factory is based in Yuyao, Ningbo. Welcome your visit if you like.

Q5:Where are your goods exported?

A:We can export to all over the world.



Ningbo Linksun Energy Science & Technology Co., LTD

+8615888168085



sales02@zjlinksun.com



@ monosolarpanel.com

2nd ,Floor,No.1 Building,Wanyang Entrepreneurial City,Yuyao,Zhejiang Province, China