

BICYCLE BATTERY

P O W E R E V E R Y J O U R N E Y



PRODUCTS CATALOG

MANUFACTURER

E-Bike Bicycle kit Battery pack

Hailong - Battery Silver Fish - battery

NEW ERA
ENERGY SAVING

ABOUT SAILI—



Dongguan Zhongda Electronic Technology Co., Ltd. was established in 2017. It is a lithium battery factory integrating R&D, design, production and sales. The company's main products include electric bicycle batteries, energy storage batteries, cylindrical batteries, polymer batteries, etc. It has many engineers specializing in the R&D and design of lithium battery processes. The company constantly serves customers with professional knowledge based on the market and customers' demands for original products.



OUR COMPANY



COMPANY CERTIFICATE



CONTENTS

☆ TITLE	PAGE
☆ BICYCLE BATTERY	01-02
☆ HAILONG LITHIUM BATTERY	03-04
☆ SILVER FISH LITHIUM BATTERY	05
☆ ELECTRIC VEHICLE BATTERY	06-07
☆ OUTDOOR POWER SUPPLY	08-09
☆ BATTERY PACK	10-11
☆ BICYCLE KIT	12-13



— Triangular bicycle battery



1 Triangle Battery

BASIC PARAMETERS

Model		
Parameter	48V20AH	52V28AH
Permutation	13S8P	14S8P
Cell Capacity	18650-2.6AH	18650-3.5AH
It Motor Power	Below 1500W	Below 2000W
Dimensions	395*355*225*75mm	



2 Triangle Battery

BASIC PARAMETERS

Model			
Parameter	52V30AH	60V25AH	72V20AH
Permutation	14S6P	16S5P	20S4P
Cell Capacity	21700-5AH	21700-5AH	21700-5AH
It Motor Power	Below 2000W	Below 3000W	Below 3000W
Dimensions	400*365*230*85mm		



3 Triangle Battery

BASIC PARAMETERS

Model				
Parameter	48V20AH 28AH / 30AH	52V20AH / 28AH / 30AH	60V25AH	72V20AH
Permutation	13S8P	14S8P	16S5P	20S4P
Cell Capacity	18650-2.6AH	18650-2.6AH/3.5AH 21700 5AH	21700 5AH	21700 5AH
It Motor Power	Below 1500W	Below 2000W	Below 2000W	Below 3000W
Dimensions	330*220*180mm			



— Triangular bicycle battery



4 Triangle Battery

BASIC PARAMETERS

Model			
Parameter	48V50AH	60V40AH	72V35AH
Permutation	13S10P	16S8P	20S7P
Cell Capacity	21700-5AH	21700-5AH	21700-5AH
It Motor Power	Below 1500W	Below 3000W	Below 3000W
Dimensions	445*400*265*95mm		



5 Triangular cloth bag

BASIC PARAMETERS

Model:	
Parameter:	72V40AH
Permutation:	20S8P
Cell Capacity:	21700-5AH
It Motor Power:	Below 6000W
Dimensions:	510*443*300*80mm



Hailong type battery



① Hailong -G80

BASIC PARAMETERS

Model		
Parameter	48V20AH	48V21AH
Permutation	13S4P	13S6P
Cell Capacity	21700-5AH	18650/3.5AH
It Motor Power	Below 1000W	Below 1000W
Dimensions	368*127*90mm	



② Hailong-Plus

BASIC PARAMETERS

Model		
Parameter	48V17.5AH	48V20AH
Permutation	13S5P	13S4P
Cell Capacity	18650/3.5AH	21700/5AH
It Motor Power	Below 1000W	Below 1000W
Dimensions	368*109*90mm	



③ Hailong-G56

BASIC PARAMETERS

Model			
Parameter	36V21AH	48V14AH	52V14AH
Permutation	10S6P	13S4P	14S4P
Cell Capacity	18650/3.5AH	18650/3.5AH	18650/3.5AH
It Motor Power	Below 1000W	Below 1000W	Below 1000W
Dimensions	362*93*90mm		



— Parrot lithium battery



1 Parrot 7

BASIC PARAMETERS

Model		
Parameter	36V13AH / 36V17.5AH	48V13AH / 48V17.5AH
Permutation	10S5P	13S5P
Cell Capacity	18650 / 2.6AH / 3.5AH	18650 / 2.6AH / 3.5AH
It Motor Power	Below 1000W	Below 1000W
Dimensions	368*90*113mm	



2 Parrot 6

BASIC PARAMETERS

Model		
Parameter	48V20AH / 48V25AH	52V20AH / 52V25AH
Permutation	13S5P	14S5P
Cell Capacity	21700-5AH	21700/5AH
It Motor Power	Below 1000W	Below 1000W
Dimensions	368*95*157mm	



3 Parrot 9

BASIC PARAMETERS

Model			
Parameter	48V18.2AH	48V20AH	48V24.5AH
Permutation	13S7P	13S7P	13S7P
Cell Capacity	18650/2.6AH	18650/2.9AH	18650/3.5AH
It Motor Power	Below 1000W	Below 1000W	Below 1000W
Dimensions	368*90*141mm		



Silver Fish lithium battery



1 Silver fish

BASIC PARAMETERS

Model			
Parameter	48V17.5AH	48V20AH	48V28AH
Permutation	13S5P	13S8P	13S8P
Cell Capacity	18650/3.5AH	18650/2.6AH	18650/3.5AH
It Motor Power	Below 1000W	Below 1500W	Below 1500W
Dimensions	405*110*76mm		



2 Silver fish-009

BASIC PARAMETERS

Model		
Parameter	36V13AH / 36V17.5AH	48V13AH / 36V17.5AH
Permutation	10S5P	13S5P
Cell Capacity	18650 / 2.6AH/3.5AH	18650 / 2.6AH/3.5AH
It Motor Power	Below 500W	Below 500W
Dimensions	430*100*44mm	



3 Silver fish-006

BASIC PARAMETERS

Model			
Parameter	48V13AH 48V17.5AH	48V10AH	48V14AH
Permutation	10S5P	13S4P	13S4P
Cell Capacity	18650/2.6AH	18650/2.6AH	18650/3.5AH
It Motor Power	Below 500W	Below 500W	Below 500W
Dimensions	430*100*44mm		



—Electric motorcycle



1 E-Bike

BASIC PARAMETERS

Model			
Parameter	52V50AH	52V70AH	52V80AH
Permutation	14S1P	14S1P	14S1P
Cell Capacity	50AH	70AH	80AH
It Motor Power	Below 3000W	Below 3000W	Below 3000W
Dimensions	340*187*165mm		



2 E-Bike

BASIC PARAMETERS

Model			
Parameter	60V40AH	60V50AH	60V80AH
Permutation	16S1P	16S1P	16S1P
Cell Capacity	40AH	50AH	80AH
It Motor Power	Below 3000W	Below 5000W	Below 5000W
Dimensions	220*340*170mm		



3 E-Bike

BASIC PARAMETERS

Model				
Parameter	72V30AH	72V40AH	72V50AH	72V80AH
Permutation	20S1P	20S1P	20S1P	20S1P
Cell Capacity	30AH	40AH	50AH	80AH
It Motor Power	Below 2000W	Below 3000W	Below 3000W	Below 5000W
Dimensions	330*220*180mm			



—Off-road electric vehicle battery



4 E-Bike

BASIC PARAMETERS

Model		
Parameter	72V30AH	72V45AH
Permutation	20S6P	20S9P
Cell Capacity	21700-5AH	21700/5AH
It Motor Power	Below 5000W	Below 5000W
Dimensions	400*160*140mm	



6 E-Bike

BASIC PARAMETERS

Model		
Parameter	72V30AH	72V45AH
Permutation	20S6P	20S9P
Cell Capacity	21700-5AH	21700/5AH
It Motor Power	Below 1500W	Below 1500W
Dimensions	400*160*145mm	



—Outdoor power supply



—Electric freedom is the true wild freedom





BASIC PARAMETERS



Model:	1000W	1500W	3000W
Capacity:	100Ah	100Ah	130Ah
Input voltage:	1000W	1500W	3000W
Output power:	12V	24V	24V
Output voltage:	~220V 50HZ	~220V 50HZ	~220V 50HZ
Charging duration:	8-12H	8-12H	8-15H
Charging parameters:	DC12.6V/5A/8A/10A DC29.2V/5A/8A/10A/15A		
Weight:	11KG	19KG	36KG



Large-capacity fast charging - all for mobile phones, cameras, drones and small refrigerators



— Off-road electric vehicle battery

Application field

Lithium batteries allow energy to flow freely - from palm phones to electric vehicles, from outdoor power sources to aerospace equipment, empowering every wonderful moment with high energy density and long-lasting battery life



BASIC PARAMETERS

Model				
Parameter	12V20AH	24V20AH	36V20AH	48V20AH
Permutation	3S8P	6S8P	10S8P	13S8P
Cell Capacity	18650 2.6AH	18650 2.6AH	18650 2.6AH	18650 2.6AH
It Motor Power	Below 500W	Below 800W	Below 1000W	Below 1500W
Dimensions	Customizable voltage and capacity			



1 Battery pack



(Voltage)	(capacity)	(endurance)	(dimension)
12V	7Ah	About 20km	145*60*90mm 150*94*92mm
	10Ah	About 35km	
	20Ah	About 60km	
	30Ah	About 100km	
24V	10Ah	About 35km	145*114*70mm 166*135*70mm 166*135*70mm
	15Ah	About 50km	
	20Ah	About 70km	
	25Ah	About 80km	
	30Ah	About 100km	
36V	10Ah	About 30km	300*68*55mm 400*68*38mm 510*68*38mm
	15Ah	About 45km	
	21Ah	About 60km	
	26Ah	About 80km	
	28Ah	About 90km	
48V	10Ah	About 30km	350*68*55mm 400*68*38mm 340*95*55mm
	15Ah	About 45km	
	20Ah	About 60km	
	23Ah	About 70km	
	26Ah	About 80km	

APPLICATION MODEL





— Off-road electric vehicle battery

Hailong bicycle kits



Waterproof



Anti-misplug

Product parameters

Motor	350W-1000W
Voltage	36V/48V
Controller	smart controller
Display	SW900 display
Brake	brake lever
Rim	20"-29"/700c



Triangular hard shell bicycle kit



Waterproof



Anti-misplug

Product parameters

Motor	500W-1000W
Voltage	36V/52V
Controller	smart controller
Display	SW900 display
Brake	brake lever
Rim	20"-29"/700c





Triangular cloth bag with bicycle kit



Waterproof



Anti-misplug

Product parameters

Motor	1000W-5000W
Voltage	52V/72V
Controller	smart controller
Display	SW900 display
Brake	brake lever
Rim	20"-29"/700c



Triangular hard shell bicycle kit



Waterproof



Anti-misplug

Product parameters

Motor	500W-1000W
Voltage	36V/52V
Controller	smart controller
Display	SW900 display
Brake	brake lever
Rim	20"-29"/700c





CHARGE CONNECTOR



CANNON Female



RCA Female



DC5521/5525 Female



3Pin/4Pin Female

DISCHARGE CONNECTOR



XT60-F



XT60-M



XT90-F



XT90-M



T port Male



T port Female



Bullet port



Bullet port



Anderson30A



Anderson50A



QS8-S-F



QS8-S-M



3 Pin port Male



3 Pin port Female



3 Pin port Male



3 Pin port Female

Manufacture | OEM/ODM 20 YRS

Alibaba's Choice

Best Seller



CONTACT US

✉ **E-mail:** Zhongdacompany@gmail.com

☎ **Tel:** Zhongda Company +86 18826974860

👤 **Tel:** Zhongda +86 13434542379

🌐 **Web:** www.zhongdabattery.com

<https://zdcell.en.alibaba.com>

