

NP series lead acid maintenance free storage battery

Maintenance-free, no need to replenish liquid, long service life, small self-discharge, small internal resistance, good high-current discharge characteristics, unique formula with good recovery performance from deep discharge, safe and explosion-proof, no free electrolyte, can still be used even if it is turned upside down by 90 degrees.



APPLICATIONS

- Uninterruptible power supply
- Electric power system (EPS)
- Emergency backup system
- Emergency light
- Railway signal / aircraft signal
- Alarm and security system
- Electronic equipment / auto control system device

Model	Rated Voltage (V)	Rated voltage capacity 25°C (AH)		Size				terminals
		20HR 1.75V/CELL	10HR 1.75V/CELL	L±1 (MM)	W±1 (MM)	H±2 (MM)	H±2 (MM)	
NP6V1.2AH	6	1.2	1.1	97	25	52	58	E
NP6V4.5AH	6	4.5	4	70	47	102	105	E
NP6V8AH	6	8	7.4	151	50	94	98	E
NP6V10AH	6	10	9.3	151	50	94	98	E
NP12V1.2AH	12	1.2	1.1	97	48	52	58	E
NP12V2.0AH	12	2	1.9	178	34	60	64	E
NP12V4.5AH	12	4.5	4.1	90	70	102	105	E
NP5V12AH	12	5	4.6	90	70	102	105	E
NP12V7AH	12	7.5	7.0	151	65	94	98	E
NP12V8AH	12	8	7.5	151	65	94	98	E
NP12V12AH	12	12	11.1	151	98	98	101	E
NP12V14AH	12	14	13	151	98	98	101	E
NP12V17AH	12	17	15.8	181	76	167	125	G
NP12V24AH	12	2.6	24	166	125	175	175	G
NP12V30AH	12	30	28	166	175	175	175	G
NP12V38AH	12	41	38	197	165	170	170	G
NP12V55AH	12	55	51	236	205	205	239	G
NP12V65AH	12	70	65	350	174	174	174	G
NP12V100AH	12	100	93	400	172	215	243	G
NP12V120AH	12	150	110	405	172	210	240	G
NF12Y150AH	12	160	150	480	172	240	240	G
NP12V180AH	12	200	186	524	216	216	244	G
NP12V200AH	12	218	200	524	216	216	244	G
NP12V250AH	12	262	250	522	268	220	225	G

Products specifications are subject to change without further notice