

Line Interactive UPS MT600-3000VA



FUNCTIONS

- Small and delicate
- Wide input voltage range
- Excellent microprocessor ensures operation
- Automatic voltage regulation
- Automatic restart function for utility power
- Simulated sine wave

APPLICATIONS

- Personal computer
- Printer
- POS(Point of sales) terminals
- Security system
- Fax machine
- Modem , router

Model	MT500	MT600	SP1000	MT2000	MT3000	
Capacity	500VA/300W	600VA/360W	1KVA/600W	2KVA/1200W	3KVA/1800W	
Importation						
Input voltage	110/120/200/220/230/240Vac					
Input voltage range	140-280V					
Input frequency	50±HZ					
Output						
Battery voltage	110/120/200/220/230/240Vac					
Output voltage range	±10%					
Output frequency	50±HZ					
Transfer time	≤6ms					
Battery						
Standard UPS	Battery voltage		12V	24V	24V	24V
	Battery model		12V/7AH	12V/9AH	12V/9AH	12V/9AH
	Battery quantity		1	1	2	4
	Charging time	10-16 Hours to 90% full capacity				
Model						
External battery UPS	Battery voltage	MT500(S)	MT600(S)	SP1000(S)	MT2000(S)	MT3000(S)
	Battery model	12V	12V	24V	24V	24V
	Battery quantity	External battery				
	Charging time	Depends on the external battery capacity				
Display description						
Display status	LCD					
Protection function	Automatic detection and discharge protection, input short circuit protection, overload protection					
Warning sound						
Battery mode	Beep every 4 seconds					
Low battery	Beep every second					
Overload	Beep every second					
Error	Continuous Beep					
Physical property						
Standard UPS	Size (MM)		320*90*140	365*140*165	365*140*165	395*145*210
	Weight(KG)		5.1	5.7	12.6	21
External battery UPS	Size (MM)	320*90*140		365*140*165	395*145*210	
	Weight(KG)	3.5		4.2	10.2	13.7
Usage environment						
Humidity	0-90% Humidity and 0-40 °C Temperature					
Noise	<40db					

Products specifications are subject to change without further notice