

DC Mini UPS Power Supply 18W/24W/36W



FUNCTIONS

- Built-in adapter, wide voltage input, provide customization various plugs
- Built-in large-capacity lithium-ion batteries, long backup time.
- Intelligent power management, automatic transfer from AC mode to battery mode
- With a variety of high-power voltage output ports and strong compatibility
- LED indicator light display design, the machine running status is clear
- Built-in multiple protection circuits, intelligently realize over-charge, over-discharge, over-current, overload, over-temperature and short circuit protection, safer to use

DC SERIES	18W			24W	36W		
Model	DC1018CP	DC1018	DC1018P	DC1024P	DC1036CP	DC1036	DC1036P
Input voltage	85-265Vac/50-60Hz						
Maximum output power	18W			24W	36W		
Output voltage	USB 5V/2A	USB 5V/2A	USB 5V/2A	USB 5V/2A		USB 5V/2A	USB 5V/2A
	DC 9V(12V)/1A	DC 5V/2A	DC 5V/2A	DC 5V/2A	USB 5V/2A	DC 5V/2A	DC 5V/2A
	POE 15V/0.6A	DC 9V/1A	DC 9V/1A	DC 9V/2A	DC 9V/12V(3A)	DC 9V/2A	DC 9V/2A
	POE 24V/0.6A	DC 12V/1A	DC 12V/1A	DC 12V/2A	POE 15V/1A	DC 12V/2A	DC 12V/2A
			POE 15V/0.6A	POE 15V/1A	POE 24V/1A		POE 15V/1A
			POE 24V/0.6A	POE 24V/1A			POE 24V/1A
Efficiency	AC mode:>85%, municipal power mode: >85%, Battery mode:>90%						
Battery specifications	18650						
Battery material	Lithium-Ion battery/LiFePO4 battery						
Battery capacity	2000mah~2600mah						
Battery quantity	4						
Shell material	ABS						
Shell color	Black、 White (Provide color customization)						
Protection function	Over-charge, over-discharge, over-current, overload, over-temperature and short circuit protection						
Work temperature	0℃-40℃						
Storage temp	-10℃-70℃						
Relative humidity	10%-90%RH						
Altitude	<3000m						
Noise	<30db						
Product size	160*105*33mm						
Package size	180*160*37mm						
Net weight	0.38kg	0.4kg	0.39kg	0.4kg	0.41kg	0.4kg	0.42kg
Gross weight	0.51kg	0.53kg	0.5kg	0.52kg	0.55kg	0.51kg	0.56kg

Products specifications are subject to change without further notice