



SIMATIC S7-300, Digital input SM 321, isolated, 16 DI; 24 V DC, 1x 20-pole, process interrupt, diagnostics, suitable for isochronous mode

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	90 mA
from backplane bus 5 V DC, max.	130 mA
Encoder supply	
Number of outputs	2
Type of output voltage	L+ (-2.5 V)
Short-circuit protection	Yes; Electronic
additional (redundant) feed	Yes
Output current	
• Rated value	120 mA
• permissible range, lower limit	0 mA
• permissible range, upper limit	150 mA
Power loss	
Power loss, typ.	4 W
Digital inputs	
Number of digital inputs	16
Input characteristic curve in accordance with IEC 61131, type 2	Yes
Number of simultaneously controllable inputs	
horizontal installation	
— up to 40 °C, max.	16
— up to 60 °C, max.	16
vertical installation	
— up to 40 °C, max.	16
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-30 to +5 V
• for signal "1"	13 to 30V
Input current	
• for signal "1", typ.	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.1 / 0.5 / 3 / 15 / 20 ms
Encoder connection	

<ul style="list-style-type: none"> <li>• Fixed current limitation for wire-break monitoring, min.</li> </ul>	10 kΩ
<ul style="list-style-type: none"> <li>• Fixed current limitation for wire-break monitoring, max.</li> </ul>	18 kΩ
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	1 000 m
<ul style="list-style-type: none"> <li>• unshielded, max.</li> </ul>	600 m
<b>Encoder</b>	
<b>Connectable encoders</b>	
<ul style="list-style-type: none"> <li>• 2-wire sensor</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— permissible quiescent current (2-wire sensor), max.</li> </ul>	2 mA
<b>Interrupts/diagnostics/status information</b>	
<b>Alarms</b>	Yes
<b>Diagnostics function</b>	Yes; Parameterizable
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>• Diagnostic alarm</li> </ul>	Yes; Parameterizable
<ul style="list-style-type: none"> <li>• Hardware interrupt</li> </ul>	Yes; Parameterizable
<b>Diagnoses</b>	
<ul style="list-style-type: none"> <li>• Diagnostic information readable</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Wire-break</li> </ul>	Yes; to I < 1 mA
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>• Group error SF (red)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Status indicator digital input (green)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Encoder supply Vs (green)</li> </ul>	Yes
<b>Potential separation</b>	
<b>Potential separation digital inputs</b>	
<ul style="list-style-type: none"> <li>• between the channels</li> </ul>	No
<ul style="list-style-type: none"> <li>• between the channels, in groups of</li> </ul>	16
<ul style="list-style-type: none"> <li>• between the channels and backplane bus</li> </ul>	Yes; Optocoupler
<b>Isolation</b>	
<b>Isolation tested with</b>	500 V DC
<b>connection method</b>	
<b>required front connector</b>	20-pin
<b>Dimensions</b>	
<b>Width</b>	40 mm
<b>Height</b>	125 mm
<b>Depth</b>	120 mm
<b>Weights</b>	
<b>Weight, approx.</b>	200 g

**last modified:** 3/12/2024 