

*** SPARE PART*** SIMATIC S7-300, CPU 314 CPU WITH INTEGRATED 24 V DC POWER SUPPLY 24 KBYTE WORKING MEMORY

Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V

Input current

Current consumption (rated value)	1 000 mA
Inrush current, typ.	8 A

Power loss

Power loss, max.	8 W
------------------	-----

Memory

Work memory	
<ul style="list-style-type: none"> integrated 	24 kbyte; 24 KB/8 K instructions RAM (integrated); 1 instruction means 3 bytes on average
Load memory	
<ul style="list-style-type: none"> expandable FEPRM 	Yes; Flash-EPRM
<ul style="list-style-type: none"> expandable FEPRM, max. 	4 Mbyte
<ul style="list-style-type: none"> integrated RAM, max. 	40 kbyte
Backup	
<ul style="list-style-type: none"> present 	Yes
<ul style="list-style-type: none"> with battery 	Yes; all blocks
<ul style="list-style-type: none"> without battery 	Yes; 4 KB: bit memory, counter, times and data

CPU processing times

for bit operations, typ.	0.3 μ s
for bit operations, max.	0.6 μ s
for word operations, typ.	1 μ s
for fixed point arithmetic, typ.	2 μ s
for floating point arithmetic, typ.	50 μ s
for timer/counter operations, typ.	12 μ s

CPU-blocks

DB	
<ul style="list-style-type: none"> Number, max. 	127
<ul style="list-style-type: none"> Size, max. 	8 kbyte
FB	

• Number, max.	128
• Size, max.	8 kbyte
FC	
• Number, max.	128
• Size, max.	8 kbyte
OB	
• Description	see instruction list
• Size, max.	8 kbyte
• Number of free cycle OBs	1; OB 1
• Number of time alarm OBs	1; OB 10
• Number of cyclic interrupt OBs	1; OB 35
• Number of process alarm OBs	1; OB 40
• Number of startup OBs	1; OB 100
Nesting depth	
• per priority class	8
Counters, timers and their retentivity	
S7 counter	
• Number	64
of which retentive with battery	
— can be set	Yes
— lower limit	0
— upper limit	63
of which retentive without battery	
— can be set	Yes
— lower limit	0
— upper limit	63
Counting range	
— lower limit	1
— upper limit	999
S7 times	
• Number	128
of which retentive with battery	
— adjustable	Yes
— lower limit	0
— upper limit	127
of which retentive without battery	
— adjustable	Yes
— lower limit	0
— upper limit	127
Time range	
— lower limit	10 ms

— upper limit

9 990 s

Data areas and their retentivity

Flag

- | | |
|--------------------------------------|---|
| • Number, max. | 256 byte |
| • Retentivity available | Yes; MB 0 to MB 255 |
| • of which retentive with battery | 0 to 2 047 (M 0.0 to M 255.7, adjustable) |
| • of which retentive without battery | 0 to 2 047 (M 0.0 to M 255.7, adjustable) |

Address area

I/O address area

- | | |
|-----------|----------|
| • Inputs | 512 byte |
| • Outputs | 512 byte |

Process image

- | | |
|-----------|----------|
| • Inputs | 128 byte |
| • Outputs | 128 byte |

Digital channels

- | | |
|-----------|-------|
| • Inputs | 1 024 |
| • Outputs | 1 024 |

Analog channels

- | | |
|-----------|-----|
| • Inputs | 256 |
| • Outputs | 128 |

Addressing volume

- | | |
|-----------|----------|
| • Inputs | 122 byte |
| • Outputs | 122 byte |

Hardware configuration

- | | |
|-------------------------------------|---|
| Number of expansion units, max. | 3 |
| connectable programming devices/PCs | PGs/PCs with STEP 7 connectable via MPI interface |

- | | |
|--|----|
| Number of modules per DP slave interface, max. | 16 |
|--|----|

Number of DP masters

- | | |
|--------------|-------------|
| • integrated | 0 |
| • via CP | 1; CP 342-5 |

Number of operable FMs and CPs (recommended)

- | | |
|-----------|---|
| • FM | 4 |
| • CP, PtP | 2 |
| • CP, LAN | 1 |

Rack

- | | |
|--------------------------|----|
| • Modules per rack, max. | 32 |
|--------------------------|----|

Time of day

Clock

- | | |
|------------------------------|-----|
| • Hardware clock (real-time) | Yes |
|------------------------------|-----|

Interfaces

MPI	
<ul style="list-style-type: none"> • Cable length, max. 	9 100 m; without repeaters: 50 m; with 2 repeaters: 1100 m; with 10 repeaters in series: 9100 m; via fiber optic cable: 23.8 km (with 16 star hubs or OLMs)

1. Interface

Functionality

<ul style="list-style-type: none"> • MPI 	Yes
---	-----

MPI

<ul style="list-style-type: none"> • Number of nodes, max. 	32; 32 nodes on MPI bus; PG/PC, OP, additional S7-300/400, C7; per CPU max. 4 static and 4 dynamic connections
<ul style="list-style-type: none"> • Transmission rate, max. 	187.5 kbit/s

Services

— PG/OP communication	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes

Communication functions

PG/OP communication	Yes
---------------------	-----

Global data communication

<ul style="list-style-type: none"> • supported 	Yes
---	-----

S7 basic communication

<ul style="list-style-type: none"> • supported 	Yes
---	-----

S7 communication

<ul style="list-style-type: none"> • supported 	Yes
<ul style="list-style-type: none"> • as server 	Yes

S5 compatible communication

<ul style="list-style-type: none"> • supported 	Yes; via loadable blocks
---	--------------------------

Standard communication (FMS)

<ul style="list-style-type: none"> • supported 	Yes; via loadable blocks
---	--------------------------

Number of connections

<ul style="list-style-type: none"> • overall 	
— of which dynamic	8
— of which static	4

Configuration

Configuration software

<ul style="list-style-type: none"> • STEP 7 	Yes; V5.0, V5.0 SP1
--	---------------------

Programming

<ul style="list-style-type: none"> • Command set 	Binary logic operations, bracketed operations, result allocation, saving, counting, loading, transferring, comparing, shifting, rotating, complementation, calling blocks, fixed point arithmetic, floating point arithmetic, jump functions
<ul style="list-style-type: none"> • Nesting levels 	8

<ul style="list-style-type: none"> • Program organization • System functions (SFC) 	Linear, structured Interrupt and error processing, copy data, clock functions, diagnostic functions, module parameterization, operating mode transitions
<ul style="list-style-type: none"> • System function blocks (SFB) 	1
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— GRAPH	Yes
Software libraries	
— Process diagnostics	Yes
— Software controller	Yes; depending on the required memory space and the resulting execution time
Know-how protection	
<ul style="list-style-type: none"> • User program protection/password protection 	Yes
Cycle time monitoring	
<ul style="list-style-type: none"> • lower limit • upper limit • adjustable • preset 	1 ms 6 000 ms Yes 150 ms
Dimensions	
Width	80 mm
Height	125 mm
Depth	130 mm
Weights	
Weight, approx.	530 g; Memory card 16 g
last modified:	03/23/2017 