

*** SPARE PART*** SIMATIC S7-300, CPU 315-2 DP CPU WITH INTEGRATED 24 V DC POWER SUPPLY, 64 KBYTE WORKING MEMORY 2ND INTERFACE DP-MASTER/SLAVE

Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V

Input current

Current consumption (rated value)	1 000 mA
Inrush current, typ.	8 A

Power loss

Power loss, max.	8 W
------------------	-----

Memory

Work memory	
<ul style="list-style-type: none"> integrated 	64 kbyte; 64 KB / 21K instructions RAM (integrated)
Load memory	
<ul style="list-style-type: none"> expandable FEPRM 	Yes; Flash-EPRM
<ul style="list-style-type: none"> expandable FEPRM, max. 	4 Mbyte
<ul style="list-style-type: none"> integrated RAM, max. 	96 kbyte
Backup	
<ul style="list-style-type: none"> with battery 	Yes; all blocks
<ul style="list-style-type: none"> without battery 	Yes; 4 KB: bit memory, counter, times and data

CPU processing times

for bit operations, typ.	0.3 μ s
for bit operations, max.	0.6 μ s
for word operations, typ.	1 μ s
for fixed point arithmetic, typ.	2 μ s
for floating point arithmetic, typ.	50 μ s
for timer/counter operations, typ.	12 μ s

CPU-blocks

DB	
<ul style="list-style-type: none"> Number, max. 	255
<ul style="list-style-type: none"> Size, max. 	16 kbyte
FB	
<ul style="list-style-type: none"> Number, max. 	192
<ul style="list-style-type: none"> Size, max. 	16 kbyte

FC	
• Number, max.	192
• Size, max.	16 kbyte
OB	
• Description	see instruction list
• Size, max.	16 kbyte
• Number of free cycle OBs	1; OB 1
• Number of time alarm OBs	1; OB 10
• Number of cyclic interrupt OBs	1; OB 35
• Number of process alarm OBs	1; OB 40
• Number of startup OBs	1; OB 100
Nesting depth	
• per priority class	8; for each programming level

Counters, timers and their retentivity

S7 counter	
• Number	64
of which retentive with battery	
— can be set	Yes
— lower limit	0
— upper limit	63
of which retentive without battery	
— can be set	Yes
— lower limit	0
— upper limit	63
Counting range	
— lower limit	1
— upper limit	999
S7 times	
• Number	128
of which retentive with battery	
— adjustable	Yes
— lower limit	0
— upper limit	127
of which retentive without battery	
— adjustable	Yes
— lower limit	0
— upper limit	127
Time range	
— lower limit	10 ms
— upper limit	9 990 s

Data areas and their retentivity

Flag	
• Number, max.	256 byte
• Retentivity available	Yes; MB 0 to MB 255
• of which retentive with battery	0 to 2 047 (M 0.0 to M 255.7, adjustable)
• of which retentive without battery	0 to 2 047 (M 0.0 to M 255.7, adjustable)
Address area	
I/O address area	
• Inputs	1 kbyte
• Outputs	1 kbyte
Process image	
• Inputs	128 byte
• Outputs	128 byte
Digital channels	
• Inputs	8 192
— of which central	1 024
• Outputs	8 192
— of which central	1 024
Analog channels	
• Inputs	512
— of which central	256
• Outputs	512
— of which central	128
Addressing volume	
• Inputs	244 byte
• Outputs	244 byte
Hardware configuration	
Number of expansion units, max.	3
connectable programming devices/PCs	PGs/PCs with STEP 7 connectable via MPI interface
Number of modules per DP slave interface, max.	64
Number of DP masters	
• integrated	1
• via CP	1; CP 342-5
Number of operable FMs and CPs (recommended)	
• FM	8
• CP, PtP	4
• CP, LAN	2
Rack	
• Modules per rack, max.	32
Time of day	
Clock	
• Hardware clock (real-time)	Yes

Interfaces	
MPI	
• Cable length, max.	9 100 m; without repeaters: 50 m; with 2 repeaters: 1100 m; with 10 repeaters in series: 9100 m; via fiber optic cable: 23.8 km (with 16 star hubs or OLMs)
1. Interface	
Functionality	
• MPI	Yes
MPI	
• Number of nodes, max.	32
• Transmission rate, max.	187.5 kbit/s
Services	
— PG/OP communication	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
2. Interface	
Functionality	
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
DP master	
• Number of DP slaves, max.	64
Services	
— Equidistance	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes; Transmitter and receiver
User data per DP slave	
— User data per DP slave, max.	244 byte
Communication functions	
PG/OP communication	Yes
Global data communication	
• supported	Yes
S7 basic communication	
• supported	Yes
S7 communication	
• supported	Yes
S5 compatible communication	
• supported	Yes; via loadable blocks
Standard communication (FMS)	
• supported	Yes; via loadable blocks

Number of connections	
<ul style="list-style-type: none"> • overall — of which dynamic — of which static 	<p>8</p> <p>4</p>
Configuration	
Configuration software	
<ul style="list-style-type: none"> • STEP 7 	Yes; STEP 7 V5.0
Programming	
<ul style="list-style-type: none"> • Command set • Nesting levels • Program organization • System functions (SFC) 	<p>Binary logic operations, bracketed operations, result allocation, saving, counting, loading, transferring, comparing, shifting, rotating, complementation, calling blocks, fixed point arithmetic, floating point arithmetic, jump functions</p> <p>8</p> <p>Linear, structured</p> <p>Interrupt and error processing, copy data, clock functions, diagnostic functions, module parameterization, operating mode transitions</p>
Programming language	
<ul style="list-style-type: none"> — LAD — FBD — STL — SCL — CFC — GRAPH — HiGraph® 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>
Software libraries	
<ul style="list-style-type: none"> — Process diagnostics — Software controller 	<p>Yes</p> <p>Yes; depending on the required memory space and the resulting execution time</p>
Know-how protection	
<ul style="list-style-type: none"> • User program protection/password protection 	Yes
Cycle time monitoring	
<ul style="list-style-type: none"> • lower limit • upper limit • adjustable • preset 	<p>1 ms</p> <p>6 000 ms</p> <p>Yes</p> <p>150 ms</p>
Dimensions	
Width	80 mm
Height	125 mm
Depth	130 mm
Weights	
Weight, approx.	530 g; Memory card 16 g