



The sum of the two fields must be equal to or less than 672. One disk can support multiple TDIs.

Ethernet Cables

Standard 10 Base-T/100 Base-TX Shielded Category 5 Cable with RJ-45 connectors (solid conductor)

138131-AAA

A: Cable Length

006	6 feet (1.8 m)
010	10 feet (3.0 m)
025	25 feet (12.2 m)
040	40 feet (12.2 m)
050	50 feet (15.2 m)
075	75 feet (22.9 m)
085	85 feet (25.9 m)
100	100 feet (30.5 m)
120	120 feet (36.6 m)
150	150 feet (45.7 m)
200	200 feet (61.0 m)
250	250 feet (76.2 m)
320	320 feet (97.5 m)



Standard lengths for 10Base-T/100Base-TX cabling are shown above.

Fiber Optic Cable

100 Base-FX fiber optic cable with MT-RJ female connectors.

175M0075-AAAA

A: Cable Length in feet up to 1000 ft (300 m)

0010	10 feet (3.0 m)
0100	100 feet (30.5 m)
0150	150 feet (45.7 m)
0330	330 feet (100.6 m)
0500	500 feet (152.4 m)
1000	1000 feet (304.8 m)

Spares

288055-01	Standard Transient Data Interface Module with USB cable
123M4610*	10 foot A to B USB cable
146031-01	10Base-T/100Base-TX I/O Module
146031-02	100Base-FX (Fiber Optic) I/O Module
161580	3500/22M TDI Operation and Maintenance User Guide
164466	Network Accessories Datasheet
00580441	Connector header, internal termination, 3-position, green
00580436	Connector header, internal termination, 6-position, green
111M5777	Connector header, internal termination, 2-position, green
166M2390	Connector header, push-in-spring type (alternative for PN 00580436)
166M4363	Connector header, push-in-spring type (alternative for PN 00580441)
146031-03	10Base-T/100Base-TX I/O Module GLD Plated