

Spare part SIMATIC S7-300, CPU 312 Central processing unit with MPI, Integr. power supply 24 V DC, Work memory 32 KB, Micro Memory Card required



Figure similar

General information	
HW functional status	01
Firmware version	V2.6
Engineering with	
<ul style="list-style-type: none"> Programming package 	STEP 7 V5.2 + SP1 or higher with HW update
Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> 24 V DC 	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	2 A min.
Input current	
Current consumption (rated value)	0.6 A
Current consumption (in no-load operation), typ.	60 mA
Inrush current, typ.	2.5 A
I^2t	0.5 A ² ·s

Power loss	
Power loss, typ.	2.5 W
Memory	
Work memory	
<ul style="list-style-type: none"> integrated 	32 kbyte; For program and data
<ul style="list-style-type: none"> expandable 	No
Load memory	
<ul style="list-style-type: none"> Plug-in (MMC) 	Yes
<ul style="list-style-type: none"> Plug-in (MMC), max. 	4 Mbyte
<ul style="list-style-type: none"> Data management on MMC (after last programming), min. 	10 y
Backup	
<ul style="list-style-type: none"> present 	Yes; Guaranteed by MMC (maintenance-free)
<ul style="list-style-type: none"> without battery 	Yes; Program and data
CPU processing times	
for bit operations, typ.	0.2 μ s
for word operations, typ.	0.4 μ s
for fixed point arithmetic, typ.	5 μ s
for floating point arithmetic, typ.	6 μ s
CPU-blocks	
Number of blocks (total)	1 024; (DBs, FCs, FBs); the maximum number of loadable blocks can be reduced by the MMC used.
DB	
<ul style="list-style-type: none"> Number, max. 	511; Number range: 1 to 511
<ul style="list-style-type: none"> Size, max. 	16 kbyte
FB	
<ul style="list-style-type: none"> Number, max. 	1 024; Number range: 0 to 2047
<ul style="list-style-type: none"> Size, max. 	16 kbyte
FC	
<ul style="list-style-type: none"> Number, max. 	1 024; Number range: 0 to 2047
<ul style="list-style-type: none"> Size, max. 	16 kbyte
OB	
<ul style="list-style-type: none"> Size, max. 	16 kbyte
<ul style="list-style-type: none"> Number of free cycle OBs 	1; OB 1
<ul style="list-style-type: none"> Number of time alarm OBs 	1; OB 10
<ul style="list-style-type: none"> Number of delay alarm OBs 	1; OB 20
<ul style="list-style-type: none"> Number of cyclic interrupt OBs 	1; OB 35
<ul style="list-style-type: none"> Number of process alarm OBs 	1; OB 40
<ul style="list-style-type: none"> Number of startup OBs 	1; OB 100
<ul style="list-style-type: none"> Number of asynchronous error OBs 	4; OB 80, 82, 85, 87
<ul style="list-style-type: none"> Number of synchronous error OBs 	2; OB 121, 122

Nesting depth	
• per priority class	8
• additional within an error OB	4
Counters, timers and their retentivity	
S7 counter	
• Number	128
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	127
— preset	8
Counting range	
— can be set	Yes
— lower limit	0
— upper limit	999
IEC counter	
• Number	Unlimited (limited only by RAM capacity)
S7 times	
• Number	128
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	127
— preset	No retentivity
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)
Data areas and their retentivity	
retentive data area in total	All (incl. memory bits, times, counters)
Flag	
• Number, max.	128 byte
• Retentivity available	Yes; MB 0 to MB 127
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte
Data blocks	
• Retentivity adjustable	Yes; via non-retain property on DB
• Retentivity preset	Yes

Local data	
• per priority class, max.	256 byte
Address area	
I/O address area	
• Inputs	1 kbyte
• Outputs	1 kbyte
Process image	
• Inputs	128 byte
• Outputs	128 byte
Digital channels	
• Inputs	256
— of which central	256
• Outputs	256
— of which central	256
Analog channels	
• Inputs	64
— of which central	64
• Outputs	64
— of which central	64
Hardware configuration	
Number of expansion units, max.	0
Number of DP masters	
• integrated	0
• via CP	4
Number of operable FMs and CPs (recommended)	
• FM	8
• CP, PtP	8
• CP, LAN	4
Rack	
• Racks, max.	1
• Modules per rack, max.	8
Time of day	
Clock	
• Software clock	Yes
• retentive and synchronizable	No
• Deviation per day, max.	15 s
Operating hours counter	
• Number	1
• Number/Number range	0
• Range of values	0 to 2 ³¹ hours (when using SFC 101)
• retentive	Yes; Must be restarted at each restart

Clock synchronization	
• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• to DP, master	No
• to DP, slave	No
• in AS, master	Yes
• in AS, slave	No
• on Ethernet via NTP	No

Digital inputs	
integrated channels (DI)	0

Digital outputs	
integrated channels (DO)	0

Analog inputs	
integrated channels (AI)	0

Analog outputs	
integrated channels (AO)	0

Interfaces	
Number of industrial Ethernet interfaces	0
Number of PROFINET interfaces	0
Number of RS 485 interfaces	1
Number of RS 422 interfaces	0

1. Interface	
Interface type	Integrated RS 485 interface
Physics	RS 485
Isolated	No
Power supply to interface (15 to 30 V DC), max.	200 mA

Functionality	
• MPI	Yes
• PROFIBUS DP master	No
• PROFIBUS DP slave	No
• Point-to-point connection	No

MPI	
• Number of connections	6
• Transmission rate, max.	187.5 kbit/s

Services	
— PG/OP communication	Yes
— Routing	No
— Global data communication	Yes
— S7 basic communication	Yes

— S7 communication	Yes
— S7 communication, as client	No
— S7 communication, as server	Yes

Communication functions

PG/OP communication	Yes
---------------------	-----

Global data communication

• supported	Yes
• Number of GD loops, max.	4
• Number of GD packets, max.	4
• Number of GD packets, transmitter, max.	4
• Number of GD packets, receiver, max.	4
• Size of GD packets, max.	22 byte
• Size of GD packet (of which consistent), max.	22 byte

S7 basic communication

• supported	Yes
• User data per job, max.	76 byte
• User data per job (of which consistent), max.	76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server)

S7 communication

• supported	Yes
• as server	Yes
• as client	Yes; Via CP and loadable FB
• User data per job, max.	180 byte; With PUT/GET
• User data per job (of which consistent), max.	64 byte

S5 compatible communication

• supported	Yes; via CP and loadable FC
-------------	-----------------------------

Number of connections

• overall	6
• usable for PG communication	5
— reserved for PG communication	1
— adjustable for PG communication, min.	1
— adjustable for PG communication, max.	5
• usable for OP communication	5
— reserved for OP communication	1
— adjustable for OP communication, min.	1
— adjustable for OP communication, max.	5
• usable for S7 basic communication	2
— reserved for S7 basic communication	0
— adjustable for S7 basic communication, min.	0
— adjustable for S7 basic communication, max.	2

S7 message functions

Number of login stations for message functions, max.	6; Depending on the configured connections for PG/OP and S7 basic communication
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	20

Test commissioning functions

Status block	Yes
Single step	Yes
Number of breakpoints	2

Status/control

• Status/control variable	Yes
• Variables	Inputs, outputs, memory bits, DB, times, counters
• Number of variables, max.	30
— of which status variables, max.	30
— of which control variables, max.	14

Forcing

• Forcing	Yes
• Forcing, variables	Inputs, outputs
• Number of variables, max.	10

Diagnostic buffer

• present	Yes
• Number of entries, max.	100
— adjustable	No

Configuration

Configuration software	
• STEP 7	Yes; V5.2 SP1 or higher with HW update

Programming

• Command set	see instruction list
• Nesting levels	8
• System functions (SFC)	see instruction list
• System function blocks (SFB)	see instruction list

Programming language

— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— GRAPH	Yes
— HiGraph®	Yes

Know-how protection

• User program protection/password protection	Yes
---	-----

Dimensions

Width	40 mm
Height	125 mm
Depth	130 mm

Weights

Weight, approx.	270 g
-----------------	-------

last modified: 04/19/2018 