

SIMATIC DP, interface DP/PA-Link and ET200M IM153-2 HF for extended temperature range for max. 12 S7-300 modules with redundancy capability, Timestamping suitable for isochronous mode
 New features: up to 12 modules can be used Slave Initiative for Drive ES and Switch ES Expanded quantity structure for HART auxiliary variables Operation of the 64-channel modules 32 signals / slot +++
 Observe compatibility instructions in manual +++

General information

Product type designation	IM 153-2 HF
Firmware version	V6.0.0
Vendor identification (VendorID)	801Eh

Supply voltage

Rated value (DC)	Yes
<ul style="list-style-type: none"> • 24 V DC 	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	2,5 A
Mains buffering	
<ul style="list-style-type: none"> • Mains/voltage failure stored energy time 	5 ms

Input current

Current consumption, max.	650 mA
Inrush current, typ.	3 A
I^2t	0.1 A ² ·s

Output current

for backplane bus (5 V DC), max.	1.5 A
----------------------------------	-------

Power loss

Power loss, typ.	5.5 W
------------------	-------

Address area

Addressing volume	
<ul style="list-style-type: none"> • Inputs 	244 byte
<ul style="list-style-type: none"> • Outputs 	244 byte

Hardware configuration

Number of modules per DP slave interface, max.	12
--	----

Time stamping

Accuracy	1 ms; 1ms at up to 8 modules; 10ms at up to 12 modules
----------	--

Number of message buffers	15
Messages per message buffer	20
Number of stampable digital inputs, max.	128; Max. 128 signals/station; max. 32 signals/slot
Time format	RFC 1119
Time resolution	0.466 ns
Time interval for transmitting the message buffer if a message is present	1 000 ms
Time stamp on signal change	rising / falling edge as signal entering or exiting

Interfaces

Transmission procedure	RS 485
------------------------	--------

PROFIBUS DP

<ul style="list-style-type: none"> • Node addresses 	1 to 125 permitted
<ul style="list-style-type: none"> • automatic detection of transmission rate 	Yes
<ul style="list-style-type: none"> • Output current, max. 	70 mA
<ul style="list-style-type: none"> • Transmission rate, max. 	12 Mbit/s
<ul style="list-style-type: none"> • SYNC capability 	Yes
<ul style="list-style-type: none"> • FREEZE capability 	Yes
<ul style="list-style-type: none"> • Direct data exchange (slave-to-slave communication) 	Yes; as publisher with all IO, as subscriber with F-IO only
<ul style="list-style-type: none"> • Design of electrical connection of PROFIBUS interface 	9-pin sub D

1. Interface

PROFIBUS DP slave

<ul style="list-style-type: none"> • GSD file 	SI05801E.GSD
<ul style="list-style-type: none"> • automatic baud rate search 	Yes

Protocols

Bus protocol/transmission protocol	PROFIBUS DP to EN 50170
------------------------------------	-------------------------

Potential separation

Potential separation exists	Yes
-----------------------------	-----

Isolation

Isolation tested with	Isolation voltage 500 V
-----------------------	-------------------------

Degree and class of protection

IP degree of protection	IP20
-------------------------	------

Ambient conditions

Altitude during operation relating to sea level	
<ul style="list-style-type: none"> • Installation altitude above sea level, max. 	3 000 m

Configuration

Configuration software	
<ul style="list-style-type: none"> • STEP 7 	Yes; STEP 7 / COM PROFIBUS / non-Siemens tools via GSD file

Dimensions

Width	40 mm
Height	125 mm
Depth	117 mm

Weights

Weight, approx.	360 g
-----------------	-------

last modified: 09/12/2019 