



*** Spare part *** SIMATIC DP, PM-E power modules for ET 200S; 24 V DC with diagnostics

Figure similar

| Supply voltage | |
|---|---|
| Load voltage L+ | |
| <ul style="list-style-type: none"> Rated value (DC) Short-circuit protection Reverse polarity protection | 24 V No; external (e.g. automatic circuit breaker), tripping characteristic C Yes |
| Input current | |
| from load voltage L+ (without load), max. | 4 mA |
| Current carrying capacity | |
| up to 60 °C, max. | 10 A |
| Power loss | |
| Power loss, typ. | 0.1 W |
| Interrupts/diagnostics/status information | |
| Diagnoses | |
| <ul style="list-style-type: none"> missing load voltage | Yes |
| Diagnostics indication LED | |
| <ul style="list-style-type: none"> Rated load voltage PWR (green) Group error SF (red) | Yes Yes |
| Parameter | |
| Remark | 3 byte |
| missing load voltage | Disable / enable |
| Potential separation | |
| primary/secondary | Yes; between rated load voltage and backplane bus, between power modules |
| Isolation | |
| Isolation tested with | 500 V DC |
| Dimensions | |
| Width | 15 mm |
| Height | 81 mm |
| Depth | 52 mm |
| Weights | |
| Weight, approx. | 35 g |

last modified: 8/21/2024 