

# YC10

Crawler Hydraulic Excavator

YC10 mini excavator is small, flexible, powerful and reliable. It is widely used in vegetable greenhouses, orchards, nurseries, landscaping, interior decoration and other agricultural, municipal construction and other fields.




#### Specifications

Operating weight (T)	0.97	Bucket capacity(m <sup>3</sup> )	0.022
Engine model	KOOP KD192F-1	Fuel tank capacity (L)	5.5
Rated power (kw/r/min)	7.0/3000	Hydraulic oil tank capacity (L)	9.4
Max. flow (L/min)	18	Max. climbing degree (%)	58
Working pressure (Mpa)	16	Average grounding pressure (Kpa)	28
Travel speed (km/h)	1.9	Arm digging force (KN)	5.2
Swing speed (r/min)	11.5	Bucket digging force (KN)	7.2

#### Dimensions (MM)

A-Overall length (mm)	2976
B-Overall width (mm)	840/880
C-Overall height (to top of boom)(mm)	1110
D-Overall height (to top of cab)(mm)	2225
E-Counterweight ground clearance(mm)	370
F-Min. ground clearance (mm)	132
G-Tail swing radius (mm)	815
H-Track ground length(mm)	900
J-Track length (mm)	1233
K Track gauge (mm)	660
L-Track width (mm)	840
M-Track shoe width (mm)	180



#### Working Range (MM)

O-Max. digging height (mm)	2585
P Max. dumping height (mm)	1715
Q-Max. digging depth (mm)	1520
R-Max. vertical wall digging depth (mm)	
T-Max. digging reach (mm)	3210
U Max. digging reach at ground level (mm)	3125

