



RX660A

MECHANICAL

Parameter	Details
Height	765mm
Diameter	696mm
Weight	48kg
Material	Aluminum alloy

ACOUSTIC PERFORMANCE

Parameter	Details
Peak SPL@1m	145dBA
Continuous SPL@1m	140dBA
Dispersal radius@85dB*	501m
Warning radius@70dB*	1407m
Dispersal radius@85dB#	1000m
Warning radius@70dB#	3163m

*Empirical calculation based on air attenuation

#Calculated in ideal environmental conditions.

ELECTRICAL REQUIREMENTS

Parameter	Details
Power Consumption	1200W
Power Input	External 110v~220V AC to 24v DC adapter

ENVIRONMENTAL PERFORMANCE

Parameter	Details
Hot Operating Temp	MIL-STD-810G, Method 501.5, Procedure II, Design type Hot, 60°C
Cold Operating Temp	MIL-STD-810G, Method 502.5, Procedure II, Design type Basic Cold, -33°C
Hot Storage Temp	MIL-STD-810G, Method 501.5, Procedure I, 70°C
Cold Storage Temp	MIL-STD-810G, Method 502.5, Procedure I, -40°C
Operating Humidity	MIL-STD 810G, Method 507.5, Procedure II, Aggravated Cycle
Rain	MIL-STD-810G, Method 506.5, Procedure I, Blowing rain
Salt Fog	MIL-STD-810G, Method 509.5
Shipboard Vibration	MIL-STD-167-1A
Shipboard Shock	MIL-S-901D, Shipboard Shock, Class I, Shock grade B
Random Vibration	MIL-STD-810G, Method 514.6, Wheeled Vehicles

SAFETY

*Designed to meet MIL-STD-810G, MIL-STD-167-1A & MIL-S-901D

Parameter	Details
safetuy	MIL - STD - 1474D

ELECTROMAGNETIC COMPATIBILITY (EMC)

Parameter	Details
EMC	FCC Part 15 class A radiated emissions; CE; MIL-STD-461F

