



# FUZHOU LUCKY STAR CO.,LTD.

Address:No.5,Shi Zi Ting Road,Cangshan Park,  
Pushang Industrial District,Fuzhou,Fujian,China

Tel:(86-591)88088171、 8330 7885

Fax:(86-591)8330 7885

E-mail:leo@fzluckystar.com

Http://www.fzluckystar.com



► Fuzhou Lucky Star Co.,Ltd.

NEW  
CATALOGUE



# PRODUCTS



# LABEL BARCODE SCALES >>

Type: Barcode Scale Label Printing Scale  
 Precision: 1/3000  
 Storage Capacity: 10,000 PLUs  
 Capacity: 6/15/30kg  
 Division: 2g/5g/10g  
 Size: 390\*410\*510mm  
 Display: Double sides displays with the pole - LCD display  
 Keyboard: 103keys(63×3=189 PLUs Hotkeys,40 Function keys)  
 Printing type: Thermal Printing,  
 Printing Speed: >50mm/s,  
 Paper Width: 57mm,Printing Width: 50mm,  
 Recommended Label Size: 60×40mm 40x30mm  
 Paper Roll Outer Diameter: 80mm(Max)  
 Paper Roll Internal Diameter: 42mm (Min)  
 Communication ports: 1x,USB,1xRS232, 1XRJ45 Ethernet, 1xCashbox  
 Power: AC: 110-240V, DC:21v

BLS-C01



With pole: 5 windows  
 Max Capacity: 6 kg/15kg/30kg  
 Division: 2g/5g/10g  
 Display: Double sides displays with the pole -LCD display  
 Keyboard:103keys(63×3=189 PLUs Hotkeys, 40 Function keys)  
 Class: Class III  
 Precision: 1/3000  
 Scale size: 410\*500\*490mm  
 Pan size: 260\*350mm  
 Dot Matrix: 160\*32  
 Printer head life: 100km  
 Printing Speed: >50mm/s  
 Paper Width: 57mm  
 Printing Width: 50mm,  
 Recommended Label Size: 60×40mm 40x30mm  
 Paper Roll Outer Diameter: 80mm(Max)  
 Paper Roll Internal Diameter: 42mm (Min)  
 Power Supply: 110-240V



BLS-C02



## LS-MDS



Dimensions: 392\*390\*530(L\*W\*H)mm  
 Screen Display: Main display: 11.6" LCD display  
 Secondary display: 10.1 LCD display  
 Touch Screen: Capacitive touch screen  
 Capacity: 15KG/30KG  
 Min. weighing: 40G/100G  
 Resolution: 2/5G, 5/10G  
 Pan size: 390\*280mm  
 Print Speed: Up to 120MM/S  
 Cpu: RK3566/3568  
 Memory: 2GB RAM (optional)  
 Story: 16GB EMMC (optional)  
 Data storage: Can edit 1-9999999 PLU numbers and 10000 PLU commodity data.  
 Power supply: DC24V 5A  
 Operating temperature: 0°C-40°C  
 Housing Material: Cast aluminum structure, good heat dissipation efficacy

Capacity: 3Kg, 6Kg, 15Kg, 30Kg  
 Resolution: 0.1g/0.2g/0.5g, 0.2g/0.5g/1g, 2g/5g, 5g/10g  
 Operator display: 11.6inch capacitive touch screen.  
 Touch screen type: Capacity touch screen  
 Customer display: 7" color TFT  
 OS: Android  
 CPU: RK3568. quad-core up to 1.83GHZ  
 Memory: 1GB/2GB RAM (Optional)  
 Storage: 8GB/16GB EMMC (Optional)  
 Density: 8dot/mm; Max print size: 56mmX100mm; head life: 150km  
 Print speed: 120mm/s (Max) Print width: 58mm  
 Interface: 1\*Ethernet, 2\*USB, 1\*RS232  
 Power: DC24V2.5A  
 Material: Aluminum Body  
 Function summary  
 1. Recognition algorithm: With the world's leading local offline recognition and continuous training technology, unrecognized products can be accurately identified through 1-2 traditional sales methods.  
 2. Recognition Speed: Recognition time  $\leq 0.25s$ . The sales efficiency is more than 2 times that of traditional label scales.  
 3. Recognition accuracy:  $\geq 98%$ . Putting on the product can automatically identify and call out the corresponding product, without remembering the product code or phonetic search, reducing the requirements for scalars.



LS-MDH++

Capacity: 3Kg, 6Kg, 15Kg, 30Kg  
 Resolution: 0.1g/0.2g/0.5g, 0.2g/0.5g/1g, 2g/5g, 5g/10g  
 Operator display: 14inch capacitive touch screen.  
 Touch screen type: Capacity touch screen  
 Customer display: 14inch capacitive touch screen.  
 CPU: RK3568. quad-core up to 1.83GHZ  
 Memory: 1GB/2GB RAM (Optional)  
 Storage: 8GB/16GB EMMC (Optional)  
 Pan size: 400\*300mm  
 Barcode type: EAN8, EAN13, EAN128, QR Code etc.  
 Communication interface: 1\*Ethernet, 2\*USB, 1\*RS232  
 Power: DC24V2.5A  
 Material: Plastic Body  
 System: Customized Android system, smoother and more stable.



LS-L309

## BLS-A



CPU: Intel Celeron 3855u  
 Memory: DDR3 4G  
 Hard Disk: SSD MSATS 32G  
 LCD: 15.6" TFT 1024\*768  
 Touch Screen: Projected Capacitive Touch Screen  
 2nd Display: 15.6" LCD 1024\*768  
 Receipt Printer: 80mm Thermal Printer w/ Auto Cutter  
 Label Printer: 60mm Label Printer  
 Power: DC 24v/2.5A  
 Wifi/Bluetooth/4G: Optional  
 Ethernet: 1\*10/100/1000M  
 Capacity & Division: 3kg, 6kg, 15kg, 30kg, 0.1/0.2/0.5g, 0.2/0.5/1g, 2g/5g, 5g/10g  
 Platter Size: 390\*285mm  
 Interfaces: 4\*USB, 1\*RJ11, 1\*RJ45, 1\*VGA, 1\*PS/2, 1\*AUDIO OUT  
 OS: Windows 7/10  
 Dimension: 390\*285\*610mm



## LS-F+



Capacity:3Kg,6Kg,15Kg,30Kg  
 Resolution:0.1g/2g/5g/10g  
 Label paper:Label width≤60mm  
 Density:8dot/mm  
 Max print size:56mmX100mm  
 Head life:150km  
 Touch:Capacitance touch screen  
 Display:15inch high-brightness industrial screen  
 OS:Android  
 CPU:RK3288.quad-core up to 1.83GHZ  
 Memory:2GB RAM  
 Storage:16GB EMMC  
 Material:Aluminum Body  
 Network:Build in wifi  
 Recognition Speed: Recognition time ≤0.25s  
 Recognition accuracy: ≥98%  
 Power:DC24V2.5A

Capacity:3Kg,6Kg,15Kg,30Kg  
 Resolution:0.1g/2g/5g/10g  
 Label paper:Label width≤60mm  
 Density:8dot/mm  
 Max print size:56mmX100mm  
 Head life:150km  
 Touch:Capacitance touch screen  
 Display:15inch high-brightness industrial screen  
 OS:Android  
 CPU:RK3288.quad-core up to 1.83GHZ  
 Memory:2GB RAM  
 Storage:16GB EMMC  
 Material:Aluminum Body  
 Network:Build in wifi  
 Recognition Speed: Recognition time ≤0.25s  
 Recognition accuracy: ≥98%  
 Power:DC24V2.5A  
 It supports all the supermarket software on the market in a compatible way.



LS-T+

Operator display:15.6inch capacitive touch screen.  
 Resolution:1366\*768  
 Touch screen type:Capacity touch screen  
 Customer display:10.1" color screen; 15" color screen(Optional)  
 Range:6kg/15kg;15kg/30kg  
 Division value:2g/5g;5g/10g  
 OS:Android  
 CPU:RK3288.quad-core up to 1.83GHZ  
 Memory:2GB RAM  
 Storage:16GB EMMC  
 Barcode type:EAN8/EAN13/EAN128/QR Code etc.  
 Paper type:Thermal label paper/receipt  
 Paper width:58mm  
 Print speed:120mm/s (Max)  
 Communication interface:1\*Ethernet, 2\*USB, 1\*RS232  
 Power:DC 24V 2.5A



LBS-A01



## LS-MDH+



Size: 400\*500\*550mm  
 Capacity: 3kg,6kg,15kg,30kg  
 Resolution: 0.1/0.2/0.5g,0.2/0.5/1g,2g/5g,5g/10g  
 Precision: 1/3000  
 Keyborad: 105Kys  
 Density:8dot/mm  
 Label Size:Width: 30mm-58mm  
 The width of paper: ≤62mm  
 Speed:100mm/s  
 Printer Head Life:150km  
 Height: ≤150mm  
 Display:7" color TFT  
 Both in vendor's and buyer's side.  
 Material:Aluminium Body  
 Storage Capacity:9,000 PLUs  
 Interface: USB,Ethernet  
 Printing Speed: 100mm/s  
 Power Input: AC100-240V 50/60Hz, 1.5A



## LS-MDB



Size: 400\*448\*170mm  
 Capacity: 3kg,6kg,15kg,30kg  
 Resolution: 0.1/0.2/0.5g,0.2/0.5/1g,2g/5g,5g/10g  
 Precision: 1/3000  
 Keyborad: 108Kys  
 Dispaly: 128\*64 Dot Matrix Display  
 Storage Capacity:9,000 PLUs  
 Interface: USB,Ethernet  
 Printer Head Life: 150KM  
 Density: 8dot/mm; Width 58mm  
 Label Size:Width: 30mm-58mm,  
 The width of paper: ≤62mm  
 Length: 25mm-48mm.  
 The height can be designed at will  
 Printing Type: Thermal Printing,  
 Printing Speed: 100mm/s  
 Power Input: AC110-240V 50/60Hz, 0.5A

Size: 400\*440\*565mm  
 Capacity: 3kg,6kg,15kg,30kg  
 Resolution: 0.1/0.2/0.5g,0.2/0.5/1g,2g/5g,5g/10g  
 Precision: 1/3000  
 Keyborad: 108Kys  
 Dispaly: LED Display  
 Storage Capacity:9,000 PLUs  
 Interface: USB,Ethernet  
 Printer Head Life: 150KM  
 Density: 8dot/mm; Width: 58mm  
 Label Size:Width: 30mm-58mm,  
 The width of paper: ≤62mm  
 Length: 25mm-48mm.  
 The height can be designed at will  
 Printing Type: Thermal Printing,  
 Printing Speed: 100mm/s  
 Power Input: AC110-240V 50/60Hz, 0.5A

Size: 400\*440\*565mm  
 Capacity: 3kg,6kg,15kg,30kg  
 Resolution: 0.1/0.2/0.5g,0.2/0.5/1g,2g/5g,5g/10g  
 Precision: 1/3000  
 Keyborad: 108Kys  
 Dispaly: 128\*64 Dot Matrix Display  
 Storage Capacity:9,000 PLUs  
 Interface: USB,Ethernet  
 Printer Head Life: 150KM  
 Density: 8dot/mm; Width: 58mm  
 Label Size:Width: 30mm-58mm,  
 The width of paper: ≤62mm  
 Length: 25mm-48mm.  
 The height can be designed at will  
 Printing Type: Thermal Printing,  
 Printing Speed: 100mm/s  
 Power Input: AC110-240V 50/60Hz, 0.5A

## LS-302



Size: 300\*250\*200mm  
 Display: Dual side 5" color TFT  
 Storage Capacity:9,000 PLUs  
 Interface: USB,Ethernet  
 Communication: Ethernet Or Vlan  
 Operation System: Standard  
 CPU: ARM  
 Touch Screen Type: Not Touch Screen  
 Hard Disk Capacity: 400 pictures storage  
 Hotkeys: 56, Function Keys: 27  
 Paper Label: Width≤62mm  
 Density: 8dot/mm; Width: 58mm  
 Speed: 100mm/s  
 Printer Head Life: 100km  
 Optional: WIFI Module for wireless  
 Power Input: AC110-240V 50/60Hz, 0.5A



## LS-MDE



## LS-MDA



## LS-MDA+



Size: 400\*440\*565mm  
 Capacity: 3kg,6kg, 15kg,30kg  
 Resolution: 0.1/0.2/0.5g,0.2/0.5/1g,2g/5g,5g/10g  
 Precision: 1/3000  
 Keyboard:(Hotkeys:108,Function Keys:81)  
 The width of paper: ≤62mm  
 Printing Performance  
 Density:8dot/mm, Width: 58mm  
 Label Size:Width: 30mm-58mm  
 Printing Speed:100mm/s  
 Printer Head Life:150km  
 Display: 5" Color TFT  
 Both in vendor's and buyer's side.  
 Storage Capacity:9,000 PLUs  
 Interface: USB,Ethernet  
 Barcode Type:EAN/UPC/CODE-128C  
 Optional:WIFI Module for wireless  
 Power Input: AC100-240V 50/60Hz, 1.5A

Capacity:3Kg,6Kg,15Kg,30Kg  
 Resolution:0.1g/2g/5g/10g  
 Display:15inch high-brightness industrial screen  
 Touch:Capacitance touch screen  
 Label paper:Label width≤60mm  
 Max label size:100mm\*56mm  
 Density:8dot/mm  
 Head life:150km  
 Material: Aluminum Body  
 OS:Android  
 CPU:RK3288.quad-core up to 1.83GHZ  
 Memory:2GB RAM  
 Storage:16GB EMMC  
 Network:Build in wifi  
 Power:DC24V2.5A  
 It can edit 1-9999999 PLUs,10000 PLUs data storage capacity Each PLU includes commodity description.



## BLS-A12T15

Scale size: 381mm\*388mm\*160mm  
 Capacity: 6kg, 15kg, 30kg.  
 Resolution: 1/3000.  
 Display mode: bright red LED or green LED.  
 Label size: 30x40mm, 37x50mm, 40x50mm, 40x60mm.  
 Label axes size: Ø25mm.  
 Printing width: 56mm (max.).  
 Printing speed: 75mm/s.  
 Paper Width: 57mm, Printing Width: 50mm  
 Keyboard:26keys  
 Port: RS232 (standard), Ethemet (optional),  
 Can store 10000 commodity names and set 71 shortcuts;  
 Can be set a mass of text import,support various PLU  
 information default format import;  
 Power supply:AC 100-240V/ DC 21V(optional)



## LS-MDA

## BLS-A51



Scale size: 381mm\*428mm\*500mm  
 Capacity: 6kg, 15kg, 30kg.  
 Display mode: bright red LED or green LED.  
 Resolution: 1/3000.  
 Label size: 40x50mm, 40x60mm.  
 Label axes size: Ø25mm.  
 Printing width: 56mm (max.).  
 Printing speed: 75mm/s.  
 Paper Width: 57mm, Printing Width: 50mm  
 Keyboard:26keys  
 Port: RS232 (standard), ethemet (optional),  
 Cash drawer (optional).  
 Can store 10000 commodity names  
 71 shortcut keys, supporting 3 products with one  
 key, 189 items for quick invocation  
 Power supply:AC 100-240V/ DC 21V(optional)



## HPS-A21



Size:410\*500\*510mm  
 Pan size:260\*350mm  
 Capacity:30kg / 10 g, 15kg/5g  
 Precision:1/3000  
 Shortcut:126  
 Display: Front 5+back4 Green LED display  
 Dot Matrix Display support different language  
 Printer head life:150km  
 Printer speed:75mm/s  
 Print Type: Auto Peel Continues  
 Thermal Label Printer  
 Label Width & Length:40 - 60mm, 30 - 120mm  
 Interfaces: USB, LAN, RS232 & RJ11  
 PLU Keypad: 126 button (with shift)  
 With pole display  
 Power:AC 110-240v 50/60Hz

Size: 381\*428\*500mm  
 Capacity:3kg/6kg/15kg/30kg  
 Division:1g/2g/5g/10g  
 Precision:1/3000  
 Accuracy class:Class III  
 Display:LCD/LED Display  
 Storage Capacity:10,000 PLUs  
 Display:Double sides displays with the pole  
 - LCD display and seven- inch touch screen  
 Keyboard:26keys  
 Thermal Printing, Printing Speed: >50mm/s,  
 Paper Width: 57mm, Printing Width: 50mm,  
 Paper Roll Outer Diameter:90mm(Max)  
 Paper Roll Internal Diameter:25mm (Min)  
 Power supply:AC 100-240V/ DC 21V(optional)  
 71 shortcut keys, supporting 3 products with one key,  
 189 items for quick invocation



BLS-A51A

Size: 390\*410\*510mm  
 Storage Capacity: 10,000 PLUs  
 Capacity:6/15/30kg  
 Division:2g/5g/10g  
 Precision:1/3000  
 Display:Double sides displays with the pole - LCD display  
 Storage Capacity:10,000 PLUs  
 Keyboard:103keys(63×3=189 PLUs Hotkeys, 40 Function keys)  
 Print: Label, Receipt  
 Printing Speed: >50mm/s,  
 Paper Width: 57mm, Printing Width: 50mm,  
 Recommended Label Size: 60×40mm 40x30mm  
 Paper Roll Outer Diameter: 80mm(Max)  
 Paper Roll Internal Diameter: 42mm (Min)  
 Communication ports: 1x,USB,1xRS232, 1XRJ45 Ethernet,  
 1XCashbox  
 Power: AC: 110-240V



BLS-C03

## LP-16



Size:360\* 440\*175mm  
 Precision: 1 / 3000  
 Weighing scope: 0-6kg-15kg or 0-15kg-30kg  
 Weighing resolution(e) : 2/5g or 5g/10g  
 Storage Capacity: 10,000PLUs  
 Display: Double sides white & black LCD display  
 with the pole:4-inch, 128X64 dot matrix.  
 Keyboard:140 keys(112x2=224 PLU hotkeys,  
 28 function keys)  
 Printing type: thermal printing,  
 Printing speed: >50mm/s  
 Printing width: 56mm(Max)  
 Label paper roll: Width(Max): 58+0.5mm  
 outer diameter: 80mm(Max)  
 Diameter: 40mm(Min)  
 Communication ports: 1xRS232, 1XRJ45 Etherne  
 Power supply: AC100-240V 50/60Hz, 0.5A



## CRS-A123P



Scale size: 590\*495\*735mm  
 Capacity: 6kg, 15kg, 30kg  
 Division value: 2g/5g; 5g/10g  
 Resolution: 1/3000  
 Operator display: 15 inch capacitive touch screen.  
 Touch screen type: Capacity touch screen  
 OS: Windows  
 CPU: I3855U  
 Memory: DDR3 4GB  
 Storage: SSD MSATS 32G  
 Printer Head Life: 100KM  
 Density: 8dot/mm; Width: 57mm  
 Printing Type: Thermal Printing,  
 Printing Speed: 100mm/s  
 Interface: USB\*4, RJ12\*1, RJ45\*1, RS232\*1, VAG\*1,  
 PS2\*1, AV\*1  
 Communication: Ethernet, WIFI  
 Power Input: AC100-240V 50/60Hz, 1.5A

Scale size: 590\*495\*720mm  
 Capacity: 6kg, 15kg, 30kg  
 Division value: 2g/5g; 5g/10g  
 Resolution: 1/3000  
 Operator display: 15 inch capacitive touch screen.  
 Touch screen type: Capacity touch screen  
 OS: Windows  
 CPU: I3855U  
 Memory: DDR3 4GB  
 Storage: SSD MSATS 32G  
 Printer Head Life: 100KM  
 Density: 8dot/mm; Width: 57mm  
 Printing Type: Thermal Printing,  
 Printing Speed: 100mm/s  
 Interface: USB\*4, RJ12\*1, RJ45\*1, RS232\*1, VAG\*1,  
 PS2\*1, AV\*1  
 Communication: Ethernet, WIFI  
 Power Input: AC100-240V 50/60Hz, 1.5A



## CRS-A123D

# Cash Register Scale >>





## LS-ADS



Size: 400\*440\*565mm  
 Capacity: 3kg, 6kg, 15kg, 30kg  
 Resolution: 0.1/0.2/0.5g, 0.2/0.5/1g, 2g/5g, 5g/10g  
 Hotkeys:99; Function Keys:35  
 Receipt:φ50X57mm; Label:Width≤62mm  
 Receipts:Density:8dot/mm; Width:48mm  
 Speed:100mm/s  
 Printer Head Life:150km  
 Labels:Density: 8dot/mm; Width:58mm  
 Label Size:Width: 30mm-58mm  
 The width of paper: ≤62mm  
 Printer Head Life:150km  
 Speed:100mm/s  
 Printing Type: Thermal Printing,  
 Display:5" Color TFT Display  
 Storage Capacity:9,000 PLUs  
 Power Input: AC110-240V 50/60Hz, 0.5A

Size: 375\*325\*510mm  
 Capacity: 6kg,15kg, 30kg  
 Resolution: 1g/2g, 2g/5g, 5g/10g  
 Hotkeys:42;Function Keys:35  
 Thermal Paper:φ50X57mm  
 Density:8dot/mm;Width:48mm  
 Speed:100mm/s  
 Printer Head Life:80km  
 Display:128\*64 Dot Matrix Display  
 Storage Capacity:9,000 PLUs  
 Printing Type: Thermal Printing  
 Interface: USB,Ethernet  
 Power Input: AC110-240V 50/60Hz, 0.5A  
 Various report printout support, including annual report, monthly report, daily report, single item report, clerk report.



LS-A

Size: 380\*410\*510mm  
 Capacity: 6kg,15kg, 30kg  
 Resolution: 1g/2g, 2g/5g, 5g/10g  
 Hotkeys:42;Function Keys:35  
 Thermal Paper:φ50X57mm  
 Density:8dot/mm;Width:48mm  
 Speed:100mm/s  
 Printer Head Life:80km  
 Display:128\*64 Dot Matrix Display  
 Storage Capacity:9,000 PLUs  
 Printing Type: Thermal Printing  
 Interface: USB,Ethernet  
 Various report printout support, including annual report, monthly report, daily report, single item report, clerk report.  
 Power Input: AC110-240V 50/60Hz, 0.5A



LS-C

## LS-C+



Size: 380\*410\*510mm  
 Capacity: 6kg,15kg, 30kg  
 Resolution: 1g/2g, 2g/5g, 5g/10g  
 Hotkeys:42;Function Keys:35  
 Thermal Paper:φ50X57mm  
 Density:8dot/mm;Width:48mm  
 Speed:100mm/s  
 Printer Head Life:80km  
 Display:5" Color TFT Display  
 Storage Capacity:9,000 PLUs  
 Printing Type: Thermal Printing  
 Interface: USB,Ethernet  
 Power Input: AC110-240V 50/60Hz, 0.5A



## LS-E+



Size: 400\*440\*565mm  
 Capacity: 6kg, 15kg, 30kg  
 Resolution: 1g/2g, 2g/5g, 5g/10g  
 Hotkeys:99;Function Keys:35  
 Thermal Paper:φ50X57mm  
 Density:8dot/mm;Width:48mm  
 Speed:100mm/s  
 Printer Head Life:80km  
 Display: Dual side 5" color TFT Display  
 Storage Capacity:9,000 PLUs  
 Printing Type: Thermal Printing  
 Interface: USB,Ethernet  
 Various report printout support, including annual report, monthly report, daily report, single item report, clerk report.  
 Power Input: AC110-240V 50/60Hz, 0.5A

Size: 300\*250\*200mm  
 Capacity: 6kg, 15kg, 30kg  
 Resolution: 1g/2g, 2g/5g, 5g/10g  
 Hotkeys:48;Function Keys:35  
 Thermal Paper:φ50X57mm  
 Density:8dot/mm;Width:48mm  
 Speed:100mm/s  
 Printer Head Life:80km  
 Display: Dual side 5" color TFT Display  
 Storage Capacity:9,000 PLUs  
 Printing Type: Thermal Printing  
 Interface: USB,Ethernet  
 Various report printout support, including annual report, monthly report, daily report, single item report, clerk report.  
 Power Input: AC110-240V 50/60Hz, 0.5A



## LS-301

Size: 380\*410\*510mm  
 Capacity: 6kg, 15kg, 30kg  
 Resolution: 1g/2g, 2g/5g, 5g/10g  
 Hotkeys:48;Function Keys:35  
 Thermal Paper:φ50X57mm  
 Density:8dot/mm;Width:48mm  
 Speed:100mm/s  
 Printer Head Life:80km  
 Display: Dual side 5" color TFT Display  
 Storage Capacity:9,000 PLUs  
 Printing Type: Thermal Printing  
 Interface: USB,Ethernet  
 Various report printout support, including annual report, monthly report, daily report, single item report, clerk report.  
 Power Input: AC110-240V 50/60Hz, 0.5A



## LS-ADCF

## CRS-A18T5



Size: 380\*260\*580mm  
 Capacity:3kg, 6kg, 15kg, 30kg  
 Resolution:0.1/0.2/0.5g, 0.2/0.5/1g,2g/5g,5g/10g  
 Hot keys:48; Function keys:25  
 Thermal paper :Width≤57mm;Diameter≤80mm  
 Printing Density:8dot/mm;Width:48mm  
 Speed:00mm/s  
 Printer Head Life:80km  
 Display: 5" Color TFT  
 Both in vendor's and buyer's side.  
 Storage Capacity:9,000 PLUs  
 Printing Type: Thermal Printing  
 Interface: USB,Ethernet  
 Various report printout support, including annual report, monthly report, daily report, single item report, clerk report.  
 Power Input: AC110-240V 50/60Hz, 0.5A



## LS-S+



Product size:398\*500\*575mm  
 Pan size: 380\*260mm  
 Capacity: 3kg, 6kg, 15kg, 30kg  
 Resolution: 0.1/0.2/0.5g, 0.2/0.5/1g, 2g/5g, 5g/10g  
 Operator display:7" color TFT  
 OS:Android  
 CPU:RK3568.quad-core up to 1.83GHZ  
 Memory:1GB/2GB RAM (Optional)  
 Storage:8GB/16GB EMMC (Optional)  
 Barcode type:EAN8、EAN13、EAN128、QR Code etc.  
 Thermal Paper:Paper width≤57mmDiameter:≤80mm  
 Printing Performance  
 Density:8dot/mm;head life:100km  
 Print speed:100mm/s (Max)  
 Print width:48mm  
 Communication interface:1\*Ethernet, 2\*USB, 1\*RS232  
 Power:DC24V2.5A  
 Keyboard  
 Hotkeys:65;Function Keys:25

Capacity:3Kg,6Kg,15Kg,30Kg  
 Resolution:0.1g/0.2g/0.5g,0.2g/0.5g/1g,2g/5g,5g/10g  
 Operator display:14inch capacitive touch screen.  
 Touch screen type:Capacity touch screen  
 Customer display:14inch capacitive touch screen.  
 OS:Android  
 CPU:RK32568.quad-core up to 1.83GHZ  
 Memory:1GB/2GB RAM (Optional)  
 Storage:8GB/16GB EMMC (Optional)  
 Pan size:400\*300mm  
 Barcode type:EAN8、EAN13、EAN128、QR Code etc.  
 Label paper:Label width≤60mm  
 Printing Performance  
 Density:8dot/mm;  
 Max print size:56mmX100mm;head life:150km  
 Print speed:120mm/s (Max)  
 Print width:58mm  
 Communication interface:1\*Ethernet, 2\*USB, 1\*RS232  
 Power:DC24V2.5A



### LS-C309

RECOGNITION:  
 ●server denfication speed  
 ●The Locel recoation speed E 0.6 seconds  
 ●7 color screen with rich and dear dsplay  
 ●The Multi-language can be customized  
 ●receipt code cam be displayed during mobile payment  
 PLU:  
 ●1-9999999 PLU nu mbers can be edited  
 ●12000 itoms can be stored  
 INTERFACE:  
 ●Money box interface; Ethemot upload and download  
 ●Udisk import and axport  
 ●scan gun interface  
 PRINTING:  
 ●Print format and barcode format can be edited at will  
 ●Can print a varley of font size, 10 wode, 20 we (trauestillycode), graphics and other information  
 POWER SUPPLY:  
 ●AC and DC dual-use  
 ●Luthium batlery supply, a u charge can standby tor 15 hours  
 WATERPROOF Waterproof grade IP65



### LS-7CV

## LS-CBL-A



1. Display : 15"Touch Screen
2. Material: Aluminum Body
- 3.Capacitance Touch Screen
4. cpu: J1800 /2.0GHZ
5. Storage:DDR3 2G
6. Hard Disk : SSD MSATS 32G
- 7.System : Windows
8. Built-in: 58 Receipt Printer, RFID Card Reader(optional)



## CRS-C61L



Size: 430\*340\*460mm  
 Capacity:3/6/15/30kg  
 Division:1g/2g/5g/10g  
 Accuracy class:Class III  
 Display: Dual LCD display  
 Plate Size:320\*220mm  
 Shortcut keys:120 shortcut keys  
 External devices:Computer/Barcode Scanner/  
 Cash Box  
 Interface:RS232/USB/RJ45/RJ11  
 Function: Weighing, pricing, printing, zero setting,  
 Tare, cleaning, etc  
 Print: Print receipt paper  
 Advantages: Main board isolately sealed design  
 Power Supply:AC 100-240V/DC 6V/Rechargeable  
 Battery

Size:340\*430\*470mm  
 Capacity: 3/6/15/30kg  
 Division:1g/2g/5g/10g  
 Accuracy class:Class III  
 Display: Dual LCD display  
 Plate Size:320\*220mm  
 Shortcut keys: 120 shortcut keys  
 External devices: Computer/Barcode Scanner/  
 Cash Box  
 Interface:RS232/USB/RJ45/RJ11  
 Advantages: Main board isolately sealed design  
 Function: Weighing, pricing, printing, zero setting,  
 Tare, cleaning, etc  
 Print: Print receipt paper  
 Power Supply: AC 100-240V/DC 6V/Rechargeable  
 Battery



## CRS-C62L

Size: 365\*465\*480mm  
 Capacity:3/6/15/30kg  
 Division:1g/2g/5g/10g  
 Accuracy class:Class III  
 Display: Dual LCD display  
 Plate Size:350\*260mm  
 Shortcut keys:180 shortcut keys  
 External devices: Computer/Barcode Scanner/  
 Cash Box  
 Interface:RS232/USB/RJ45/RJ11  
 Advantages: Main board isolately sealed design  
 Function: Weighing, pricing, printing, zero setting,  
 Tare, cleaning, etc  
 Print: Print receipt paper  
 Power Supply: AC 100-240V/DC 6V/Rechargeable  
 Battery



## CRS-C63L

## TP-30D



Size:367\*410\*115mm  
 Capacity: 6/15kg or 15/30kg  
 Resolution(e): 2/5g or 5/10g  
 Precision:1/3000  
 Display Double LED display: 5 digits weight,  
 5 digits unit price, 6 digits total price  
 Storage capacity: 1000 PLUS  
 Keyboard: 25 function keys, 35×2 hotkeys  
 Ports:1×PS/2,1×USB,1×U-DISK,  
 1×CASHDRAWER  
 Printing type Thermal printing  
 Printing speed: 60mm/s  
 Paper roll Printing width:48mm  
 paper roll:57.5±0.5mm x Φ50mm  
 Built-in battery 6V/4AH  
 Power Adapter Input: AC100-240V, 50/60Hz  
 Output: DC7.5V/3A



## WBS-C151D



Dimensions:110\*150\*122 mm  
 Image Sensor:640 \* 480 CMOS  
 Light Source:4PCS WHITE LED  
 Symbolgies  
 2D:PDF417,Data Matrix,QRCode,Micro QR  
 1D:Code 128,UCC/EAN-128,AIM 128,EAN-8,EAN-13,ISSN,ISBN,UPC-E,UPC-A,Interleaved 2 of 5,ITF-14,Matrix 2 of 5(European Matrix 2 of 5),Industrial 2 of 5,Standard 2 of 5,Code 39,Codabar,Code 93,Code 11,MSI-Plessey,RSS-14,RSS-Limited,RSS-Expand etc.  
 Resolution:1D≥5mil,2D≥10mil  
 DEPTH OF FIELD  
 EAN13:20mm-200mm (13mil)  
 Code 39:10mm-100mm (5mil)  
 QR Code:5mm-180mm (15mil)  
 Payment Code(Phoe):20mm-450mm  
 PCS:10%  
 Inout Voltage:5VDC±10%  
 CURRENT  
 Operating:210mA±10mA  
 Standby:130±5mA  
 Operating Temperature:0°C ~ 45°C  
 Storage Temperture:-20°C ~ 60°C  
 Humidity:5%~90% (no-condensing)  
 Interface:USB-HID,USB-VCOM,UART(Optional)  
 Working Mode:Trigger mode,Auto-sensor,Continuous scan



Dimensions:110\*150\*122 mm  
 Image Sensor:640 \* 480 CMOS  
 Light Source:650nm ±10nm visible laser diode  
 Scan Depth of Field:up to 230mm @ 13mil  
 Symbolgies  
 2D:PDF417,Data Matrix,QRCode,Micro QR  
 1D:Code 128,UCC/EAN-128,AIM 128,EAN-8,EAN-13,ISSN,ISBN,UPC-E,UPC-A,Interleaved 2 of 5,ITF-14,Matrix 2 of 5(European Matrix 2 of 5),Industrial 2 of 5,Standard 2 of 5,Code 39,Codabar,Code 93,Code 11,MSI-Plessey,RSS-14,RSS-Limited,RSS-Expand etc.  
 Resolution:5mil  
 DEPTH OF FIELD  
 EAN13:20mm-230mm (13mil)  
 Code 39:10mm-100mm (5mil)  
 QR Code:5mm-180mm (15mil)  
 Payment Code(Phoe):20mm-450mm  
 PCS:10%  
 Power:Input: 5VDC Current max 340mA  
 CURRENT  
 Operating:210mA±10mA  
 Standby:130±5mA  
 Operating Temperature:0°C ~ 45°C  
 Storage Temperture:-20°C ~ 60°C  
 Humidity:5%~90% (no-condensing)  
 Interface:USB-HID, USB-UART, PS / 2, RS232  
 Shock Resistance:1.0M FREE FALL TEST



## WBS-C132D

# CASHIER EXTERNAL EQUIPMENT >>



## LS-405A

Dimensions 405\*420\*100 mm  
 Material of Housing Thick gauge cold rolled steel & SECC  
 Color: black,white  
 Material of cash tray High impact ABS plastic cash till  
 Currency Layout 5 bill with metal wire clips 8 coin adjustable sections  
 Drawer Front one media slot  
 Drawer Lock 3-Position lock, emergency switch at the bottom  
 Power: 12V/24V



Dimensions 405\*410\*110 mm  
 Material of Housing Thick gauge cold rolled steel & SECC  
 Color white/black/Ivory white  
 Material of cash tray High impact ABS plastic cash till  
 Currency Layout 5 bill with metal wire clips 3 coin adjustable sections, Extra wide check slot  
 Drawer Front one media slot  
 Drawer Lock 3-Position lock, emergency switch at the bottom  
 Interface RJ11 (Connects to receipt printer), option: USB  
 Power: 12V/24V(optional)

## LS-400AD

## PCS-C151

Products Name:POS comminication scale  
 Dimension:394\*355\*55 mm  
 Platter Size: 394\*309 mm  
 Display:5Bit 8Byte LCD  
 Capacity:6/15kg, 15/30kg  
 Minimum division value:2g/5g, 5g/10g  
 Internal resolution:1/3000  
 Maximum tare weight:-5.998kg, -14.995kg  
 Minimum weight:40g,100g  
 Material:ABS+PS+Stainless Steel  
 Button:function key, peeling, zeroing  
 Interface:RS232 communication + USB Micro power  
 Operating temperature and humidity:0-40°C 5%~85%R.H  
 Power Supply:DC 3.7V 2600mA



Dimensions:158\*65\*88 mm  
 Light Source:650nm±10% VLD,< 20mW  
 Scan Width:0-550mm (1.0mmDensity barcode test values)  
 Scan Depth of Field:Up to 70°down to70°,right to 70°left to 70°  
 Contrast:>=30%  
 Decoding rate:200 / sec  
 Bit Error Rate:1 / 8million  
 UART: Baud rate1200-115200bps  
 Voltage DC: 3.5-5.5V  
 Inference:USB-HID: Support USB1.1the above,Support



## WBS-C122D

## CRS-C71T

10.1" LED Capacitive Touch Screen  
 80mm(3") Thermal Printer  
 Customer Display LCD (20mm\*2lines)  
 OS: Windows or Android  
 Display: 10.1" IPS, 250 nits, 1280\*800Pixel  
 Touch: Capacitive Touch  
 WIFI  
 Optional: RFID Card Reader  
 2D Barcode Scanner  
 Magnetic Card Reader(1 2 3 tracks)  
 Color: Black  
 Dimension: 282\*305\*126(W\*D\*H:mm)  
 CPU:  
 RAM Memory: 2GB, up to 8GB, 2GB DDR3(Support 4GB)  
 OS Support: Linux, Windows 7 8 10..., Anderoid 7.1  
 SSD or HDD Storage: Msata: 32/64/128 Inter brand, 8GB(16/32GB)Optional-Android  
 Printer: 80mm Thermal Rcerpt Printer  
 Compliance: FCC/CE/Rohs  
 Tilt Anle: 30°  
 Optional: Second display LCD(20mm\*2 Lines), WIFI/Bluetooth, MSR/4G WCDMA, RFID card reader/NFC, 2D barcode scanner(alipay,wechat pay apple pay), Battery:6000mAh  
 Interface: 1\*VGA port,4\*USB 2.0(External),4\*USB 2.0(Internal),1\*RS232, 1\*12V DC In, 1\*RJ-45 Giga LAN Support, 1\*HDMI, 1\*Audio Line Out, 1\*MIC In, 1\*RJ11  
 Power Input: 12V DC,5A(External Adaptor: 100-240V AC,50/60HZ)



## LS609G

1.CPU:Intel Celeron (Optional)  
 2.RAM: 4GB,8GB (Optional)  
 3.SSD:32GB,64GB,128GB (Optional)  
 4.Material: ABS Plastic  
 5.Touch Screen: Capacitive screen  
 6.Resolution: 1024\*768  
 7.Size:15 inch LED non- flat touch screen+8 characters" customer display  
 8.Case color: Black  
 9.Interface: USB 6; 1 network port; COM\*1: VGA\*1 power port\*1  
 10.Power supply: 12V-5A  
 Size:42\*28\*43CM

Color:Black  
 Aspect Ratio:4:3  
 Type:Capacitive  
 Interface Type:usb, VGA  
 Display area:245\*285mm  
 Standard Resolution:1024\*768  
 Number of Colors:16.2M  
 Brightness:300cd/m2  
 Response time:5ms  
 Contrase ratio:450:1  
 Video input format:(analog) RGB  
 Frequency:30~80KHz/60~75Hz  
 Panel size:15 inch TFT-LCD Touch Screen Monitor  
 Power supply:External Power Supply:100 to 240V (DC 12V)





## ▶ Fuzhou Lucky Star Co.,Ltd.

Lucky Star has a very professional team for researching and designing new products. not only do ODM products. But also welcome your OEM project. Our team has rich experiences in opening new mould for your ODM products. So just let us know your requirements. We will be happy to work together with you.



## COMPANY PROFILE

Fuzhou Lucky Star Co., Ltd has been manufacturing and exporting different kinds of scales over 20 years.

Lucky Star is an ISO 9001:2008-certified manufacturer, we have full range of product lines, From industrial scales to consumer scales. Such as Precision balance, Weighing scales, Counting scales, Bench scales, Price computing scales, Shipping scales, Kitchen scales, Personal scales and Portable luggage scales...etc. We can meet all your weighing requirements.

Now Lucky Star has around 300 employees, can produce over 50,000pcs electronic scales each month. Our export markets cover Europe, North and South America and Asia. Hope you would be our next clients.