

PD SERIES 650VA-1000VA

Desktop Line Interactive UPS PD Series

PD Series 650VA - 1000VA (1ph in/ 1ph out)



Key Features:

- Intelligent CPU Control
- Auto restart while AC is recovering
- Boost and buck AVR for voltage stabilization
- Cold start function
- Off-mode charging
- Optional USB or RJ45 port
- Optional LED or LCD panels
- The UPS has mute function when the UPS in battery mode
- The LCD display can be off when the UPS in AC/Battery mode

Applications:

- Personal Computer
- Printer
- POS(Point of sales)Terminals
- Security System
- Fax Machine
- Modem, Router

Shenzhen UPSen Electronic CO.,Ltd.

www.upsen.net

Technical Specification:

Model	PD650	PD850	PD1000
Capacity	650VA / 360W	850VA / 480W	1000VA / 510W
INPUT			
Voltage	110V/120 VAC or 220/230/240 VAC		
Voltage Range	81-145VAC or 145-275VAC		
Frequency	50 / 60 Hz (Auto Sensing)		
OUTPUT			
Voltage	110/120 VAC or 220/230/240 VAC		
Voltage Range	±10%		
Frequency Range(Battery Mode)	50 / 60 ±1Hz		
Transfer Time	4 - 6ms		
Wave Form(Battery Mode)	Simulated Sine Wave		
BATTERY			
Battery Model & Quantity	12V/7AH * 1PC	12V/9AH * 1PC	12V/7AH * 1 PCS
Charge Time	8 hours recover to 90%capacity		
PROTECTION			
Full Protection	Discharge, Short circuit and overload protection		
INDICATORS			
LCD Display	AC mode, Battery mode, Load level, Battery level, Input voltage, Output voltage, Overload and low battery		
ALARM			
Battery Mode	Sounding every 4 seconds		
Low Battery	Sounding every second		
Overload	Sounding every second		
Fault	Continuously sounding		
INTERFACE			
Interface	Support windows XP/Vista, Windows 7/8, Linux, Unix, and MAC		
Communication Interface	USB / RJ45 Port(Optional)		
ENVIRONMENT			
Humidity	0-90%RH @0-40C(Non-condensing)		
Noise Level	Less than 40dB		
Dimension(mm)	115*115*40		
N.W.(kg)	5.8	6	6
Note : Product Specification are Subject to Change Without Further Notice.			