

# HD SERIES 600VA / 1000VA

## High Frequency Desktop UPS HD Series

HD Series 600VA / 1000VA(1ph in/ 1ph out)



### Key Features:

- Off-mode Charging
- Supports 110VAC / 220VAC voltage input
- LED Display
- At half-charge, the standby time can reach 4 minutes.
- USB Output: 5V / 2A \* 2 pcs



# Technical Specification:

Model	HD 600	HD-LV 600	HD 1000	HD-LV 1000
Rated Power	600VA / 360W		1000VA / 500W	
Power Factor	0.6		0.5	
<b>BATTERY</b>				
Discharge Time	300 watts for 4 minutes			
Battery Capacity	12V 4.5Ah Lead acid battery		12V 5Ah Lead acid battery	
Recharge Time	8 hours			
<b>INPUT</b>				
AC Input Voltage	220VAC	110VAC	220VAC	110VAC
AC Input Voltage Range	175 - 260VAC	90 - 130VAC	175 - 260VAC	90 - 130VAC
AC Input Frequency	50 / 60Hz			
<b>OUTPUT</b>				
AC Output Voltage Range	90 - 130VAC	90 - 130VAC	90 - 130VAC	90 - 130VAC
AC Output Voltage (Battery Mode)	225 ± 5VAC	115 ± 5VAC	225 ± 5VAC	115 ± 5VAC
AC Output Frequency	50 / 60Hz			
Output Waveform	PWM (batt.mode)			
USB Output	5V / 2A* 2			
Output Sockets	4 x European or 8 x American standard backup socket or bypass for option			
<b>ENVIRONMENT</b>				
Environment of Performance	Temperature 0°C - 40°C, Humidity 20% - 90%			
Noise Level	≤ 40dB (1m)			
<b>MACHINE SPECIFICATIONS</b>				
Dimension (L*W*H) (mm)	257*170*108			
Net Weight (Kg)	3			
*Product Specifications are Subject to Change Without Notice.				