

Pacific Star Plastic Case 650VA - 1500VA

Line Interactive UPS Technical Specification

PS650 - PS1500 (1ph in / 1ph out)



Key Features:

- Intelligent CPU Control
- Auto restart while AC is recovering
- Boost and buck AVR for voltage stabilization
- Cold start function
- Off-mode charging
- Optional USB or RJ45 port
- Optional LED or LCD panels
- The UPS has mute function when the UPS in battery mode
- The LCD display can be off when the UPS in AC/Battery mode

Applications:

- Personal Computer
- Printer
- POS(Point of sales)Terminals
- Security System
- Fax Machine
- Modem, Router

Shenzhen UPSEN Electronic CO.,Ltd.
www.upsen.net

Technical Specification:

Model	PS500	PS650	PS800	PS1000	PS1500
Capacity	500VA / 300W	650VA / 390W	800VA / 480W	1000VA / 600W	1500VA / 900W
INPUT					
Voltage	110V / 120 VAC or 220 / 230 / 240 VAC				
Voltage Range	81-145VAC or 145-275VAC				
Frequency	50 / 60 Hz (Auto Sensing)				
OUTPUT					
Voltage	110V / 120 VAC or 220 / 230 / 240 VAC				
Voltage Range	±10%				
Frequency Range(Battery Mode)	50 / 60 ±1Hz				
Transfer Time	4 - 6ms				
Wave Form(Battery Mode)	Simulated Sine Wave				
BATTERY					
Battery Model & Quantity	12V/4.5AH * 1PC	12V/7AH * 1PC	12V/9AH * 1PC	12V/7AH * 2 PCS	12V/9AH * 2 PCS
Charge Time	8 hours recover to 90%capacity				
PROTECTION					
Full Protection	Discharge, Short circuit and overload protection				
INDICATORS					
LCD Display	AC mode, Battery mode, Load level, Battery level, Input voltage, Output voltage, Overload and low battery				
Line Mode	Green lighting				
Battery Mode	Red lighting				
Battery Charge Mode	Yellow lighting				
ALARM					
Battery Mode	Sounding every 4 seconds				
Low Battery	Sounding every second				
Overload	Sounding every second				
Fault	Continuously sounding				
INTERFACE					
Interface	Support windows XP/Vista, Windows 7/8, Linux, Unix, and MAC				
Communication Interface	USB / RJ45 Port(Optional)				
ENVIRONMENT					
Humidity	0-90%RH @0-40°C (Non-condensing)				
Noise Level	Less than 40dB				
Dimension(mm)	310*95*130	320*95*130	315*95*130	315*120*170	315*120*170
N.W.(kg)	3.9	5.1	5.6	9.8	11.8
Note : Product Specification are Subject to Change Without Further Notice.					