

1T-30T Flake Ice Machine

1T-30T 片冰机



Taizhou S&J Trading Co., Ltd.
 Zhejiang Litan Industrial Co.,Ltd.
 web: www.forefrigeration.com
 e-mail: ice@forefrigeration.com

技术参数 Technical Data

The industrial flake ice machine produces thin, smooth flake ice with a large contact area and low temperature. This unique ice form rapidly cools down the materials it contacts, achieving ideal preservation and chilling effects. The equipment is easy to operate, highly cost-effective, and offers an excellent return on investment.

Model	Daily Output	Refrigerating Capacity	Total Power	Compressor Power	Refrigerant	Cooling Way	Operating Weight	Dimension of M.unit	Dimension with bin
SDAF-1T	1T	5.8kw	4.6 kw	3.4 kw	R404a	Air	330kg	1370*800*900mm	1370*1030*2035mm
SDAF-1.5T	1.5T	8.6 kw	6.8 kw	5.3kw	R404a	Air	380 kg	1410*900*1000mm	1410*1320*2200mm
SDAF-2T	2T	12.3 kw	8.47 kw	7.0kw	R404a	Air	480 kg	1500*1000*1080mm	1500*1380*2280mm
SDAF-3T	3T	18.3 kw	11.6 kw	10.2 kw	R404a	Air	600 kg	1670*1200*1250mm	1670*1610*2550mm
SDAF-5T	5T	30.9 kw	19.2 kw	16kw	R404a	Air	960kg	1890*1500*1400mm	/
SDWF-10T	10T	67.4kw	38.2 kw	31.6kw	R404a/R22	Water	2250 kg	2500*1900*1830mm	/
SDWF-15T	15T	96.9 kw	48.5kw	41.9 kw	R404a/R22	Water	3650kg	2500*1900*2350mm	/
SDWF-20T	20T	120.6 kw	59.5 kw	50.2kw	R404a/R22	Water	4410kg	3300*2100*2100mm	/
SDWF-25T	25T	157.3kw	77.6kw	64.9 kw	R404a/R22	Water	4960kg	3300*2100*2360mm	/
SDWF-30T	30T	191 kw	90.2 kw	77.5 kw	R404a/R22	Water	5380 kg	4100*2100*2640mm	/

标准运行工况 Standard Working Conditions

环境温度(Ambient Temp): 25°C 电源(Power Supply): 3P/380V/50Hz or Customization
 进水温度(Inlet Water): 18°C 给水压力(Water Inlet Pressure): 0.1MPa~0.5MPa
 冰片厚度(Ice thickness):1.5~2.2mm