

Water based isocyanate hardener/curing agent DOXU-5380

Product Features :

This product is an anionic water dispersible isocyanate curing agent based on HDI, with high hardness, fast drying speed, excellent hand mixing performance, certain self extinction effect, and excellent chemical resistance.

Application scope:

Low gloss water-based polyurethane curing agents, industrial coatings, floor paints, and other fields.

Product Parameters :

Product Indicator	Product parameter	Unit	Test Method
Appearance	Water white to slightly yellow transparent mucus	/	GB/T 1721-2008
(Pt Co) color number	≤100	/	GB/T 9282.1-2008
NCO content	17.4±0.5	%	Di-n-butylamine method
Free HDI	≤0.24	%	GB/T 18446-2009
Solid content	80.0±2.0	%	GB/T 1725-2007
Viscosity (25 °)	130±50	mPa·s	GB/T 9751.1-2008

Instructions for Use:

1. This product can be diluted with amino ester grade solvents such as PMA (propylene glycol methyl ether acetate), PGDA (propylene glycol diacetate), PC (propylene carbonate), etc.
2. This product is extremely sensitive to air humidity. When opening or small packaging, please be careful not to let water vapor enter. After use, seal it immediately or use it up as soon as possible.

Packaging and Storage:

1. 10KG, 20KG, 60KG, 200KG iron drums or customized by customers.
2. This product must be stored in a cool and dry environment, avoiding outdoor placement. In sealed packaging, the shelf life is 12 months.

Disclaimers:

This product manual is written by our company using advanced testing equipment based on actual testing and production experience. However, the differences in working environment and material coordination during product application are beyond our company's control. Therefore, our company recommends that users conduct tests, experiments, and trials according to their actual needs and purposes before using this product. Our company does not assume any losses or risks for users using this product due to this manual.