

# ASP PRODUCTS INTRODUCTION

Guarantee	
Power Output	25 years power output guarantee for 90% of nominal output during first 10 years and 80% over 25 years.
materials and workmanship	10 years

  

Temperature Coefficients		
Pm=-0.214%/°C	Voc=-0.321%/°C	Isc=0.060%/°C

Tested under STC:1000W/m<sup>2</sup>,AM1.5, 25°C

## STANDARD THIN FILM MODULE

### Product Specification

Module Dimension	Weight
L1200*W600*D6.8mm	11.8kg

### ASP-S1



#### ASP-S1

Specification	ASP-S1-80	ASP-S1-85
Nominal Power (Pm)	80W	85W
Open Circuit Voltage (Voc)	118.9V	120.5V
Short Circuit Current (Isc)	0.95A	0.98A
Voltage at Max. Power(Vm)	94.1V	96.6V
Current at Max. Power (Im)	0.85A	0.88A

TUV Certified: ASP-S1-75 ASP-S1-77 UL Certified: ASP-S1-80 ASP-S1-85

### ASP-S4



#### ASP-S4

Specification	ASP-S4-77
Nominal Power (Pm)	77W
Open Circuit Voltage (Voc)	28V
Short Circuit Current (Isc)	3.91A
Voltage at Max. Power(Vm)	21V
Current at Max. Power (Im)	3.66A

Tested under STC: 1000W/m<sup>2</sup>, AM1.5, 25°C

