


PWSOLAR

725W Bifacial Topcon

MONOCRYSTALLINE MODULE



ADVANCED PERFORMANCE & PROVEN ADVANTAGES

- ◆ High module conversion efficiency up to 23.34% by using innovative Half-cell design and Multi-busbar(MBB) cell technology.
- ◆ Low temperature coefficient and excellent performance under high temperature and low light conditions.
- ◆ Robust aluminum frame ensures the modules to withstand wind loads up to 2400Pa and snow loads up to 5400Pa.
- ◆ High reliability against extreme environmental conditions (passing salt mist, ammonia and hail tests).
- ◆ Potential induced degradation(PID) resistance.
- ◆ Power tolerance of $\pm 3\%$.

ELECTRICAL CHARACTERISTICS AT STC

Model	PWDG725Wp-132M
Maximum Power (P_{max})	725W
Power Tolerance	$\pm 3\%$
Open Circuit Voltage(VOC)	48.90V
Short Circuit Current(ISC)	18.74A
Voltage at Nominal Power (V_{mp})	41.00V
Current at Nominal Power (I_{mp})	17.69A
Size of Module	2384 x 1303 x 30mm
Standard Test condition	Irradiance: 1000W/M ² Temp: 25°C , & AM :1.5G spectrum
Maximum system voltage	1000VDC/1500VDC
Operating temperature	- 40°C to +85°C
Module Efficiency	23.34%

ELECTRICAL CHARACTERISTICS AT STC

NOCT	45 $\pm$ 2°C
Voltage temperature coefficient(Voc)	-0.330%/°C
Current temperature coefficient I sc)	+0.058%/°C
Power temperature coefficient(Pmpp)	-0.400%/°C
Minimum power tolerance	$\pm$ 10%
NOCT	45 $\pm$ 2°C



Room 101, No. 5 Building, No. 9 Haikou Road, Shinan District, Qingdao, China 266000



0086 532 85872070



0086 155 6392 6558



0086 138 6421 6496



sales@pwsolarpower.com



info@pwsolarpower.com



www.pwsolarpower.com

MECHANICAL CHARACTERISTICS

Cell Type	Monocrystalline (210*105)
Number of cell	132pcs (6 x 22)
Size of Module	2384 x 1303 x 30mm
Weight	About 30.60kgs
Front Cover	3.2mm tempered glass with AR coating
Frame	Anodized aluminum alloy
Junction Box	IP68, 3 diodes
Cable	4mm ² (0.006inches ²),Positive: 300mm, Negative: 200mm Length can be customized
Connector	MC4orMC4compatible
Maximum Load Capacity(Pa)	2400(wind load)/2400(snow load)

MODULE WARRANTY



12 year limited product; limited linear power warranty: 12 year 91.20% of nominal power output, 30 year 80.60% of nominal power output.
20 years product warranty; 30 years linear power output

PACKING

Standard Packing: 36pcs/Pallet Module Quantity of 20' container:240pcs Module Quantity of 40' container: 612pcs

ENGINEERING DRAWING

IV CURVES



Room 101, No. 5 Building, No. 9 Haikou Road, Shinan District, Qingdao, China 266000

0086 532 85872070 0086 155 6392 6558 0086 138 6421 6496

sales@pwsolarpower.com info@pwsolarpower.com www.pwsolarpower.com

Specifications in this datasheet are subject to change without prior notice